

Ouick Start Guide for FreeStyle Libre 2 Reader





Refer to your User's Manual for full System instructions and information.

Sensor

Applicator

Setup Overview

Assemble and Apply Sensor to your body



Start new Sensor with Reader



Check your glucose whenever you want for up to 14 days



Assemble and Apply Sensor to the back of your upper arm

Pack

STEP 1



Select site on back of upper arm. Do not use other sites as these may result in inaccurate glucose readings. Note: Avoid scars, moles, stretch marks, lumps, and insulin injection sites. To prevent skin irritation, rotate sites between applications.

STEP 2

Codes on labels must match



Wash site using a plain soap, dry, and then clean with alcohol wipe. Allow site to air dry before proceeding.

STEP 3





Peel lid completely off Sensor Pack. Unscrew cap from Sensor Applicator.

CAUTION: Sensor codes must match on Sensor Pack and Sensor Applicator or glucose readings will be incorrect.



STEP 4



Line up dark mark on Sensor Applicator with dark mark on Sensor Pack. On a hard surface, press down firmly on Sensor Applicator until it comes to a stop.

STEP 5



Lift Sensor Applicator out of Sensor Pack.

STEP 6



Sensor Applicator is ready to apply Sensor.

CAUTION: Sensor Applicator now contains a needle. Do not touch inside Sensor Applicator or put it back into Sensor Pack.


STEP 7



Place Sensor Applicator over site and push down firmly to apply Sensor.

CAUTION: Do not push down on Sensor Applicator until placed over prepared site to prevent unintended results or injury.

STEP 8



Gently pull Sensor Applicator away from your body.

STEP 9



Make sure Sensor is secure. Discard used Sensor Applicator and Sensor Pack according to local regulations.



STEP 1



Press Home Button to turn on Reader.

Note: If using Reader for the first time, follow the prompts to set date and time.

STEP 2



Touch **Start New Sensor**. Hold Reader within 1.5 inches (4 cm) of Sensor to scan it.

STEP 3





Review the important information on the screen.

Sensor can be used to check your glucose after 60 minutes.

3 Check your glucose

STEP 1




Press Home Button to turn on Reader.

STEP 2



Hold Reader within 1.5 inches (4 cm) of Sensor to scan it.

STEP 3



Glucose
Trend Arrow

↑ Glucose rising quickly

☐ Glucose rising

☐ Glucose changing slowly

☐ Glucose falling

☐ Glucose falling

Reader shows your glucose reading. This includes your Current Glucose, Glucose Trend Arrow, and Glucose Graph.

Setting Alarms

The Sensor automatically communicates with the Reader and can give you glucose alarms. Alarms are on by default. To change their settings or turn alarms off, follow these steps.

IMPORTANT: Glucose alarms are an important safety feature. Please consult your health care professional before making changes.

STEP 1



Press Home Button to go to Home Screen. Touch ۞.

STEP 2





Touch **Alarms** and then touch **Change Alarm Settings**.

STEP 3

Settings
Low Glucose Alarm

Notifies you when Sensor is not communicating with Reader and that you are not getting Low or High Glucose Alarms.

Notifies you when glucose is below the level you set.

Select and set your alarms. Touch **done** to save.

High Glucose Alarm

Signal Loss Alarm

Using Alarms

You must scan your Sensor to see your glucose reading.





Touch **Dismiss Alarm & Check Glucose** or press the Home Button to dismiss alarm and check your glucose.



Touch **No** to dismiss alarm.

Touch **Yes** or press the Home Button to dismiss alarm and scan the Sensor.



Notifies you when glucose is

above the level you set.

When any alarm is on, sound/vibration and signal status display on the Home Screen.

Symbol	What it means
■)}	Sound and Vibration ON
×	Sound and Vibration OFF
((•))	Sensor communicating with Reader
(%)	Sensor not communicating with Reader

Refer to User's Manual for additional symbols.

