

MASSEY FERGUSON



24.8 HP SPECIFICATIONS

1526 Compact Tractor



MASSEY FERGUSON

1526

FROM MASSEY FERGUSON

A world of experience. Working with you.



BACK BY POPULAR DEMAND.

They say your Massey Ferguson® will be the last tractor you'll ever need. If you take a look around, you'll see why. Massey Ferguson tractors are everywhere. Brand new ones — and classics from the 1950s, '60s and '70s — that are still getting the job done today.

You wanted a small tractor with a mid PTO for more application versatility. We've responded by bringing back a versatile workhorse, the MF1526 compact tractor. This one's built especially for a new generation of landowners and hobby farmers who want a tractor that's as hardworking and no-nonsense as they are.



YOU CAN DO MORE WITH THIS TRACTOR. BECAUSE IT'S MADE TO HANDLE MORE.

VERSATILITY – Truly a versatile workhorse — only better.

- **Mid PTO** – A rear and mid PTO give you more versatility on operations and implements. The rear PTO and mid PTO levers allow for independent or simultaneous operation of both drives. The electro-hydraulic PTO clutch features push-button control, so you can engage or disengage both on the go — no clutching, no reaching for levers.
- **Transmission** – (HST with Cruise Control) A three-range hydrostatic transmission with intuitive operation means faster range-gear selection, while separate forward and reverse foot pedals on the uncluttered platform give precise control of speed and direction.
- **Loader** – Attaching the bucket and changing it is simple, and the 1526 offers an optional L100E quick attach.

STABILITY – You want a more stable tractor that lets you work harder, doing more things in more places. We get that.

- **Frame** – A larger frame than other models in its category gives more stability and allows for more confident operation in numerous applications.
- **Sturdy** – Compare the tractor weight of the 1526 with that of the competition; these tractors have an excellent power-to-weight ratio.

COMFORT – We start with a simple idea: the more comfortable you are in your tractor, the more work you can get done.

- **Operator station** – The semi-flat platform gives you more legroom and makes entering and exiting the operator station easier.
- **Dual hydrostatic control pedals** – Pedals are positioned to provide a more natural seating position during directional changes.
- **Seatbelt** – Seat-mounted, retractable seatbelt enhances comfort.

EASE OF USE – The work you do is hard. Driving your tractor is supposed to be the easy part. With the return of the MF1526, it is.

- **Brake location** – The brake pedal has been moved to the left side of the platform for quicker use of the steering brake, allowing you to work more efficiently.
- **Instrument panel** – Features a straightforward design that lets you read all tractor functions with a quick glance.
- **Light switch** – The light combination switch makes using headlights and turn signals effortless.
- **Serviceability** – A simple release hood latch makes preventative maintenance, like checking filters and fluid levels, easy.



We've been making tractors for a long time, and we believe in what we make. That's why we offer a 5-year powertrain warranty. (Feel free to ask those other guys how long their warranties are.)

masseyferguson.us

Ideal for loader work, mowing and snow blowing — with the ability to handle box blade work, tilling, post hole digging and numerous other jobs.





MASSEY FERGUSON

masseyferguson.us

SPECIFICATIONS*

MODEL	1526
ENGINE	
Gross engine HP (kW)	24.8 (18.5)
PTO HP HST (kW)	20.1 (15)
Rated engine speed	2,600
Type	3-cylinder diesel
Displacement in. ³ (L)	91.41 (1.5)
Cooling system	Liquid cooled
Fuel tank capacity gal. (L)	7.1 (27)
TRANSMISSION	
Hydrostatic w/ cruise	3 range
Rear brakes	Wet disc
PTO	
Rear PTO type	Independent 540 RPM
Control	Electro-hydraulic
Mid PTO type – Opt.	2,000 RPM
HYDRAULICS	
Type of system	Open center
Flow at remotes gpm (LPM)	5.5 (20.8)
Power steering flow gpm (LPM)	3.2 (12.3)
Total flow gpm (LPM)	8.7 (32.9)
Factory-installed joystick	Opt.
3-POINT HITCH	
ASAE hitch	Cat. 1
Controls	Position
Rate of drop control	Std.
Lift capacity @ hitch point lbs. (kg.)	1,322 (600)
Lift capacity @ 24" behind lbs. (kg.)	992 (450)

MODEL	1526
OPERATOR AREA	
Platform type	Semi-flat ISO mounted
ROPS	Foldable
Seat type	Suspended with retractable seatbelt
DIMENSIONS WITH AG TIRES	
Overall length in. (mm)	111 (2,820)
Min. overall width in. (mm)	49.2 (1,250)
Max. height over ROPS in. (mm)	95.5 (2,425)
Ground clearance in. (mm)	11 (280)
Wheelbase in. (mm)	61.4
Shipping weight platform lbs. (kg.)	1,873 (850)
LOADER	
Max. lift height @ pivot pin in. (mm)	90.5 (2,299)
Dump angle @ max. height degrees	43
Clearance with bucket dumped 45 degrees in. (mm)	71 (1,803)
Lift capacity to full height @ 19.5 forward lbs. (kg.)	820 (372)
Breakout force @ bucket edge lbs. (N)	1,270 (5,649)
Bucket options (in.)	54, 60
MID-MOUNT MOWER	
Discharge type	Right side discharge
Cutting width in. (mm)	60 (1,524)
Number of blades	3

*Specifications are manufacturer's estimates at time of publication and are subject to change without prior notification.



©2016 AGCO Corporation. Massey Ferguson is a worldwide brand of AGCO Corporation. AGCO and Massey Ferguson are trademarks of AGCO®. All rights reserved. MF16S002CR

AGCO may at any time, and from time to time, for technical or other necessary reasons, modify any of the data, specifications or warranty of the products described herein. Some equipment shown may be optional. Attention: photographs in this publication may show protective shields and guards open or removed for the purposes of illustration. Be certain all shields and guards are in place during operation.

AGCO is a premier manufacturer of agricultural equipment, providing high-tech solutions for professional farmers feeding the world. The company is dedicated to delivering superior customer service, innovation and quality. AGCO products are distributed in more than 140 countries worldwide.