

HYDRAULIC HOSE

January 2016 • Prices are subject to change without notice

| Hydraulic Hose 2 |
|--|
| General Purpose Hose7 |
| Special Application / Truck Hose10 |
| Thermoplastic Hose12 |
| Braided Hose Fittings14 |
| W Series Hose Fittings21 |
| 3 Series Thermoplastic Hose Fittings28 |
| T Series PTFE Hose Fittings |
| JJ Series Hose Fittings32 |
| Suction Hose Fittings |
| Steel Hose Barbs35 |
| SAE 100R1AT Field-Attachable Hose Fittings36 |
| SAE 100R2AT Field-Attachable Hose Fittings36 |
| SAE 100R5 Field-Attachable Hose Fittings37 |
| SAE 100R6 Field-Attachable Hose Fittings |
| SAE 100R7 Field-Attachable Hose Fittings |
| SAE 100R14A Field-Attachable Hose Fittings39 |
| Push-Lock Hose Barbs40 |

| Brass Hose Barbs42 |
|---|
| Brass Hose Ferrules and Clamps |
| SAE 100R5 Truck Hose Fittings |
| Beadlock Air Conditioning Hose Fittings47 |
| Air Brake Hose Fittings48 |
| SAE 30R7 Fuel Line Hose Barbs |
| Hydraulic Quick Disconnects50 |
| Hydraulic Pumps & Accessories55 |
| Steel Grease Fittings |
| Cam & Groove Hose Fittings59 |
| Hose Protection62 |
| Reelcraft [®] Hose Reels64 |
| Hose Cutting and Cleaning Tools65 |
| Hydraulic Hose Crimpers66 |
| Hose Crimpers and Swaging Tools |
| Crimp Specifications70 |
| Fluid Port and Connector Thread Sizes75 |
| |



DiscountHydraulicHose.com is brought to you by:

Hydraulax Products Inc. 5606 Tulip Street PO Box 9580 Philadelphia, PA 19124 USA Sales/Customer Service orders@discounthydraulichose.com 800-535-1302

Technical Support support@discounthydraulichose.com 800-535-1302

Outside the USA, call 1-215-744-2828

LIMITED WARRANTY: For ninety days after the date of purchase, Hydraulax Products Inc. warrants the products in this catalog to be free from defect in materials and workmanship when properly installed and maintained. Any claim for defects must be in writing and must be received within 90 days of the receipt of the product. Hydraulax Products Inc. must have a reasonable opportunity thereafter to examine and investigate. The customer's exclusive remedy with respect to any claim of any kind whatsoever shall be refund of the purchase price or replacement of the product at the option of Hydraulax Products Inc. In no event shall Hydraulax Products Inc. be liable for any incidental or consequential damages whatsoever.

Hydraulic Hose





Tube: oil-resistant synthetic rubber
Reinforcement: two braids of high-tensile steel wire
Cover: oil and abrasion-resistant synthetic rubber

Temperature range: -40° to +212° F

Recommended hose fittings:



Braided Hose Fittings: page 14



SAE 100R2 AT Field-Attachable Hose Fittings: page 36

R2 | High Pressure, 2-Wire

Meets all requirements of SAE 100R2 AT

Recommended for hydraulic service with petroleum and water-base fluids. No skiving required. Long-lasting cover is well suited for mobile hydraulics.

| ltem # | Inside Diameter | Outside Diameter | Maximum Operating (PSI) | Minimum Burst (PSI) | Minimum Bend Radius | Reel Length* | Reel Price (per foot) | Cut Price (per foot) |
|--------|--------------------|---------------------|-------------------------------|------------------------|---------------------------|-----------------|--------------------------|-------------------------|
| R2-04 | 1/4" | 0.59" | 5,800 | 23,200 | 4" | 500' | \$1.18 | \$1.29 |
| R2-06 | 3/8" | 0.75" | 4,785 | 19,140 | 5" | 450' | \$1.41 | \$1.55 |
| R2-08 | 1/2" | 0.88" | 4,000 | 16,000 | 7" | 320' | \$1.58 | \$1.72 |
| R2-10 | 5/8" | 0.98" | 3,625 | 14,500 | 8" | 520' | \$2.26 | \$2.43 |
| R2-12 | 3/4" | 1.16" | 3,120 | 12,480 | 91⁄2" | 400' | \$2.30 | \$2.55 |
| R2-16 | 1" | 1.50" | 2,395 | 9,580 | 12" | 200' | \$3.15 | \$3.50 |
| R2-20 | 1¼" | 1.87" | 1,815 | 7,260 | 16½" | 131' | \$10.34 | \$10.86 |
| R2-24 | 11⁄2" | 2.17" | 1,305 | 5,220 | 20" | 131' | \$12.35 | \$12.64 |
| R2-32 | 2" | 2.66" | 1,160 | 4,640 | 25" | 131' | \$15.33 | \$16.08 |

* Reel may not contain one continuous length of hose.



Tube: oil-resistant synthetic rubber **Reinforcement:** two braids of high-tensile

steel wire

Cover: synthetic rubber with the following key characteristics:

- superior abrasion resistance
- excellent ozone and UV resistance
- · weather and salt water resistance
- flame resistance according to MSHA and DSK (LOBA) specs.
- antistatic

Temperature range: -40° to +212° F

Recommended hose fittings:



Braided Hose Fittings: page 14 (up to size -12 only)



W Series Hose Fittings: page 21

HT | Hydraulax Tough[™] 2-Wire

MSHA approved

Hydraulax Tough[™] is the ideal hose for high abrasion environments. In addition to its recognised benefits of excellent resistance to ozone, UV radiation, high temperatures and salt water, it meets the special requirements of the underground coal mining industry.

Recommended for hydraulic service with petroleum and water-base fluids. No skiving required. Long-lasting tough cover is ideal for mobile hydraulics in harsh environments.

| Item # | Inside Diameter | Outside Diameter | Maximum Operating (PSI) | Minimum Burst (PSI) | Minimum Bend Radius | Reel Length* | Reel Price (per foot) | Cut Price (per foot) |
|--------|--------------------|---------------------|-------------------------------|------------------------|---------------------------|-----------------|--------------------------|-------------------------|
| HT-04 | 1/4" | 0.53" | 6,525 | 26,100 | 1.8" | 400' | \$1.76 | \$1.94 |
| HT-06 | 3/8" | 0.68" | 5,585 | 22,340 | 2.8" | 525' | \$1.99 | \$2.21 |
| HT-08 | 1/2" | 0.81" | 5,000 | 20,000 | 3.5" | 360' | \$2.49 | \$2.75 |
| HT-10 | 5/8" | 0.93" | 4,205 | 16,820 | 5.1" | N/A | N/A | \$3.98 |
| HT-12 | 3/4" | 1.09" | 4,060 | 16,240 | 6.3" | 426' | \$4.13 | \$4.57 |
| HT-16 | 1" | 1.40" | 2,900 | 11,600 | 8.3" | N/A | N/A | \$6.64 |





Tube: oil-resistant synthetic rubber
Reinforcement: two braids of high-tensile steel wire
Cover: oil and abrasion-resistant synthetic rubber

Temperature range: -40° to +212° F

Recommended hose fittings:



Braided Hose Fittings: page 14

R16 | Compact, High Pressure, 2-Wire

Meets all requirements of SAE 100R16

Recommended for hydraulic service with petroleum and water-base fluids. No skiving required. Half bend radius compared to SAE 100R2.

| ltem # | Inside Diameter | Outside Diameter | Maximum Operating (PSI) | Minimum Burst (PSI) | Minimum Bend Radius | Reel Length* | Reel Price (per foot) | Cut Price (per foot) |
|--------|--------------------|---------------------|-------------------------------|------------------------|---------------------------|-----------------|--------------------------|-------------------------|
| R16-04 | 1/4" | 0.55" | 5,800 | 23,200 | 2" | 500' | \$1.20 | \$1.27 |
| R16-06 | 3/8" | 0.67" | 4,780 | 19,120 | 21⁄2" | 450' | \$1.62 | \$1.71 |
| R16-08 | 1/2" | 0.81" | 3,980 | 15,920 | 31⁄2" | 320' | \$1.83 | \$1.90 |
| R16-10 | 5/8" | 0.93" | 3,620 | 14,480 | 4" | 520' | \$2.65 | \$2.79 |
| R16-12 | 3/4" | 1.07" | 3,110 | 12,440 | 4¾" | 400' | \$2.74 | \$2.90 |
| R16-16 | 1" | 1.37" | 2,390 | 9,560 | 6" | 200' | \$3.91 | \$4.11 |

* Reel may not contain one continuous length of hose.



 Tube: oil-resistant synthetic rubber
 Reinforcement: one braid of high-tensile steel wire (R17-04, R17-06); two braids of high-tensile steel wire (all other sizes)
 Cover: oil and abrasion-resistant synthetic rubber
 Temperature range: -40° to +212° F

Recommended hose fittings:



Braided Hose Fittings: page 14 (up to size -12 only)



W Series Hose Fittings: page 21

R17 | Compact, Constant Pressure

Meets all requirements of SAE 100R17

Recommended for hydraulic service with petroleum and water-base fluids. No skiving required. Half bend radius compared to SAE 100R2.

| ltem # | Inside Diameter | Outside Diameter | Maximum Operating (PSI) | Minimum Burst (PSI) | Minimum Bend Radius | Reel Length* | Reel Price (per foot) | Cut Price (per foot) |
|--------|--------------------|---------------------|-------------------------------|------------------------|---------------------------|-----------------|--------------------------|-------------------------|
| R17-04 | 1/4" | 0.50" | 3,000 | 12,000 | 2" | 500' | \$1.05 | \$1.11 |
| R17-06 | 3/8" | 0.66" | 3,000 | 12,000 | 21⁄2" | 500' | \$1.44 | \$1.52 |
| R17-08 | 1/2" | 0.80" | 3,000 | 12,000 | 31⁄2" | 350' | \$1.73 | \$1.83 |
| R17-10 | 5/8" | 1.00" | 3,000 | 12,000 | 4" | 520' | \$2.68 | \$2.84 |
| R17-12 | 3/4" | 1.12" | 3,000 | 12,000 | 4¾" | 400' | \$2.86 | \$3.02 |
| R17-16 | 1" | 1.48" | 3,000 | 12,000 | 6" | 200' | \$4.17 | \$4.41 |

* Reel may not contain one continuous length of hose.

Hydraulic Hose





Tube: oil-resistant synthetic rubber
Reinforcement: four spiral layers of hightensile steel wire
Cover: oil and abrasion-resistant synthetic rubber
Temperature range: -40° to +250° F

Recommended hose fittings:



W Series Hose Fittings: page 21



Meets all requirements of SAE 100R12

Recommended for hydraulic service with petroleum and water-base fluids. No skiving required. Long-lasting cover is well suited for mobile hydraulics.

| ltem # | Inside Diameter | Outside Diameter | Maximum Operating (PSI) | Minimum Burst (PSI) | Minimum Bend Radius | Price Per Foot (100 feet or more) | Price Per Foot (up to 99 feet) |
|--------|--------------------|---------------------|-------------------------------|------------------------|---------------------------|--------------------------------------|-----------------------------------|
| R12-06 | 3/8" | 0.80" | 4,000 | 16,000 | 5" | \$4.34 | \$4.55 |
| R12-08 | 1/2" | 0.94" | 4,000 | 16,000 | 7" | \$4.70 | \$4.95 |
| R12-12 | 3/4" | 1.21" | 4,000 | 16,000 | 91⁄2" | \$6.26 | \$6.58 |
| R12-16 | 1" | 1.50" | 4,000 | 16,000 | 12" | \$7.42 | \$7.79 |
| R12-20 | 11⁄4" | 1.85" | 3,000 | 12,000 | 16½" | \$14.08 | \$14.76 |
| R12-24 | 11⁄2" | 2.11" | 2,500 | 10,000 | 20" | \$16.61 | \$17.47 |
| R12-32 | 2" | 2.63" | 2,500 | 10,000 | 25" | \$25.40 | \$26.67 |



 Tube: oil-resistant synthetic rubber
 Reinforcement: four spiral layers of hightensile steel wire
 Cover: oil and abrasion-resistant synthetic rubber

Temperature range: -40° to +212° F (max. 248° F intermittent)

Recommended hose fittings:



W Series Hose Fittings: page 21 (sizes -12 through -24 only)



JJ Series Hose Fittings: page 32 (sizes -24 and -32 only)

4SH | Extreme High Pressure, 4-Wire

Meets or exceeds all requirements of DIN 20023 4SH and DIN EN 856 4SH.

Recommended for hydraulic service with petroleum and water-base fluids. No skiving required. Long-lasting cover is well suited for mobile hydraulics.

| ltem # | Inside Diameter | Outside Diameter | Maximum Operating (PSI) | Minimum Burst (PSI) | Minimum Bend Radius | Coil Length | Coil Price (per foot) | Cut Price (per foot) |
|--------|--------------------|---------------------|-------------------------------|------------------------|---------------------------|----------------|--------------------------|-------------------------|
| 4SH-12 | 3/4" | 1.21" | 6,095 | 24,380 | 91⁄2" | 131' | \$8.35 | \$8.79 |
| 4SH-16 | 1" | 1.50" | 5,515 | 22,060 | 12" | 131' | \$11.47 | \$12.06 |
| 4SH-20 | 1¼" | 1.85" | 5,000 | 20,000 | 16½" | 131' | \$18.38 | \$19.33 |
| 4SH-24 | 11⁄2" | 2.11" | 4,200 | 16,800 | 20" | 131' | \$21.95 | \$23.10 |
| 4SH-32 | 2" | 2.63" | 3,625 | 14,500 | 25" | 131' | \$30.29 | \$31.88 |





Tube: oil-resistant synthetic rubber
Reinforcement: four spiral layers of hightensile steel wire (R13-12, R13-16); six spiral layers of hightensile steel wire (R13-20, R13-24, and R13-32)
Cover: oil and abrasion-resistant synthetic rubber
Temperature range: -40° to +250° F

Recommended hose fittings:



W Series Hose Fittings: page 21 (sizes -12 and -16 only)



JJ Series Hose Fittings: page 32 (sizes -20 through -32)



- Oil-resistant synthetic rubber
- Two braids of high-tensile steel wire reinforcement
- Black oil-resistant and abrasionresistant synthetic rubber
- Temperature range: -40° to $+212^{\circ}$ F

Recommended hose fittings:



Braided Hose Fittings: page 14

R13 | Extreme High Pressure

Meets all requirements of SAE 100R13

Recommended for hydraulic service with petroleum and water-base fluids. Long-lasting cover is well suited for mobile hydraulics.

| ltem # | Inside Diameter | Outside Diameter | Maximum Operating (PSI) | Minimum Burst (PSI) | Minimum Bend Radius | Coil Length | Coil Price (per foot) | Cut Price (per foot) |
|--------|--------------------|---------------------|-------------------------------|------------------------|---------------------------|----------------|--------------------------|-------------------------|
| R13-12 | 3/4" | 1.26" | 5,000 | 20,000 | 91⁄2" | 131' | \$11.85 | \$12.47 |
| R13-16 | 1" | 1.54" | 5,000 | 20,000 | 12" | 131' | \$17.67 | \$18.56 |
| R13-20 | 1¼" | 1.96" | 5,000 | 20,000 | 16½" | 131' | \$25.82 | \$27.12 |
| R13-24 | 1½" | 2.26" | 5,000 | 20,000 | 20" | 131' | \$30.53 | \$32.07 |
| R13-32 | 2" | 2.8" | 5,000 | 20,000 | 25" | 131' | \$38.98 | \$40.93 |

HJK | 10,000 PSI Jack Hose

Approved for 10,000 psi static jacking applications

Recommended for hydraulic jacking systems with petroleum and water-base fluids. Not intended for impulse applications.

| ltem # | Inside Diameter | Outside Diameter | Maximum Operating (PSI) | Minimum Burst (PSI) | Minimum Bend Radius | Reel Length* | Reel Price (per foot) | Cut Price (per foot) |
|--------|--------------------|---------------------|-------------------------------|------------------------|---------------------------|-----------------|--------------------------|-------------------------|
| HJK-04 | 1/4" | 0.59" | 10,000 | 20,000 | 4" | 500' | \$2.00 | \$2.13 |
| HJK-06 | 3/8" | 0.75" | 10,000 | 20,000 | 7" | 450' | \$2.69 | \$2.85 |

* Reel may not contain one continuous length of hose.

Hydraulic Hose





Tube: oil-resistant synthetic rubber
Reinforcement: one braid of high-tensile steel wire
Cover: oil and abrasion-resistant synthetic rubber

Temperature range: -40° to +212° F

Recommended hose fittings:



Braided Hose Fittings: page 14



SAE 100R1 AT Field-Attachable Hose Fittings: page 36



Tube: oil-resistant synthetic rubberReinforcement: one helical wire between two braids of textile reinforcement.Cover: oil and abrasion-resistant synthetic rubber

Temperature range: -40° to +212° F

Recommended hose fittings:



Suction Hose Fittings: page 34



Steel Hose Barbs: page 35

R1 | Medium Pressure, 1-Wire

Meets all requirements of SAE 100R1 AT

Recommended for hydraulic service with petroleum and water-base fluids. No skiving required. Long-lasting cover is well suited for mobile hydraulics.

| Item # | Inside Diameter | Outside Diameter | Maximum Operating (PSI) | Minimum Burst (PSI) | Minimum Bend Radius | Reel Length* | Reel Price (per foot) | Cut Price (per foot) |
|--------|--------------------|---------------------|-------------------------------|------------------------|---------------------------|-----------------|--------------------------|-------------------------|
| R1-04 | 1/4" | .53" | 2,750 | 11,000 | 4" | 500' | \$1.16 | \$1.20 |
| R1-06 | 3/8" | .69" | 2,250 | 9,000 | 5" | 500' | \$1.23 | \$1.28 |
| R1-08 | 1/2" | .82" | 2,000 | 8,000 | 7" | 350' | \$1.53 | \$1.61 |
| R1-10 | 5/8" | .94" | 1,500 | 6,000 | 8" | 650' | \$2.13 | \$2.24 |
| R1-12 | 3/4" | 1.10" | 1,250 | 5,000 | 91⁄2" | 500' | \$2.22 | \$2.32 |
| R1-16 | 1" | 1.41" | 1,000 | 4,000 | 12" | 280' | \$3.10 | \$3.24 |

* Reel may not contain one continuous length of hose.

R4 | Suction and Return Meets all requirements of SAE 100R4

Recommended for suction and transfer applications with petroleum-based hydraulic fluid, fuel, lubricating oils, gasoline and water.

| ltem # | Inside Diameter | Outside Diameter | Maximum Operating (PSI) | Minimum Burst (PSI) | Rated Suction | Minimum Bend Radius | Coil Length | Coil Price (per foot) | Cut Price (per foot) |
|--------|--------------------|---------------------|-------------------------------|------------------------|------------------|---------------------------|----------------|--------------------------|-------------------------|
| R4-12 | 3/4" | 1.18" | 300 | 1,200 | 25"/hg. | 5" | 131' | \$5.08 | \$5.36 |
| R4-16 | 1" | 1.43" | 250 | 1,000 | 25"/hg. | 6" | 131' | \$6.27 | \$6.58 |
| R4-20 | 11⁄4" | 1.74" | 200 | 800 | 25"/hg. | 8" | 131' | \$6.55 | \$6.90 |
| R4-24 | 11⁄2" | 1.95" | 150 | 600 | 25"/hg. | 10" | 131' | \$7.08 | \$7.42 |
| R4-32 | 2" | 2.42" | 100 | 400 | 25"/hg. | 12" | 131' | \$7.62 | \$8.00 |





Tube: oil-resistant synthetic rubber Reinforcement: two textile braids Cover: oil and abrasion-resistant synthetic rubber

Temperature range: 40° to +212° F

Recommended hose fittings:



Braided Hose Fittings: page 14

R3 | Low/Medium Pressure, Fiber Braid

Meets all requirements of SAE 100R3

Recommended for hydraulics, fuel, lubricating oils, gasoline, air and water. Not approved for air brake applications.

| ltem # | Inside Diameter | Outside Diameter | Maximum Operating (PSI) | Minimum Burst (PSI) | Minimum Bend Radius | Reel Length* | Reel Price (per foot) | Cut Price (per foot) |
|--------|--------------------|---------------------|-------------------------------|------------------------|---------------------------|-----------------|--------------------------|-------------------------|
| R3-04 | 1/4" | 0.57" | 1,250 | 5,000 | 3" | 250' | \$2.57 | \$2.71 |
| R3-06 | 3/8" | 0.75" | 1,125 | 4,500 | 4" | 250' | \$2.70 | \$2.84 |
| R3-08 | 1/2" | 0.94" | 1,000 | 4,000 | 5" | 250' | \$3.70 | \$3.89 |
| R3-12 | 3/4" | 1.25" | 750 | 3,000 | 6" | 250' | \$5.33 | \$5.60 |
| R3-16 | 1" | 1.50" | 565 | 2,250 | 8" | 250' | \$6.32 | \$6.63 |



 Tube: oil-resistant synthetic rubber
 Reinforcement: one textile braid
 Cover: oil and abrasion-resistant synthetic rubber
 Temperature range: 40° to +212° F

Recommended hose fittings:



SAE 100R6 Field-Attachable Hose Fittings: page 38



Meets all requirements of SAE 100R6

Recommended for gasoline, fuel, lubricating oils, air and water. Not approved for air brake applications.

| Item # | Inside Diameter | Outside Diameter | Maximum Operating (PSI) | Minimum Burst (PSI) | Minimum Bend Radius | Reel Length* | Reel Price (per foot) | Cut Price (per foot) |
|--------|--------------------|---------------------|-------------------------------|------------------------|---------------------------|-----------------|--------------------------|-------------------------|
| R6-04 | 1/4" | .50" | 400 | 1,600 | 21⁄2" | 250' | \$1.34 | n/a |
| R6-05 | 5/16" | .57" | 400 | 1,600 | 3" | 250' | \$1.44 | n/a |
| R6-06 | 3/8" | .63" | 400 | 1,600 | 3" | 250' | \$1.63 | \$1.72 |



Tube: water-resistant synthetic rubber Reinforcement: one braid of high-tensile steel wire

Cover: abrasion-resistant synthetic rubber **Temperature range:** -40° to +275° F

Recommended hose fittings:



Braided Hose Fittings: page 14

PW/PWB | 4,000 PSI Pressure Wash

Recommended for pressure washer applications. Available with black (PW) or non-marking blue (PWB) cover.

| Item # | Inside Diameter | Outside Diameter | Maximum Operating (PSI) | Minimum Burst (PSI) | Minimum Bend Radius | Reel Length* | Reel Price (per foot) | Cut Price (per foot) |
|--------|--------------------|---------------------|-------------------------------|------------------------|---------------------------|-----------------|--------------------------|-------------------------|
| PW-06 | 3/8" | .65" | 4,000 | 16,000 | 3" | 500' | \$0.89 | \$0.95 |
| PWB-06 | 3/8" | .65" | 4,000 | 16,000 | 3" | 500' | \$1.06 | \$1.11 |

General Purpose Hose





Tube: EPDM Reinforcement: multi-fiber spiral Cover: abrasion-resistant EPDM Temperature range: 40° to +160° F (water up to 180° F)

Recommended hose fittings:



Brass Hose Barbs: page 42

1145 | Heavy-Duty Air

Recommended for air and water applications where petroleum contact is limited. Also recommended for some agricultural solutions. Not recommended for hydraulic fluids.

| ltem # | Inside Diameter | Outside Diameter | Maximum Operating (PSI) | Minimum Burst (PSI) | Minimum Bend Radius | Length on a Reel* | Reel Price (per foot) | Cut Price (per foot) |
|------------|--------------------|---------------------|-------------------------------|------------------------|---------------------------|-------------------------|--------------------------|-------------------------|
| 1145-04400 | 1/4" | 0.63" | 300 | 1,200 | 3" | 700' | \$0.93 | \$1.01 |
| 1145-05400 | 5/16" | 0.63" | 300 | 1,200 | 3¼" | 700' | \$1.05 | \$1.10 |
| 1145-06400 | 3/8" | 0.72" | 300 | 1,200 | 31⁄4" | 700' | \$1.16 | \$1.24 |
| 1145-08400 | 1/2" | 0.88" | 300 | 1,200 | 41⁄2" | 700' | \$1.41 | \$1.48 |
| 1145-10400 | 5/8" | 1.00" | 300 | 1,200 | 5¼" | 700' | \$1.68 | \$1.75 |
| 1145-12400 | 3/4" | 1.16" | 300 | 1,200 | 5¾" | 700' | \$2.12 | \$2.21 |
| 1145-16300 | 1" | 1.44" | 200 | 800 | 7¾" | 700' | \$2.98 | \$3.12 |
| 1145-20200 | 1¼" | 1.78" | 200 | 800 | 8¾" | 550' | \$4.22 | \$4.44 |
| 1145-24200 | 1½" | 2.03" | 200 | 800 | 10½" | 400' | \$5.19 | \$5.46 |
| 1145-32200 | 2" | 2.50" | 200 | 800 | 14" | 300' | \$7.46 | \$7.85 |

* Reel may not contain one continuous length of hose.



Tube: PVC
Reinforcement: one braid of high-tensile polyester yarn
Cover: PVC
Temperature range: -15° to +150° F

Recommended hose fittings:



Brass Hose Barbs: page 42

K1134 | PVC Multipurpose Air & Water

Recommended for air, water, and mild water-soluble chemicals. Ideal for in-plant operations requiring color coding of hose supply lines.

| Item # | Inside Diameter | Outside Diameter | Maximum Operating (PSI) @ 70° F | Maximum Operating (PSI) @ 122° F | Length on a Reel* | Reel Price (per foot) | Cut Price* (per foot) |
|----------|--------------------|---------------------|---------------------------------------|--|----------------------|--------------------------|--------------------------|
| K1134-04 | 1/4" | 0.50" | 300 | 180 | 500' | \$0.54 | \$0.56 |
| K1134-05 | 5/16" | 0.63" | 300 | 180 | 500' | \$0.70 | \$0.74 |
| K1134-06 | 3/8" | 0.63" | 300 | 180 | 500' | \$0.66 | \$0.69 |
| K1134-08 | 1/2" | 0.81" | 300 | 180 | 500' | \$0.82 | \$0.87 |
| K1134-10 | 5/8" | 0.91" | 300 | 180 | 300' | \$1.09 | \$1.14 |
| K1134-12 | 3/4" | 1.13" | 300 | 180 | 300' | \$1.49 | \$1.56 |
| K1134-16 | 1" | 1.41" | 300 | 180 | 300' | \$1.93 | \$2.04 |

* Available in full reel or 100 ft. lengths only.

Please specify color when ordering: Red (K1134) available in all sizes Blue (K1136), sizes -04, -06, -08, -12 and -16 only Gray (K1138), sizes -04, -06, -08, -12 and -16 only Yellow (K1131), sizes -04, -06, -08, -12 and -16 only





Tube: oil-resistant Nittrile (BTR)
Reinforcement: braided fiber
Cover: oil and Abrasion-resistant, black Neoprene (CR)
Temperature range: -40° to +212° F

Water not to exceed 150° F Air not to exceed 160° F

Recommended hose fittings:



Push-Lock Hose Barbs: page 40



Construction: clear PVC tubing with high tensile polyester yarn reinforcement. Temperature range: +14° to +149° F

Recommended hose fittings:



Brass Hose Barbs: page 42

3384 | Push-Lock (No Clamps or Ferrules)

Recommended for gasoline, fuel and lubricating oils, air and water. No clamps or ferrules needed when used with Push-Lock hose barbs.

| ltem # | Inside Diameter | Outside Diameter | Maximum Operating (PSI) | Minimum Burst (PSI) | Minimum Bend Radius | Length on Reel | Reel Price (per foot) | Cut Price (per foot) |
|---------|--------------------|---------------------|-------------------------------|------------------------|---------------------------|-------------------|--------------------------|-------------------------|
| 3384-04 | 1/4" | 0.50" | 250 | 1,000 | 3" | 250' | \$1.32 | \$1.38 |
| 3384-06 | 3/8" | 0.62" | 250 | 1,000 | 3" | 250' | \$1.68 | \$1.75 |
| 3384-08 | 1/2" | 0.75" | 250 | 1,000 | 5" | 250' | \$1.95 | \$2.04 |
| 3384-10 | 5/8" | 0.91" | 250 | 1,000 | 6" | 250' | \$2.67 | \$2.81 |
| 3384-12 | 3/4" | 1.03" | 250 | 1,000 | 7" | 250' | \$3.47 | \$3.64 |

Push-Lock Hose is also available in Blue (3385), Gray (3386), Red (3387), and Yellow (3389). Please specify color when ordering.

IBR | Clear Braided PVC Tubing

Recommended for various machine tools and transportation of chemicals.

| Item # | Inside Diameter | Outside Diameter | Maximum Operating (PSI) | Coil Length | Coil Price | Cost (Per Foot) |
|---------|--------------------|---------------------|----------------------------|-------------|------------|--------------------|
| IBR0446 | 1/4" | 0.50" | 142 psi | 300' | \$135.45 | \$0.45 |
| IBR0609 | 3/8" | 0.63" | 114 psi | 300' | \$176.40 | \$0.59 |
| IBR0812 | 1/2" | 0.75" | 100 psi | 300' | \$220.50 | \$0.74 |
| IBR1218 | 3/4" | 1.06" | 71 psi | 300' | \$428.40 | \$1.43 |
| IBR1621 | 1" | 1.31" | 71 psi | 200' | \$367.50 | \$1.84 |

IBR tubing is sold in coil lengths only.





Tube: oil-resistant synthetic rubber Reinforcement: one braid of high-tensile steel wire Cover: braided textile

Temperature range: -40° to +212° F Hydraulic fluids: -40° to +212° F Air brake: -40° to +200° F Hot oil: -40° to +302° F (sizes -20 or larger not to exceed 250° F)

Recommended hose fittings:



R5 Truck Hose Fittings: page 46



SAE 100R5 Field-Attachable Hose Fittings: page 37



Tube: PTFE Reinforcement and cover: one braid of type 304 stainless steel Temperature range: -65° to +450° F

Recommended hose fittings:



T Series PTFE Hose Fittings: page 30



SAE 100R14A Field-Attachable Hose Fittings: page 41

R5 | 1-Wire, Braided Cover

Meets all requirements of SAE 100R5, DOT* and SAE J1402*

Recommended for hydraulics, air, air brake, gasoline, fuel, and lubricating oils. SAE 100R5 is *not* Coast Guard approved for fuel lines on pleasure crafts.

| ltem # | Inside Diameter | Outside Diameter | Maximum Operating (PSI) | Minimum Burst (PSI) | Minimum Bend Radius | Reel Length* | Reel Price (per foot) | Cut Price (per foot) |
|--------|----------------------|---------------------|-------------------------------|------------------------|---------------------------|-----------------|--------------------------|-------------------------|
| R5-04 | 3/16" | 0.51" | 3,000 | 12,000 | 3" | 250' | \$4.51 | \$4.74 |
| R5-05 | 1/4" | 0.57" | 3,000 | 12,000 | 31⁄2" | 250' | \$4.62 | \$4.84 |
| R5-06 | 5/16" | 0.67" | 2,250 | 9,000 | 4" | 250' | \$5.32 | \$5.58 |
| R5-08 | 13/32" | 0.76" | 2,000 | 8,000 | 41⁄2" | 250' | \$5.55 | \$5.84 |
| R5-10 | 1/2" | 0.92" | 1,750 | 7,000 | 51⁄2" | 250' | \$6.79 | \$7.14 |
| R5-12 | 5/8" | 1.07" | 1,500 | 6,000 | 6½" | 250' | \$8.36 | \$8.77 |
| R5-16 | 7/8" | 1.23" | 800 | 3,200 | 71⁄2" | 250' | \$9.46 | \$9.93 |
| R5-20 | 11%" | 1.50" | 625 | 2,500 | 9" | 150' | \$12.17 | \$12.77 |
| R5-24 | 1%" | 1.75" | 500 | 2,000 | 10½" | 100' | \$14.16 | \$14.86 |
| R5-32 | 1 ¹³ ⁄16" | 2.10" | 350 | 1,400 | 13¼" | 100' | \$17.40 | \$18.29 |

* Sizes -16 and larger are *not* SAE or DOT approved for air brake applications. ** Reel may not contain one continuous length of hose.

R14 | PTFE Hose

Meets all requirements of SAE 100R14A

Recommended for steam, solvents, fuels, hydraulic fluids, most chemicals and acids. Vibration absorption and high temperature and pressure ranges make PTFE hose extremely versatile.


| ltem # | Inside Diameter | Outside Diameter | Maximum Operating (PSI) | Minimum Burst (PSI) | Minimum Bend Radius | Coil Length | Coil Price (per foot) | Cut Price (per foot) |
|--------|--------------------|---------------------|-------------------------------|------------------------|---------------------------|----------------|--------------------------|-------------------------|
| R14-04 | 3/16" | .30" | 3,000 | 12,000 | 2" | 100' | \$2.64 | \$2.77 |
| R14-05 | 1/4" | .38" | 3,000 | 12,000 | 3" | 100' | \$3.08 | \$3.24 |
| R14-06 | 5/16" | .44" | 2,500 | 10,000 | 4" | 100' | \$3.37 | \$3.55 |
| R14-07 | 3/8" | .52" | 2,000 | 8,000 | 5" | 100' | \$4.44 | \$4.67 |
| R14-08 | 13/32" | .54" | 2,000 | 8,000 | 5" | 100' | \$4.45 | \$4.68 |
| R14-10 | 1/2" | .63" | 1,500 | 6,000 | 6½" | 100' | \$5.44 | \$5.72 |
| R14-12 | 5/8" | .76" | 1,200 | 4,800 | 71⁄2" | 100' | \$6.69 | \$7.04 |
| R14-14 | 3/4" | .89" | 1,000 | 4,000 | 81⁄2" | 100' | \$9.43 | \$9.92 |
| R14-16 | 7/8" | 1.03" | 1,000 | 4,000 | 9" | 100' | \$9.64 | \$10.14 |
| R14-18 | 1" | 1.22" | 1,000 | 4,000 | 12" | 100' | \$15.74 | \$16.57 |





Tube: synthetic rubberReinforcement: Spiral multi-fiberCover: neopreneTemperature range: -40° to +200° F

Recommended hose fittings:



Air Brake Hose Fittings: page 48

4821 | Air Brake

Meets all requirements of SAE J1402A and DOT, Type All

Recommended for air brake applications. Available in 50' coils or 250' and 500' reels. 250' and 500' reels may not contain one continuous length of hose.

| Item # | Inside Diameter | Outside Diameter | Maximum Operating (PSI) | Minimum Burst (PSI) | Minimum Bend Radius | Length of Coil/Reel (with cost per foot) | Price |
|-----------|--------------------|---------------------|-------------------------------|------------------------|---------------------------|---|----------|
| 482106451 | 3/8" | 0.75" | 225 | 900 | 3.5" | 50 feet @ \$1.79 | \$89.25 |
| 482106498 | 3/8" | 0.75" | 225 | 900 | 3.5" | 250 feet @ \$1.69 | \$422.63 |
| 482106499 | 3/8" | 0.75" | 225 | 900 | 3.5" | 500 feet @ \$1.61 | \$803.25 |
| 482108451 | 1/2" | 0.88" | 225 | 900 | 4" | 50 feet @ \$2.17 | \$108.68 |
| 482108498 | 1/2" | 0.88" | 225 | 900 | 4" | 250 feet @ \$2.09 | \$522.38 |
| 482108500 | 1/2" | 0.88" | 225 | 900 | 4" | 500 feet @ \$1.92 | \$960.75 |



Tube: oil-resistant synthetic rubberReinforcement: braided multifiberCover: HypalonTemperature range: -40° to +257° F

Recommended hose fittings:



Fuel Line Hose Barbs: page 49

30R7 | Fuel Line

Meets all requirements of SAE 30R7

Recommended for low pressure / high temperature fuel for passenger car, light truck and small engine applications. Not intended for fuel injection applications.

Important: 30R7 is not Coast Guard approved for marine applications.


| Item # | Inside Diameter | Outside Diameter | Maximum Operating (PSI) | Minimum Burst (PSI) | Minimum Bend Radius | Reel Length* | Reel Price | Cost Per Foot |
|---------|--------------------|---------------------|-------------------------------|------------------------|---------------------------|-----------------|------------|------------------|
| 30R7-03 | 3/16" | .41" | 50 | 250 | 2" | 700' | \$661.50 | \$0.95 |
| 30R7-04 | 1/4" | .50" | 50 | 250 | 21⁄2" | 700' | \$749.70 | \$1.07 |
| 30R7-05 | 5/16" | .57" | 50 | 250 | 2¾" | 700' | \$904.05 | \$1.29 |
| 30R7-06 | 3/8" | .63" | 50 | 250 | 3" | 700' | \$940.80 | \$1.34 |

* Reel may not contain one continuous length of hose.



Tube:polychloropene barrierReinforcement:braided textileCover:abrasion-resistant EPDMTemperature range:-22° to +257° F

Recommended hose fittings:



Beadlock A/C Hose Fittings: page 47

BH | A/C, Mobile Refrigeration

Meets all requirements for SAE J2064 Type C Class II

Recommended for R12 and R134A refrigerant application. Ideal for heavy duty truck use as well as industrial and automotive applications.

Sold in 50 foot lengths only.

| Item # | Inside Diameter | Outside Diameter | Maximum Operating (PSI) | Minimum Burst (PSI) | Minimum Bend Radius | Coil Length | Coil Price | Cost Per Foot |
|------------|--------------------|---------------------|-------------------------------|------------------------|---------------------------|----------------|------------|------------------|
| BH-06-COIL | 5/16" | .75" | 350 | 2,000 | 4" | 50' | \$119.18 | \$2.38 |
| BH-08-COIL | 13/32" | .91" | 350 | 2,000 | 4¾" | 50' | \$137.03 | \$2.74 |
| BH-10-COIL | 1/2" | 1.00" | 350 | 2,000 | 51⁄2" | 50' | \$162.75 | \$3.26 |
| BH-12-COIL | 5/8" | 1.13" | 350 | 1,750 | 6½" | 50' | \$179.03 | \$3.58 |

Thermoplastic Hose





Tube: oil-resistant synthetic thermoplasticReinforcement: textileCover: abrasion-resistant polyurethaneTemperature range: -40° to +200° F

Recommended hose fittings:



3 Series Hose Fittings: page 28



SAE 100R7 Field-Attachable Hose Fittings: page 38

R7 | Medium Pressure Thermoplastic

Meets all requirements of SAE 100R7

Recommended for hydraulic lines, lubrication, medium pressure gas, and solvent. Available in black (BK) or nonconductive orange (NC).

| ltem # | Inside Diameter | Outside Diameter | Maximum Operating (PSI) | Minimum Burst (PSI) | Minimum Bend Radius | Length on a Reel* | Reel Price (per foot) | Cut Price (per foot) |
|-----------|--------------------|---------------------|-------------------------------|------------------------|---------------------------|-------------------------|--------------------------|-------------------------|
| R7-02BK** | 1/8" | 0.32" | 2,500 | 10,000 | 1/2" | 250' | \$1.40 | \$1.47 |
| R7-03BK | 3/16" | 0.41" | 3,000 | 12,000 | 3/4" | 250' | \$1.55 | \$1.64 |
| R7-03NC | 3/16" | 0.41" | 3,000 | 12,000 | 3/4" | 250' | \$1.73 | \$1.83 |
| R7-04BK | 1/4" | 0.49" | 2,750 | 11,000 | 1¼" | 250' | \$1.59 | \$1.66 |
| R7-04NC | 1/4" | 0.49" | 2,750 | 11,000 | 1¼" | 250' | \$1.79 | \$1.87 |
| R7-05BK | 5/16" | 0.56" | 2,500 | 10,000 | 1¾" | 250' | \$2.18 | \$2.29 |
| R7-05NC | 5/16" | 0.56" | 2,500 | 10,000 | 1¾" | 250' | \$2.29 | \$2.42 |
| R7-06BK | 3/8" | 0.62" | 2,250 | 9,000 | 2" | 250' | \$2.07 | \$2.18 |
| R7-06NC | 3/8" | 0.62" | 2,250 | 9,000 | 2" | 250' | \$2.17 | \$2.28 |
| R7-08BK | 1/2" | 0.76" | 2,000 | 8,000 | 3" | 250' | \$2.66 | \$2.80 |
| R7-08NC | 1/2" | 0.76" | 2,000 | 8,000 | 3" | 250' | \$2.91 | \$3.07 |

* Reel may not contain one continuous length of hose.

** Size -02 (1/8" ID) is available in black only.



Tube:oil-resistant synthetic thermoplasticReinforcement:textileCover:abrasion-resistant polyurethaneTemperature range:-40° to +200° F

Recommended hose fittings:



3 Series Hose Fittings: page 28



SAE 100R7 Field-Attachable Hose Fittings: page 38


R7T | Medium Pressure Thermoplastic Twin Line

Meets all requirements of SAE 100R7

Recommended for hydraulic lines, lubrication, medium pressure gas, and solvent. Available in black (BK) or nonconductive orange (NC).

| Item # | Inside Diameter | Outside Diameter | Maximum Operating (PSI) | Minimum Burst (PSI) | Minimum Bend Radius | Length on a Reel* | Reel Price (per foot) | Cut Price (per foot) |
|----------|--------------------|---------------------|-------------------------------|------------------------|---------------------------|-------------------------|--------------------------|-------------------------|
| R7T-04BK | 1/4" | 0.51" | 2,750 | 11,000 | 11⁄4" | 250' | \$3.93 | \$4.14 |
| R7T-04NC | 1/4" | 0.51" | 2,750 | 11,000 | 11⁄4" | 250' | \$4.19 | \$4.41 |
| R7T-06BK | 3/8" | 0.65" | 2,250 | 9,000 | 2" | 250' | \$5.17 | \$5.43 |
| R7T-06NC | 3/8" | 0.65" | 2,250 | 9,000 | 2" | 250' | \$5.33 | \$5.61 |
| R7T-08BK | 1/2" | 0.81" | 2,000 | 8,000 | 3" | 250' | \$7.09 | \$7.47 |
| R7T-08NC | 1/2" | 0.81" | 2,000 | 8,000 | 3" | 250' | \$7.42 | \$7.81 |

* Reel may not contain one continuous length of hose.







Tube:oil-resistant synthetic thermoplasticReinforcement:textileCover:abrasion-resistant polyurethaneTemperature range:-40° to +200° F

Recommended hose fittings:



3 Series Hose Fittings: page 28



SAE 100R7 Field-Attachable Hose Fittings: page 38

R8 | High Pressure Thermoplastic

Meets all requirements of SAE 100R8

Reduced OD allows use of standard SAE 100R7 hose fittings.

Recommended for hydraulic lines, lubrication, medium pressure gas, and solvent. Available in black (BK) or nonconductive orange (NC).

| ltem # | Inside Diameter | Outside Diameter | Maximum Operating (PSI) | Minimum Burst (PSI) | Minimum Bend Radius | Length on a Reel* | Reel Price (per foot) | Cut Price (per foot) |
|-----------|--------------------|---------------------|-------------------------------|------------------------|---------------------------|-------------------------|--------------------------|-------------------------|
| R8-03BK** | 3/16" | 0.41" | 5,000 | 20,000 | 11⁄2" | 250' | \$3.39 | \$3.57 |
| R8-04BK | 1/4" | 0.49" | 5,000 | 20,000 | 2" | 250' | \$4.46 | \$4.68 |
| R8-04NC | 1/4" | 0.49" | 5,000 | 20,000 | 2" | 250' | \$5.31 | \$5.58 |
| R8-06BK | 3/8" | 0.62" | 4,000 | 16,000 | 21⁄2" | 250' | \$5.85 | \$6.14 |
| R8-06NC | 3/8" | 0.62" | 4,000 | 16,000 | 21⁄2" | 250' | \$6.41 | \$6.71 |
| R8-08BK | 1/2" | 0.76" | 3,500 | 14,000 | 4" | 250' | \$7.74 | \$8.12 |
| R8-08NC | 1/2" | 0.76" | 3,500 | 14,000 | 4" | 250' | \$9.17 | \$9.63 |

* Reel may not contain one continuous length of hose.

** Size -03 (3/16" ID) is available in black only.



FJX

JIC 37° Female Swivel

| FJX-02-03 | | \$5.21 |
|-----------|----------|---------|
| FJX-02-04 | | \$5.48 |
| FJX-03-04 | | \$5.28 |
| FJX-03-05 | | \$5.54 |
| FJX-04-03 | | \$5.81 |
| FJX-04-04 | | \$2.42 |
| FJX-04-04 | Min. 200 | \$2.25 |
| FJX-04-05 | | \$2.47 |
| | Min. 200 | \$2.30 |
| FJX-04-06 | | \$2.42 |
| FJX-04-06 | Min. 200 | \$2.32 |
| FJX-04-08 | | \$9.49 |
| FJX-05-05 | | \$12.88 |
| FJX-06-04 | | \$8.13 |
| FJX-06-04 | Min. 200 | \$7.12 |
| FJX-06-05 | | \$5.00 |
| FJX-06-06 | | \$3.03 |
| FJX-06-06 | Min. 200 | \$2.65 |
| FJX-06-08 | | \$3.33 |
| FJX-06-08 | Min. 200 | \$3.10 |
| FJX-06-10 | | \$4.33 |
| FJX-06-12 | | \$16.65 |
| FJX-08-06 | | \$4.15 |
| FJX-08-06 | Min. 150 | \$3.85 |
| FJX-08-08 | | \$3.74 |
| FJX-08-08 | Min. 150 | \$3.48 |
| FJX-08-10 | | \$4.41 |
| FJX-08-10 | Min. 120 | \$4.11 |
| FJX-08-12 | | \$6.45 |
| FJX-08-12 | Min. 100 | \$6.01 |
| FJX-08-16 | | \$21.16 |
| FJX-10-08 | | \$10.45 |
| FJX-10-10 | | \$6.53 |
| FJX-10-10 | Min. 100 | \$6.08 |
| FJX-10-12 | | \$6.89 |
| FJX-12-08 | | \$11.39 |
| FJX-12-10 | | \$12.37 |
| FJX-12-12 | | \$6.17 |
| FJX-12-12 | Min. 80 | \$5.75 |
| FJX-12-14 | | \$10.40 |
| FJX-12-16 | | \$8.46 |
| FJX-16-12 | | \$16.15 |
| FJX-16-14 | | \$19.28 |
| FJX-16-16 | | \$10.84 |
| FJX-16-16 | Min. 60 | \$8.58 |
| FJX-16-20 | | \$28.00 |
| FJX-20-16 | | \$41.93 |
| FJX-20-20 | | \$26.22 |
| | | |

SS-FJX


JIC 37° Female Swivel Stainless Steel



| SS-FJX-04-04 | \$49.04 |
|--------------|----------|
| SS-FJX-06-06 | \$52.55 |
| SS-FJX-06-08 | \$80.60 |
| SS-FJX-08-08 | \$63.06 |
| SS-FJX-08-10 | \$84.09 |
| SS-FJX-10-10 | \$92.80 |
| SS-FJX-12-12 | \$94.62 |
| SS-FJX-16-16 | \$101.62 |

FJX45

JIC 37° Female Swivel 45°



| FJX45-04-04 | | | \$6.39 |
|-------------|------|-----|---------|
| FJX45-04-05 | | | \$7.20 |
| FJX45-04-06 | | | \$7.08 |
| FJX45-06-04 | | | \$7.60 |
| FJX45-06-05 | | | \$12.94 |
| FJX45-06-06 | | | \$6.87 |
| FJX45-06-06 | Min. | 150 | \$6.26 |
| FJX45-06-08 | | | \$7.30 |
| FJX45-08-06 | | | \$8.45 |
| FJX45-08-08 | | | \$7.40 |
| FJX45-08-08 | Min. | 100 | \$6.68 |
| FJX45-08-10 | | | \$11.43 |
| FJX45-10-10 | | | \$12.85 |
| FJX45-10-12 | | | \$13.59 |
| FJX45-12-12 | | | \$14.51 |
| FJX45-12-16 | | | \$22.73 |
| FJX45-16-12 | | | \$54.98 |
| FJX45-16-16 | | | \$25.50 |
| FJX45-20-20 | | | \$47.92 |
| | | | |
| | | | |

FJX90

JIC 37° Female Swivel 90°



| FJX90-04-04 | | \$6.24 |
|-------------|----------|---------|
| FJX90-04-04 | Min. 150 | \$5.48 |
| FJX90-04-05 | | \$7.63 |
| FJX90-04-06 | | \$6.59 |
| FJX90-04-06 | Min. 150 | \$5.92 |
| FJX90-06-04 | | \$7.20 |
| FJX90-06-05 | | \$10.12 |
| FJX90-06-06 | | \$6.54 |
| FJX90-06-06 | Min. 150 | \$5.89 |
| FJX90-06-08 | | \$7.28 |
| FJX90-06-08 | Min. 150 | \$6.53 |
| FJX90-08-06 | | \$8.99 |
| FJX90-08-08 | | \$8.47 |
| FJX90-08-08 | Min. 120 | \$7.52 |
| FJX90-08-10 | | \$15.06 |
| FJX90-08-10 | Min. 100 | \$13.71 |
| FJX90-08-12 | | \$14.43 |
| FJX90-10-10 | | \$11.83 |
| FJX90-10-12 | | \$16.91 |
| FJX90-12-10 | | \$16.20 |
| FJX90-12-12 | | \$14.51 |
| FJX90-12-12 | Min. 40 | \$13.10 |
| FJX90-12-16 | | \$23.45 |
| FJX90-16-16 | | \$22.27 |
| FJX90-16-16 | Min. 40 | \$20.57 |
| FJX90-20-20 | | \$69.97 |

SS-FJX90


JIC 37° Female Swivel 90° Stainless Steel



| SS-FJX90-04-04 | \$90.48 |
|----------------|----------|
| SS-FJX90-06-06 | \$94.37 |
| SS-FJX90-06-08 | \$107.76 |
| SS-FJX90-08-08 | \$100.71 |
| SS-FJX90-08-10 | \$123.92 |
| SS-FJX90-12-12 | \$175.12 |
| SS-FJX90-16-16 | \$201.97 |
| | |

FJX90M

JIC 37° Female Swivel 90° Medium Drop Elbow



| FJX90M-04-04 | \$7.07 |
|--------------|---------|
| FJX90M-06-06 | \$8.13 |
| FJX90M-08-08 | \$9.11 |
| FJX90M-10-10 | \$14.83 |
| FJX90M-12-12 | \$20.61 |

FJX90L

JIC 37° Female Swivel 90° Long Drop Elbow



| FJX90L-04-04 | \$6.80 |
|--------------|---------|
| FJX90L-04-06 | \$6.95 |
| FJX90L-06-04 | \$9.98 |
| FJX90L-06-06 | \$10.56 |
| FJX90L-06-08 | \$8.49 |
| FJX90L-08-08 | \$11.92 |
| FJX90L-08-10 | \$10.11 |
| FJX90L-10-10 | \$11.83 |
| FJX90L-12-12 | \$17.26 |
| FJX90L-16-16 | \$26.80 |
| | |

Braided Hose Fittings are intended for use with most 1-wire and 2-wire hydraulic hoses including R1, R2, R2, R16, R17 KT, and HJK.




Braided Hose Fittings interchange with Weatherhead U Series, Dayco-Eastman HY Series, Aeroquip FJ Series, Imperial-Eastman HU Series and Dayco SB Series hose fittings.




FJXT

JIC 37° Female Swivel Long



| FJXT-04-04 | \$7.89 |
|------------|---------|
| FJXT-04-05 | \$15.77 |
| FJXT-06-05 | \$15.77 |
| FJXT-06-06 | \$7.95 |
| FJXT-06-08 | \$14.90 |
| FJXT-08-08 | \$10.93 |
| FJXT-08-10 | \$14.22 |

MJ JIC 37° Male Rigid



| MJ-04-04 | \$2.64 |
|----------|---------|
| MJ-04-05 | \$2.70 |
| MJ-04-06 | \$2.93 |
| MJ-05-05 | \$12.77 |
| MJ-05-06 | \$13.10 |
| MJ-06-04 | \$5.36 |
| MJ-06-06 | \$2.93 |
| MJ-06-08 | \$3.00 |
| MJ-06-10 | \$6.73 |
| MJ-08-06 | \$14.41 |
| MJ-08-08 | \$3.49 |
| MJ-08-10 | \$4.08 |
| MJ-08-12 | \$7.81 |
| MJ-10-10 | \$5.37 |
| MJ-10-12 | \$5.84 |
| MJ-12-10 | \$11.90 |
| MJ-12-12 | \$5.18 |
| MJ-12-14 | \$7.42 |
| MJ-12-16 | \$7.50 |
| MJ-16-16 | \$9.67 |
| MJ-20-20 | \$16.08 |

SS-MJ JIC 37° Male Rigid

Stainless Steel

| [| |
|---|--|
|---|--|

| SS-MJ-04-04 | \$40.07 |
|-------------|---------|
| SS-MJ-06-06 | \$46.04 |
| SS-MJ-08-08 | \$53.32 |
| SS-MJ-12-12 | \$77.23 |
| SS-MJ-16-16 | \$83.11 |
| | |

MP NPTF Male Pipe Rigid




| MP-02-02 | | \$1.93 |
|----------|----------|---------|
| MP-02-02 | Min. 200 | \$1.80 |
| MP-03-02 | | \$3.29 |
| MP-04-02 | | \$3.30 |
| MP-04-02 | Min. 200 | \$3.03 |
| MP-04-04 | | \$2.19 |
| MP-04-04 | Min. 200 | \$2.05 |
| MP-04-06 | | \$2.22 |
| MP-04-06 | Min. 200 | \$2.08 |
| MP-04-08 | | \$8.06 |
| MP-06-04 | | \$2.27 |
| MP-06-04 | Min. 200 | \$2.11 |
| MP-06-06 | | \$2.45 |
| MP-06-06 | Min. 200 | \$2.29 |
| MP-06-08 | | \$2.68 |
| MP-06-08 | Min. 160 | \$2.50 |
| MP-08-06 | | \$2.59 |
| MP-08-06 | Min. 160 | \$2.43 |
| MP-08-08 | | \$2.68 |
| MP-08-08 | Min. 160 | \$2.50 |
| MP-08-12 | | \$4.69 |
| MP-08-12 | Min. 100 | \$4.39 |
| MP-10-08 | | \$6.31 |
| MP-10-12 | | \$8.74 |
| MP-12-08 | | \$8.22 |
| MP-12-12 | | \$5.01 |
| MP-12-12 | Min. 100 | \$4.67 |
| MP-12-16 | | \$8.61 |
| MP-16-12 | | \$8.24 |
| MP-16-16 | | \$7.73 |
| MP-16-16 | Min. 60 | \$7.23 |
| MP-20-20 | | \$18.88 |

SS-MP

NPTF Male Pipe Rigid Stainless Steel

| SS-MP-04-04 | \$31.51 |
|-------------|---------|
| SS-MP-06-06 | \$35.41 |
| SS-MP-08-08 | \$45.53 |
| SS-MP-12-12 | \$70.08 |
| SS-MP-16-16 | \$77.08 |
| SS-MP-16-16 | \$77.09 |
| | |

MPX NPTF Male Pipe Swivel



| MPX-04-02 | | \$6.13 |
|-----------|----------|---------|
| MPX-04-04 | | \$4.54 |
| MPX-04-04 | Min. 200 | \$4.14 |
| MPX-04-06 | | \$5.48 |
| MPX-06-04 | | \$4.76 |
| MPX-06-06 | | \$4.20 |
| MPX-06-06 | Min. 200 | \$3.85 |
| MPX-06-08 | | \$5.20 |
| MPX-06-08 | Min. 200 | \$3.82 |
| MPX-08-06 | | \$5.28 |
| MPX-08-08 | | \$4.57 |
| MPX-08-08 | Min. 150 | \$4.29 |
| MPX-10-08 | | \$20.25 |
| MPX-10-12 | | \$21.49 |
| MPX-12-12 | | \$7.36 |
| MPX-12-12 | Min. 100 | \$7.31 |
| MPX-16-16 | | \$14.06 |
| MPX-16-16 | Min. 60 | \$13.13 |

MPX90

NPTF Male Pipe Swivel 90°



| MPX90-04-04 | \$8.05 |
|----------------------|---------|
| MPX90-04-06 | \$8.90 |
| MPX90-06-04 | \$10.57 |
| MPX90-06-06 | \$8.83 |
| MPX90-06-06 Min. 150 | \$8.21 |
| MPX90-06-08 | \$10.08 |
| MPX90-08-08 | \$9.73 |
| MPX90-08-08 Min. 150 | \$8.72 |
| MPX90-12-12 | \$16.75 |
| MPX90-16-16 | \$33.66 |

Braided Hose Fittings

FP NPTF Female Pipe Rigid

| ₿— |
|--------|
| F |
| ₩— |
| _^ |

| FP-04-02 | \$5.13 |
|----------|---------|
| FP-04-04 | \$3.68 |
| FP-04-06 | \$15.98 |
| FP-06-04 | \$8.69 |
| FP-06-06 | \$3.49 |
| FP-06-08 | \$7.21 |
| FP-08-08 | \$3.93 |
| FP-12-08 | \$22.45 |
| FP-12-12 | \$9.02 |
| FP-16-16 | \$16.59 |

FPX

NPSM Female Pipe Swivel

| FPX-03-04 | \$6.28 |
|-----------|---------|
| FPX-04-02 | \$27.57 |
| FPX-04-04 | \$4.77 |
| FPX-06-06 | \$5.18 |
| FPX-06-08 | \$9.92 |
| FPX-08-08 | \$6.13 |
| FPX-08-12 | \$19.78 |
| FPX-12-12 | \$9.84 |
| FPX-16-16 | \$13.90 |
| FPX-20-20 | \$21.18 |

PTFE Thread Sealing Compound



Temperature range: -300° to 500° F

| LCTS14 (1/4 pint) | \$12.60 |
|-------------------|---------|
| LCTS1 (1/2 pint) | \$18.47 |
| LCTS2 (1 pint) | \$28.67 |



FFX

O-Ring Face Seal (ORFS) Female Swivel



| FFX-04-04 | \$4.48 |
|-----------|---------|
| FFX-04-06 | \$5.26 |
| FFX-05-06 | \$18.99 |
| FFX-06-04 | \$11.74 |
| FFX-06-06 | \$5.16 |
| FFX-06-08 | \$5.88 |
| FFX-08-06 | \$9.84 |
| FFX-08-08 | \$6.24 |
| FFX-08-10 | \$9.02 |
| FFX-08-12 | \$12.37 |
| FFX-10-08 | \$12.78 |
| FFX-10-10 | \$10.16 |
| FFX-10-12 | \$12.10 |
| FFX-12-10 | \$18.32 |
| FFX-12-12 | \$11.83 |
| FFX-12-16 | \$22.09 |
| FFX-16-16 | \$22.18 |
| FFX-16-20 | \$24.61 |
| FFX-20-20 | \$52.54 |
| FFX-20-24 | \$28.63 |
| | |

FFX90 O-Ring Face Seal (ORFS)


Female Swivel 90°



| FFX90-04-04 | \$8.47 |
|-------------|---------|
| FFX90-04-06 | \$9.69 |
| FFX90-05-06 | \$15.69 |
| FFX90-06-04 | \$18.85 |
| FFX90-06-06 | \$8.89 |
| FFX90-06-08 | \$11.37 |
| FFX90-08-06 | \$12.75 |
| FFX90-08-08 | \$10.47 |
| FFX90-08-10 | \$12.39 |
| FFX90-08-12 | \$35.84 |
| FFX90-10-10 | \$14.46 |
| FFX90-10-12 | \$19.25 |
| FFX90-12-10 | \$20.94 |
| FFX90-12-12 | \$22.65 |
| FFX90-12-16 | \$52.40 |
| FFX90-16-16 | \$26.53 |
| FFX90-16-20 | \$61.49 |
| FFX90-20-20 | \$64.94 |
| | |

FFX90L


O-Ring Face Seal (ORFS) Female Swivel 90° Long



| FFX90L-04-04 | \$10.12 |
|--------------|---------|
| FFX90L-06-06 | \$11.35 |
| FFX90L-06-08 | \$14.67 |
| FFX90L-08-08 | \$12.02 |
| FFX90L-08-10 | \$26.37 |
| FFX90L-10-10 | \$22.96 |
| FFX90L-10-12 | \$24.92 |
| FFX90L-12-12 | \$22.87 |
| FFX90L-16-16 | \$32.00 |

FFX45

O-Ring Face Seal (ORFS) Female Swivel 45°



| | Ŭ, |
|---------------|---------|
| FFX45-04-04 | \$8.37 |
| FFX45-04-06 | \$10.63 |
| FFX45-06-06 | \$9.10 |
| FFX45-06-08 | \$11.83 |
| FFX45-08-06 | \$12.24 |
| FFX45-08-08 | \$11.40 |
| FFX45-08-10 | \$14.98 |
| FFX45-08-12 | \$24.00 |
| FFX45-10-10 | \$15.15 |
| FFX45-10-12 | \$18.47 |
| FFX45-12-10 | \$24.98 |
| FFX45-12-12 | \$23.61 |
| FFX45-12-16 | \$29.23 |
| FFX45-16-16 | \$27.92 |
| FFX45L-16-16 | \$42.03 |
| FFX45LL-16-16 | \$46.27 |
| FFX45-16-20 | \$40.55 |
| FFX45-20-20 | \$62.88 |
| FFX45-16-20 | \$40.19 |
| | |

\$62.34

MF

O-Ring Face Seal (ORFS) Male Rigid



| MF-04-04 | \$4.01 |
|----------|---------|
| MF-04-06 | \$6.11 |
| MF-06-06 | \$5.85 |
| MF-06-08 | \$14.32 |
| MF-08-08 | \$5.41 |
| MF-08-10 | \$12.62 |
| MF-08-12 | \$21.53 |
| MF-10-10 | \$9.93 |
| MF-10-12 | \$19.79 |
| MF-12-12 | \$19.85 |
| MF-12-16 | \$54.54 |
| MF-16-16 | \$26.91 |

FS4000

FS4000-04

FS4000-06

FS4000-08

FS4000-10

FS4000-12

FS4000-16

FS4000-20

FS4000-24

Buna O-Ring for Face Seal

\$0.14

\$0.17 \$0.20

\$0.24

\$0.36

\$0.45


\$0.68

\$0.35

FFXT

Page 16


O-Ring Face Seal (ORFS) Female Swivel Long



| FFXT-04-04 | \$4.15 |
|------------|---------|
| FFXT-04-06 | \$6.23 |
| FFXT-06-06 | \$5.02 |
| FFXT-06-08 | \$6.84 |
| FFXT-08-08 | \$5.70 |
| FFXT-10-10 | \$8.34 |
| FFXT-10-12 | \$17.30 |
| FFXT-12-12 | \$11.72 |
| FFXT-16-16 | \$20.82 |
| | |

| С | С | v | o | n | Μ | |
|---|---|---|---|---|-----|--|
| Г | Г | Λ | 7 | υ | IVI | |

O-Ring Face Seal (ORFS Female Swivel 90° Medium



| FFX90M-04-04 | \$12.45 |
|--------------|---------|
| FFX90M-06-06 | \$13.23 |
| FFX90M-08-08 | \$14.76 |
| FFX90M-10-10 | \$22.96 |
| FFX90M-12-12 | \$31.62 |
| FFX90M-16-16 | \$28.28 |
| | |

FFX45-20-20



MB

SAE Straight Thread O-Ring Boss Male Rigid

| MB-03-04 | \$2.91 |
|----------|---------|
| MB-04-04 | \$3.60 |
| MB-04-05 | \$5.76 |
| MB-04-06 | \$3.58 |
| MB-04-08 | \$8.27 |
| MB-06-06 | \$3.72 |
| MB-06-08 | \$3.36 |
| MB-06-10 | \$7.30 |
| MB-08-08 | \$3.36 |
| MB-08-10 | \$4.60 |
| MB-08-12 | \$18.47 |
| MB-10-10 | \$9.38 |
| MB-10-12 | \$8.05 |
| MB-12-10 | \$7.50 |
| MB-12-12 | \$9.08 |
| MB-12-14 | \$24.84 |
| MB-12-16 | \$18.68 |
| MB-16-12 | \$18.68 |
| MB-16-16 | \$10.30 |
| | |

MBX

SAE Straight Thread O-Ring Boss Male Swivel



| MBX-04-04 | \$5.02 |
|-----------|---------|
| MBX-04-05 | \$18.79 |
| MBX-04-06 | \$5.66 |
| MBX-06-04 | \$7.44 |
| MBX-06-06 | \$4.48 |
| MBX-06-08 | \$5.31 |
| MBX-08-08 | \$5.39 |
| MBX-08-10 | \$5.57 |
| MBX-12-12 | \$11.80 |
| MBX-16-16 | \$33.48 |
| | |

MBX90


SAE Straight Thread O-Ring Boss Male Swivel 90°



| MBX90-04-04 | \$7.75 |
|-------------|---------|
| MBX90-04-06 | \$7.99 |
| MBX90-06-06 | \$9.18 |
| MBX90-06-08 | \$9.95 |
| MBX90-06-10 | \$12.71 |
| MBX90-08-08 | \$10.43 |
| MBX90-08-10 | \$11.20 |
| MBX90-08-12 | \$31.21 |
| MBX90-10-10 | \$64.18 |
| MBX90-12-12 | \$23.70 |

MENDER

Hose Mender



| MENDER-04 | \$13.46 |
|-----------|---------|
| MENDER-06 | \$7.54 |
| MENDER-08 | \$8.23 |
| MENDER-12 | \$18.95 |
| MENDER-16 | \$51.95 |

SHELL

Crimp collar only

| \$0.98 |
|--------|
| \$1.23 |
| \$1.54 |
| \$1.68 |
| \$2.27 |
| \$2.65 |
| |

C61


Code 61 Flange



| C61-08-08 | \$15.57 |
|-----------|---------|
| C61-08-12 | \$16.77 |
| C61-12-12 | \$16.65 |
| C61-12-16 | \$26.41 |
| C61-16-16 | \$20.96 |
| C61-16-20 | \$22.04 |
| C61-20-20 | \$53.07 |


C6145

Code 61 Flange 45°



| C6145-08-08 | \$22.51 |
|-------------|---------|
| C6145-08-12 | \$35.03 |
| C6145-12-12 | \$28.35 |
| C6145-12-16 | \$31.67 |
| C6145-12-20 | \$51.21 |
| C6145-16-16 | \$35.75 |
| C6145-16-20 | \$45.65 |
| C6145-16-24 | \$57.25 |
| C6145-20-20 | \$45.72 |
| | |

C6190 Code 61 Flange 90°



| C6190-08-08 | \$26.29 |
|-------------|---------|
| C6190-08-12 | \$28.41 |
| C6190-12-12 | \$28.59 |
| C6190-12-16 | \$31.75 |
| C6190-12-20 | \$44.68 |
| C6190-16-16 | \$37.81 |
| C6190-16-20 | \$39.69 |
| C6190-16-24 | \$52.95 |
| C6190-20-20 | \$45.02 |
| | |

61SF-KIT

Code 61 Split Flange Kit



| 61SF-08-KIT | \$6.92 |
|-------------|----------|
| 61SF-12-KIT | \$5.23 |
| 61SF-16-KIT | \$5.74 |
| 61SF-20-KIT | \$7.01 |
| 61SF-24-KIT | \$9.31 |
| 61SF-32-KIT | \$10.17 |
| 61SF-40-KIT | \$18.59 |
| 61SF-48-KIT | \$19.18 |
| 61SF-56-KIT | \$125.46 |
| 61SF-64-KIT | \$147.47 |

610

Buna O-Ring for Code 61 and Code 62 Flanges

| \bigcirc | |
|------------|--------|
| 610-08 | \$0.22 |
| 610-12 | \$0.25 |
| 610-16 | \$0.29 |
| 610-20 | \$0.34 |
| 610-24 | \$0.44 |
| 610-32 | \$0.51 |

MT

Flareless Male

| MT-04-04 | \$6.07 |
|----------|---------|
| MT-04-05 | \$6.94 |
| MT-04-06 | \$16.62 |
| MT-04-08 | \$20.36 |
| MT-06-04 | \$16.84 |
| MT-06-05 | \$6.70 |
| MT-06-06 | \$6.58 |
| MT-06-08 | \$7.36 |
| MT-08-08 | \$8.85 |
| MT-08-10 | \$9.58 |
| MT-08-12 | \$26.62 |
| MT-12-12 | \$14.12 |
| MT-12-16 | \$29.78 |
| MT-16-16 | \$20.06 |
| | |

\$13.63

MIX90

MIX90-03-04

MIX90-04-03

MIX90-04-04

MIX90-04-05

MIX90-04-06

MIX90-06-04

MIX90-06-05

MIX90-06-06

MIX90-06-07

MIX90-06-08 MIX90-08-08

MIX90-08-10

SAE 45° Female Swivel

FSX

FSX-04-06

FSX-05-06

FSX-06-06

FSX-12-12

90°



LF

Flareless Female Swivel

| LF-04-04 | |
|----------|--|
| LF-04-05 | |

| LF-04-05 | \$17.72 |
|----------|---------|
| LF-04-06 | \$14.41 |
| LF-04-08 | \$17.46 |
| LF-06-05 | \$20.36 |
| LF-06-06 | \$14.98 |
| LF-06-08 | \$14.58 |
| LF-06-10 | \$24.55 |
| LF-08-08 | \$15.77 |
| LF-08-10 | \$19.04 |
| LF-08-12 | \$20.31 |
| LF-12-12 | \$19.37 |

GT

Grease Trap Female



| GT-04-08 | \$7.47 |
|----------|--------|
| GT-06-08 | \$7.64 |

KAR


Karcher Pressure Wash Female Swivel



KAR-04-22 \$6.42 KAR-06-22 \$6.27

ΜΙΧ


Inverted Flare Male Swivel



| MIX-04-03 | \$8.94 |
|-----------|---------|
| MIX-04-04 | \$8.53 |
| MIX-04-05 | \$8.57 |
| MIX-04-06 | \$9.25 |
| MIX-06-04 | \$8.61 |
| MIX-06-05 | \$9.42 |
| MIX-06-06 | \$9.09 |
| MIX-06-07 | \$9.94 |
| MIX-06-08 | \$9.25 |
| MIX-08-08 | \$10.67 |
| MIX-08-10 | \$11.52 |
| | |

MIX45

Inverted Flare Male Swivel 45°




| | • |
|-------------|---------|
| MIX45-04-03 | \$9.14 |
| MIX45-04-04 | \$8.58 |
| MIX45-04-05 | \$9.60 |
| MIX45-04-06 | \$9.84 |
| MIX45-06-05 | \$7.70 |
| MIX45-06-06 | \$9.10 |
| MIX45-06-07 | \$9.94 |
| MIX45-06-08 | \$11.26 |
| MIX45-08-08 | \$9.44 |
| MIX45-08-10 | \$20.09 |

Inverted Flare Male Swivel

FSXT


SAE 45° Female Swivel Long



| FSXT-04-04 | \$7.89 |
|------------|---------|
| FSXT-04-05 | \$15.77 |
| FSXT-06-04 | \$12.44 |
| FSXT-06-05 | \$15.77 |
| FSXT-06-06 | \$7.95 |
| FSXT-06-08 | \$14.90 |
| FSXT-08-08 | \$10.93 |
| FSXT-08-10 | \$14.22 |

FSX45

SAE 45° Female Swivel 45°



| \$10.05 |
|---------|
| \$12.94 |
| \$14.71 |
| \$8.58 |
| \$11.16 |
| \$15.06 |
| \$20.70 |
| \$12.63 |
| |

FSX90

\$8.11

\$9.45

\$8.96

\$7.75

\$7.89

\$7.98

\$11.95

\$10.11

\$12.17 \$12.10

\$12.22

\$21.80


\$4.88

\$6.17

\$3.53

\$7.77

SAE 45° Female Swivel 90°



FSX90-04-04 \$8.60 FSX90-04-05 \$12.75 FSX90-05-06 \$15.03 FSX90-06-04 \$11.56 FSX90-06-05 \$13.07 FSX90-06-06 \$9.38 FSX90-06-08 \$10.87 FSX90-08-08 \$11.16 FSX90-08-10 \$15.06 FSX90-10-12 \$22.17

\$13.85

FSX90-12-12

MS

SAE 45° Male Rigid



| \$15.08 |
|---------|
| \$15.32 |
| \$17.46 |
| \$5.70 |
| \$16.03 |
| \$15.32 |
| \$11.55 |
| |

FW

Weld Fitting Female




| FW-03-04 | \$4.77 |
|----------|---------|
| FW-04-04 | \$3.14 |
| FW-04-05 | \$3.89 |
| FW-04-06 | \$3.72 |
| FW-06-06 | \$3.82 |
| FW-06-08 | \$3.58 |
| FW-08-08 | \$4.50 |
| FW-08-10 | \$5.36 |
| FW-12-12 | \$5.96 |
| FW-16-16 | \$17.21 |
| | |

MW

Stand Tube (North American)







MMSP Metric Stand Tube

|--|

| MMSP-04-06 | \$9.50 |
|------------|---------|
| MMSP-04-08 | \$8.88 |
| MMSP-04-10 | \$8.90 |
| MMSP-05-10 | \$9.07 |
| MMSP-05-12 | \$9.12 |
| MMSP-06-10 | \$10.28 |
| MMSP-06-12 | \$10.32 |
| MMSP-06-14 | \$10.77 |
| MMSP-08-15 | \$10.62 |
| MMSP-08-16 | \$10.79 |
| MMSP-08-18 | \$10.89 |
| MMSP-10-18 | \$12.02 |
| MMSP-10-20 | \$12.27 |
| MMSP-12-20 | \$12.46 |
| MMSP-12-22 | \$12.67 |
| MMSP-12-25 | \$12.95 |
| MMSP-16-25 | \$16.65 |
| MMSP-16-28 | \$16.94 |
| MMSP-16-30 | \$17.84 |
| | |

MMSP45 Metric Stand Tube 45°

| MMSP45-04-06 | \$14.98 |
|--------------|---------|
| MMSP45-04-08 | \$15.06 |
| MMSP45-04-10 | \$16.57 |
| MMSP45-06-10 | \$17.37 |
| MMSP45-06-12 | \$16.08 |
| MMSP45-06-14 | \$16.84 |
| MMSP45-08-15 | \$16.49 |
| MMSP45-08-16 | \$16.49 |
| MMSP45-08-18 | \$17.02 |
| MMSP45-10-18 | \$18.08 |
| MMSP45-10-20 | \$18.59 |
| MMSP45-12-20 | \$18.84 |
| MMSP45-12-22 | \$19.11 |
| MMSP45-12-25 | \$20.19 |
| MMSP45-16-25 | \$24.61 |
| MMSP45-16-28 | \$25.76 |
| MMSP45-16-30 | \$26.60 |
| | |

MMSP90

Metric Stand Tube 90°



| MMSP90-04-06 | \$15.03 |
|--------------|---------|
| MMSP90-04-08 | \$15.15 |
| MMSP90-04-10 | \$16.68 |
| MMSP90-06-10 | \$17.47 |
| MMSP90-06-12 | \$16.23 |
| MMSP90-06-14 | \$17.16 |
| MMSP90-08-15 | \$16.79 |
| MMSP90-08-16 | \$17.26 |
| MMSP90-08-18 | \$17.39 |
| MMSP90-10-18 | \$18.40 |
| MMSP90-10-20 | \$19.13 |
| MMSP90-12-20 | \$19.38 |
| MMSP90-12-22 | \$19.76 |
| MMSP90-12-25 | \$21.05 |
| MMSP90-16-25 | \$25.48 |
| MMSP90-16-28 | \$27.20 |
| MMSP90-16-30 | \$28.17 |
| | |

FBSPX Britich Standard


British Standard Pipe Female Swivel



| FBSPX-04-02 | \$24.26 |
|-------------|---------|
| FBSPX-03-04 | \$10.77 |
| FBSPX-04-04 | \$5.00 |
| FBSPX-04-06 | \$8.52 |
| FBSPX-06-04 | \$18.81 |
| FBSPX-06-06 | \$4.20 |
| FBSPX-06-08 | \$7.78 |
| FBSPX-08-06 | \$18.17 |
| FBSPX-08-08 | \$6.21 |
| FBSPX-08-10 | \$17.47 |
| FBSPX-10-08 | \$20.57 |
| FBSPX-10-10 | \$10.35 |
| FBSPX-10-12 | \$25.37 |
| FBSPX-12-12 | \$8.77 |
| FBSPX-12-16 | \$29.39 |
| FBSPX-16-16 | \$13.01 |
| FBSPX-20-20 | \$40.78 |
| | |

FBSPX45 British Standard Pipe


Female Swivel 45°



| FBSPX45-04-04 | \$11.42 |
|---------------|----------|
| FBSPX45-04-06 | \$14.15 |
| FBSPX45-06-06 | \$12.81 |
| FBSPX45-06-08 | \$15.78 |
| FBSPX45-08-08 | \$14.76 |
| FBSPX45-10-10 | \$24.80 |
| FBSPX45-12-12 | \$24.02 |
| FBSPX45-16-16 | \$33.97 |
| FBSPX45-20-20 | \$113.80 |

FBSPX90

British Standard Pipe Female Swivel 90°



| FBSPX90-04-04 | \$15.06 |
|---------------|---------|
| FBSPX90-04-06 | \$12.33 |
| FBSPX90-06-06 | \$13.83 |
| FBSPX90-06-08 | \$15.91 |
| FBSPX90-08-08 | \$14.58 |
| FBSPX90-08-10 | \$38.58 |
| FBSPX90-10-10 | \$16.67 |
| FBSPX90-10-12 | \$28.70 |
| FBSPX90-12-12 | \$36.33 |
| FBSPX90-16-16 | \$29.49 |
| | |

MBSPP

British Standard Pipe Parallel Male Rigid



| MBSPP-04-04 | \$8.15 |
|-------------|---------|
| MBSPP-04-06 | \$16.51 |
| MBSPP-06-06 | \$4.15 |
| MBSPP-06-08 | \$31.00 |
| MBSPP-08-06 | \$19.25 |
| MBSPP-08-08 | \$6.01 |
| MBSPP-10-10 | \$49.95 |
| MBSPP-12-12 | \$18.66 |
| MBSPP-16-16 | \$35.08 |
| | |

MBSPT

British Pipe Taper Male Rigid

| MBSPT-04-02 | \$19.37 |
|-------------|---------|
| MBSPT-04-04 | \$7.63 |

| MBSPT-04-04 | \$7.63 |
|-------------|---------|
| MBSPT-04-06 | \$11.88 |
| MBSPT-06-06 | \$4.54 |
| MBSPT-06-08 | \$13.11 |
| MBSPT-08-06 | \$13.68 |
| MBSPT-08-08 | \$5.16 |
| MBSPT-12-12 | \$7.07 |
| MBSPT-16-16 | \$10.63 |

FBFPX

BSP Flat Face (HIAB) Female Swivel

| FBFPX-06-06 | \$9.94 |
|-------------|---------|
| FBFPX-06-08 | \$11.90 |
| FBFPX-08-08 | \$17.46 |
| FBFPX-12-12 | \$25.78 |



FJISX

Japanese Industrial Standard (JIS 30°) Female Swivel



Threads are similar to BSPP.

| FJISX-04-04 | \$5.64 |
|-------------|---------------------|
| | |
| FJISX-06-06 | \$4.66 |
| | ć 4 0 0 |
| FJISX-08-08 | \$4.92 |
| FJISX-10-10 | \$24.47 |
| FJI3X-10-10 | <u>ې۲4.4</u> / |
| FIISX-12-12 | \$12.45 |
| 11124-12-12 | γ12. - J |
| FJISX-16-16 | \$16.66 |
| 1313/ 10-10 | J10.00 |

FKOMX

Komatsu (Metric JIS) Female Swivel



| FKOMX-04-14 | \$11.26 |
|-------------|----------|
| FKOMX-06-18 | \$13.01 |
| FKOMX-08-22 | \$13.24 |
| FKOMX-08-24 | \$17.02 |
| FKOMX-10-24 | \$18.59 |
| FKOMX-12-30 | \$18.00 |
| FKOMX-16-33 | \$26.10 |
| FKOMX-20-36 | \$117.36 |

FDINLX


DIN Light (Metric) Universal Seat Female Swivel



| FDINLX-04-12 | \$20.31 |
|--------------|---------|
| FDINLX-04-14 | \$8.06 |
| FDINLX-04-16 | \$8.61 |
| FDINLX-06-16 | \$17.97 |
| FDINLX-06-18 | \$17.36 |
| FDINLX-08-22 | \$5.92 |
| FDINLX-10-26 | \$7.70 |
| FDINLX-12-30 | \$16.18 |
| FDINLX-16-36 | \$23.15 |
| | |

FDINLX45

DIN Light (Metric) Universal Seat Female Swivel 45°



| FDINLX45-04-14 | \$21.45 |
|----------------|---------|
| FDINLX45-04-16 | \$20.57 |
| FDINLX45-06-16 | \$27.99 |
| FDINLX45-06-18 | \$12.63 |
| FDINLX45-08-22 | \$14.58 |
| FDINLX45-10-26 | \$22.18 |
| FDINLX45-12-30 | \$23.95 |
| FDINLX45-16-36 | \$28.28 |
| | |

FDINLX90

DIN Light (Metric) Universal Seat Female Swivel 90°



| FDINLX90-04-14 | \$18.30 |
|----------------|---------|
| FDINLX90-04-16 | \$20.27 |
| FDINLX90-06-16 | \$27.31 |
| FDINLX90-06-18 | \$13.01 |
| FDINLX90-08-22 | \$14.71 |
| FDINLX90-10-26 | \$22.68 |
| FDINLX90-12-30 | \$24.32 |
| FDINLX90-16-36 | \$28.34 |
| | |

MDL

DIN Light (Metric) Universal Seat Male



| \$15.63 |
|---------|
| \$14.99 |
| \$10.48 |
| \$14.13 |
| \$6.57 |
| \$16.08 |
| \$6.30 |
| \$18.54 |
| \$13.31 |
| \$19.76 |
| |

FDINHX


DIN Heavy (Metric) Universal Seat Female Swivel



| FDINHX-04-16 | \$18.54 |
|--------------|---------|
| FDINHX-04-18 | \$8.82 |
| FDINHX-06-16 | \$51.08 |
| FDINHX-06-20 | \$18.47 |
| FDINHX-06-22 | \$5.89 |
| FDINHX-08-20 | \$20.61 |
| FDINHX-08-24 | \$10.11 |
| FDINHX-10-30 | \$7.70 |
| FDINHX-12-36 | \$11.43 |
| FDINHX-16-42 | \$52.21 |
| | |

FDINHX45


DIN Heavy (Metric) Universal Seat Female Swivel 45°



| FDINHX45-04-16 | \$20.36 |
|----------------|---------|
| FDINHX45-04-18 | \$14.12 |
| FDINHX45-06-20 | \$24.57 |
| FDINHX45-06-22 | \$14.41 |
| FDINHX45-08-24 | \$16.85 |
| FDINHX45-10-30 | \$20.66 |
| FDINHX45-12-36 | \$25.00 |
| FDINHX45-16-42 | \$28.74 |

FDINHX90

DIN Heavy (Metric) Universal Seat Female Swivel 90°




MDH

DIN Heavy (Metric) Universal Seat Male



| MDH-04-08-16 | \$20.72 |
|--------------|---------|
| MDH-04-10-18 | \$8.38 |
| MDH-06-10-18 | \$15.89 |
| MDH-06-12-20 | \$16.08 |
| MDH-06-14-22 | \$8.47 |
| MDH-08-16-24 | \$8.57 |
| MDH-10-20-30 | \$9.18 |
| MDH-12-25-36 | \$14.69 |
| MDH-16-30-42 | \$21.96 |
| | |





FJX JIC 37° Female Swivel



| FJX-04-04W | \$4.05 |
|------------|---------|
| FJX-04-05W | \$4.27 |
| FJX-04-06W | \$4.44 |
| FJX-06-04W | \$10.69 |
| FJX-06-05W | \$12.41 |
| FJX-06-06W | \$6.42 |
| FJX-06-08W | \$5.63 |
| FJX-06-10W | \$7.98 |
| FJX-08-06W | \$8.34 |
| FJX-08-08W | \$8.46 |
| FJX-08-10W | \$9.18 |
| FJX-08-12W | \$9.46 |
| FJX-10-08W | \$15.00 |
| FJX-10-10W | \$8.44 |
| FJX-10-12W | \$10.51 |
| FJX-12-08W | \$16.98 |
| FJX-12-10W | \$9.75 |
| FJX-12-12W | \$8.86 |
| FJX-12-14W | \$16.33 |
| FJX-12-16W | \$17.89 |
| FJX-16-12W | \$23.40 |
| FJX-16-16W | \$17.50 |
| FJX-16-20W | \$25.52 |
| FJX-20-16W | \$41.83 |
| FJX-20-20W | \$32.84 |
| FJX-20-24W | \$73.52 |
| FJX-24-24W | \$38.89 |
| FJX-32-32W | \$86.12 |


SS-FJX

JIC 37° Female Swivel Stainless Steel



| .23 |
|-----|
| .94 |
| .00 |
| .83 |
| |


FJX45



| FJX45-04-04W | \$8.24 |
|--------------|----------|
| FJX45-04-06W | \$8.49 |
| FJX45-06-06W | \$17.66 |
| FJX45-06-08W | \$18.56 |
| FJX45-08-08W | \$20.00 |
| FJX45-08-10W | \$21.06 |
| FJX45-10-10W | \$15.18 |
| FJX45-10-12W | \$21.35 |
| FJX45-12-12W | \$29.59 |
| FJX45-12-16W | \$35.71 |
| FJX45-16-16W | \$41.38 |
| FJX45-16-20W | \$44.35 |
| FJX45-20-20W | \$61.50 |
| FJX45-20-24W | \$63.68 |
| FJX45-24-24W | \$71.38 |
| FJX45-32-32W | \$111.49 |
| | |

FJX90

JIC 37° Female Swivel 90°




| FJX90-04-04W | \$7.36 |
|--------------|----------|
| FJX90-04-05W | \$9.70 |
| FJX90-04-06W | \$9.28 |
| FJX90-06-04W | \$11.45 |
| FJX90-06-06W | \$14.51 |
| FJX90-06-08W | \$10.27 |
| FJX90-08-06W | \$12.00 |
| FJX90-08-08W | \$15.54 |
| FJX90-08-10W | \$20.95 |
| FJX90-08-12W | \$20.22 |
| FJX90-10-10W | \$13.79 |
| FJX90-10-12W | \$19.76 |
| FJX90-12-12W | \$26.88 |
| FJX90-12-16W | \$35.71 |
| FJX90-16-16W | \$37.56 |
| FJX90-16-20W | \$44.35 |
| FJX90-20-20W | \$55.87 |
| FJX90-20-24W | \$65.91 |
| FJX90-24-24W | \$75.53 |
| FJX90-32-32W | \$115.38 |
| | |

W Series Hose Fittings feature a bite-to-the wire-design, and are intended for use with 4SH (up to size -24), R12, R13 (up to size -16), R1, R2, R16, R17 and KT hydraulic hoses.



FJX90L

JIC 37° Female Swivel 90° Long



| FJX90L-04-04W | \$10.57 |
|---------------|---------|
| FJX90L-06-06W | \$10.35 |
| FJX90L-06-08W | \$13.14 |
| FJX90L-08-08W | \$14.56 |
| FJX90L-08-10W | \$13.10 |
| FJX90L-10-10W | \$19.43 |
| FJX90L-12-12W | \$30.50 |
| FJX90L-16-16W | \$47.42 |
| | |

MJ JIC 37° Male Rigid



| MJ-04-04W | \$3.58 |
|-----------|---------|
| MJ-04-05W | \$7.44 |
| MJ-04-06W | \$4.55 |
| MJ-06-05W | \$9.78 |
| MJ-06-06W | \$5.45 |
| MJ-06-08W | \$7.14 |
| MJ-06-10W | \$10.41 |
| MJ-08-06W | \$12.03 |
| MJ-08-08W | \$6.54 |
| MJ-08-10W | \$9.74 |
| MJ-08-12W | \$10.56 |
| MJ-10-10W | \$8.64 |
| MJ-12-12W | \$12.24 |
| MJ-12-14W | \$12.31 |
| MJ-12-16W | \$12.95 |
| MJ-16-16W | \$20.42 |
| MJ-16-20W | \$23.00 |
| MJ-20-20W | \$23.88 |
| MJ-20-24W | \$55.37 |
| MJ-24-24W | \$37.74 |
| MJ-32-32W | \$86.12 |

MP NPTF Male Pipe Rigid

| MP-04-02W | \$3.42 |
|-----------|---------|
| MP-04-04W | \$3.18 |
| MP-04-06W | \$5.94 |
| MP-04-08W | \$9.78 |
| MP-06-04W | \$3.38 |
| MP-06-06W | \$4.16 |
| MP-06-08W | \$4.75 |
| MP-08-06W | \$8.22 |
| MP-08-08W | \$5.50 |
| MP-08-12W | \$8.88 |
| MP-10-06W | \$26.82 |
| MP-10-08W | \$6.80 |
| MP-10-12W | \$7.14 |
| MP-12-08W | \$9.92 |
| MP-12-12W | \$7.36 |
| MP-12-16W | \$12.62 |
| MP-16-12W | \$16.00 |
| MP-16-16W | \$11.14 |
| MP-16-20W | \$21.68 |
| MP-20-20W | \$30.10 |
| MP-20-24W | \$29.98 |
| MP-24-24W | \$33.96 |
| MP-32-32W | \$52.80 |
| | |

SS-MP

NPTF Male Pipe Rigid Stainless Steel




| SS-MP-08-08W | \$78.58 |
|--------------|----------|
| SS-MP-12-12W | \$102.95 |
| SS-MP-16-16W | \$124.48 |
| SS-MP-20-20W | \$228.11 |
| SS-MP-24-24W | \$259.74 |
| SS-MP-32-32W | \$438.14 |
| | |

W Series Hose Fittings



MPX


NPTF Male Pipe Swivel



MPX-04-04W \$5.60 MPX-04-06W \$6.86 MPX-06-04W \$6.96 MPX-06-06W \$5.66 MPX-06-08W \$7.75 MPX-08-06W \$8.94 MPX-08-08W \$6.96 MPX-12-12W \$11.10 MPX-16-16W \$16.86

MPX90

NPTF Male Pipe Swivel 90°



MPX90-04-04W\$11.30MPX90-06-06W\$13.41MPX90-06-08W\$14.70MPX90-08-08W\$12.71MPX90-12-12W\$33.18

FP

NPTF Female Pipe Rigid



| FP-04-02W | \$7.80 |
|-----------|---------|
| FP-04-04W | \$2.98 |
| FP-04-06W | \$6.24 |
| FP-06-04W | \$9.42 |
| FP-06-06W | \$5.93 |
| FP-06-08W | \$9.73 |
| FP-08-08W | \$5.74 |
| FP-12-12W | \$14.67 |

NPSM Female Pipe Swivel



| FPX-04-04W | \$3.61 |
|------------|---------|
| FPX-06-06W | \$4.36 |
| FPX-08-08W | \$5.81 |
| FPX-12-12W | \$12.26 |
| FPX-16-16W | \$19.43 |

MB


SAE Straight Thread O-Ring Boss Male Rigid



| \$3.89 |
|---------|
| \$6.50 |
| \$4.33 |
| \$5.18 |
| \$4.65 |
| \$7.51 |
| \$12.00 |
| \$5.18 |
| \$5.92 |
| \$13.05 |
| \$15.66 |
| \$17.85 |
| \$12.24 |
| \$61.99 |
| \$15.92 |
| \$28.26 |
| \$19.59 |
| |

MBX


SAE Straight Thread O-Ring Boss Male Swivel



| MBX-04-04W | \$8.06 |
|------------|---------|
| MBX-06-06W | \$7.60 |
| MBX-06-08W | \$7.77 |
| MBX-08-08W | \$8.56 |
| MBX-08-10W | \$8.61 |
| MBX-12-12W | \$12.50 |

MBX90

SAE Straight Thread O-Ring Boss Male Swivel



MBX90-06-06W\$13.66MBX90-06-08W\$14.90MBX90-08-08W\$15.55MBX90-08-10W\$16.75MBX90-12-12W\$33.18


FFX O-Ring Face Seal (ORFS) Female Swivel



| FFX-04-04W | \$3.93 |
|------------|---------|
| FFX-04-06W | \$8.45 |
| FFX-04-08W | \$16.10 |
| FFX-06-06W | \$8.49 |
| FFX-06-08W | \$10.11 |
| FFX-08-06W | \$17.12 |
| FFX-08-08W | \$8.85 |
| FFX-08-10W | \$9.28 |
| FFX-08-12W | \$17.81 |
| FFX-10-08W | \$21.30 |
| FFX-10-10W | \$11.75 |
| FFX-10-12W | \$18.71 |
| FFX-12-10W | \$15.50 |
| FFX-12-12W | \$13.62 |
| FFX-12-16W | \$20.60 |
| FFX-16-12W | \$27.97 |
| FFX-16-16W | \$17.31 |
| FFX-16-20W | \$42.89 |
| FFX-20-20W | \$42.87 |
| FFX-20-24W | \$84.27 |
| FFX-24-24W | \$62.44 |
| | |
| | |
| | |

FFX45


O-Ring Face Seal (ORFS) Female Swivel 45°



| FFX45-04-04W | \$11.71 |
|--------------|---------|
| FFX45-04-06W | \$14.58 |
| FFX45-06-06W | \$17.09 |
| FFX45-06-08W | \$22.79 |
| FFX45-08-08W | \$17.47 |
| FFX45-08-10W | \$18.51 |
| FFX45-08-12W | \$27.27 |
| FFX45-10-10W | \$20.70 |
| FFX45-10-12W | \$40.86 |
| FFX45-12-10W | \$64.97 |
| FFX45-12-12W | \$24.92 |
| FFX45-12-16W | \$29.23 |
| FFX45-16-16W | \$30.28 |
| FFX45-16-20W | \$48.85 |
| FFX45-20-20W | \$44.66 |
| FFX45-20-24W | \$73.34 |
| FFX45-24-24W | \$72.33 |
| | |

FFX90

O-Ring Face Seal (ORFS) Female Swivel 90°




| FFX90-04-04W | \$10.77 |
|--------------|---------|
| FFX90-04-06W | \$14.68 |
| FFX90-04-08W | \$16.49 |
| FFX90-06-04W | \$40.56 |
| FFX90-06-06W | \$10.05 |
| FFX90-06-08W | \$14.92 |
| FFX90-08-08W | \$10.48 |
| FFX90-08-10W | \$11.52 |
| FFX90-08-12W | \$27.35 |
| FFX90-10-08W | \$19.74 |
| FFX90-10-10W | \$13.81 |
| FFX90-12-10W | \$28.63 |
| FFX90-12-12W | \$27.28 |
| FFX90-12-16W | \$35.92 |
| FFX90-16-16W | \$32.31 |
| FFX90-16-20W | \$53.97 |
| FFX90-20-20W | \$46.25 |
| FFX90-20-24W | \$78.08 |
| FFX90-24-24W | \$86.91 |
| | |

Discount Hydraulic Hose

FFX90M

O-Ring Face Seal (ORFS) Female Swivel 90° Medium



 FFX90M-04-04W
 \$12.63

 FFX90M-06-06W
 \$21.75


 FFX90M-08-08W
 \$15.86

 FFX90M-12-12W
 \$27.94

 FFX90M-16-16W
 \$24.53

FFX90L

O-Ring Face Seal (ORFS) Female Swivel 90° Long



| FFX90L-04-04\ | N | \$19.26 |
|---------------|---|---------|
| FFX90L-06-06\ | N | \$14.71 |
| FFX90L-06-08\ | N | \$25.91 |
| FFX90L-08-08\ | N | \$14.24 |
| FFX90L-08-10\ | N | \$30.48 |
| FFX90L-10-10\ | N | \$26.53 |
| FFX90L-10-12\ | N | \$48.46 |
| FFX90L-12-12\ | N | \$30.46 |
| FFX90L-16-16\ | N | \$54.30 |
| FFX90L-20-20\ | N | \$74.54 |
| | | |

MF

O-Ring Face Seal (ORFS) Male Rigid



| MF-04-04W | \$6.96 |
|-----------|---------|
| MF-04-06W | \$17.21 |
| MF-06-06W | \$7.14 |
| MF-06-08W | \$11.79 |
| MF-08-08W | \$8.56 |
| MF-08-10W | \$9.04 |
| MF-08-12W | \$29.80 |
| MF-10-10W | \$13.82 |
| MF-10-12W | \$14.46 |
| MF-12-12W | \$23.85 |
| MF-12-16W | \$60.17 |
| MF-16-12W | \$63.24 |
| MF-16-16W | \$29.18 |
| | |

C61 Code 61 Flange



| C61-08-08W | \$14.47 |
|------------|----------|
| C61-08-12W | \$29.07 |
| C61-12-12W | \$16.46 |
| C61-12-16W | \$17.80 |
| C61-16-16W | \$22.98 |
| C61-16-20W | \$23.11 |
| C61-16-24W | \$55.65 |
| C61-20-20W | \$26.43 |
| C61-20-24W | \$31.80 |
| C61-24-24W | \$44.47 |
| C61-24-32W | \$112.26 |
| C61-32-32W | \$64.74 |
| | |

C6122 Code 61 Flange 22°



| C6122-12-12W | \$26.59 |
|--------------|---------|
| C6122-12-16W | \$27.10 |
| C6122-16-16W | \$33.18 |
| C6122-16-20W | \$28.73 |
| C6122-20-20W | \$45.35 |
| C6122-20-24W | \$42.78 |
| C6122-24-24W | \$61.22 |
| C6122-32-32W | \$91.49 |
| | |

C6130 Code 61 Flange 30°



| C6130-12-12W | \$22.24 |
|--------------|---------|
| C0150-12-12W | ۶ZZ.Z4 |
| C6130-12-16W | \$22.87 |
| C6130-16-16W | \$28.30 |
| C6130-16-20W | \$28.74 |
| C6130-20-20W | \$42.78 |
| C6130-20-24W | \$42.84 |
| C6130-24-24W | \$57.63 |
| C6130-32-32W | \$79.96 |

C6145

C6160

Code 61 Flange 60°

C6160-08-12W

C6160-12-12W

C6160-12-16W

C6160-16-16W

C6160-16-20W


C6160-20-20W

C6160-20-24W

C6160-24-24W

C6160-32-32W

Code 61 Flange 45°



| C6145-08-08W | \$21.70 |
|--------------|----------|
| C6145-08-12W | \$24.86 |
| C6145-12-12W | \$23.61 |
| C6145-12-16W | \$23.23 |
| C6145-16-16W | \$30.29 |
| C6145-16-20W | \$28.74 |
| C6145-20-20W | \$40.24 |
| C6145-20-24W | \$42.78 |
| C6145-24-24W | \$51.87 |
| C6145-24-32W | \$77.43 |
| C6145-32-32W | \$86.92 |
| C6145-32-40W | \$157.41 |


C6190

Code 61 Flange 90°

| C6190-08-08W | \$23.23 |
|--------------|---------|
| C6190-08-12W | \$31.85 |
| C6190-12-12W | \$23.61 |
| C6190-12-16W | \$27.86 |
| C6190-16-16W | \$30.10 |
| C6190-16-20W | \$29.74 |
| C6190-20-20W | \$41.25 |
| C6190-20-24W | \$43.95 |
| C6190-24-24W | \$53.39 |
| C6190-24-32W | \$99.98 |
| C6190-32-32W | \$88.82 |



Code 61 Flange 90° Long



| C6190L-08-12W | \$36.84 |
|---------------|---------|
| C6190L-12-12W | \$33.79 |
| C6190L-16-16W | \$43.75 |
| C6190L-16-20W | \$47.22 |

61SF-KIT Code 61 Split Flange Kit



\$37.08

\$22.46

\$24.85

\$33.67

\$34.96

\$39.88

\$40.71

\$50.49

\$80.55

| 61SF-08-KIT | \$6.92 |
|-------------|----------|
| 61SF-12-KIT | \$5.23 |
| 61SF-16-KIT | \$5.74 |
| 61SF-20-KIT | \$7.01 |
| 61SF-24-KIT | \$9.31 |
| 61SF-32-KIT | \$10.17 |
| 61SF-40-KIT | \$18.59 |
| 61SF-48-KIT | \$19.18 |
| 61SF-56-KIT | \$125.46 |
| 61SF-64-KIT | \$147.47 |
| | |



W Series Hose Fittings





Hydraulic O-Ring Assortment

A full assortment of O-rings for split flange, face seal, and straight thread (ORB) connectors in a handy steel case.

Kit includes 12 O-rings of each size shown below (also sold separately).

| ltem # | Description | Price |
|-----------|----------------------------------|----------|
| DRG24 | Complete Kit (288 O-Rings) | \$206.46 |
| 610-08 | Split Flange O-Ring | \$0.23 |
| 610-12 | Split Flange O-Ring | \$0.25 |
| 610-16 | Split Flange O-Ring | \$0.30 |
| 610-20 | Split Flange O-Ring | \$0.38 |
| 610-24 | Split Flange O-Ring | \$0.47 |
| 610-32 | Split Flange O-Ring | \$0.58 |
| 4000-02 | Split Flange O-Ring | \$0.26 |
| 4000-03 | SAE Straight Thread (ORB) O-Ring | \$0.26 |
| 4000-04 | SAE Straight Thread (ORB) O-Ring | \$0.25 |
| 4000-05 | SAE Straight Thread (ORB) O-Ring | \$0.42 |
| 4000-06 | SAE Straight Thread (ORB) O-Ring | \$0.42 |
| 4000-08 | SAE Straight Thread (ORB) O-Ring | \$0.42 |
| 4000-10 | SAE Straight Thread (ORB) O-Ring | \$0.55 |
| 4000-12 | SAE Straight Thread (ORB) O-Ring | \$0.55 |
| 4000-14 | SAE Straight Thread (ORB) O-Ring | \$1.14 |
| 4000-16 | SAE Straight Thread (ORB) O-Ring | \$1.17 |
| 4000-20 | SAE Straight Thread (ORB) O-Ring | \$1.25 |
| 4000-24 | SAE Straight Thread (ORB) O-Ring | \$1.35 |
| 4000-32 | SAE Straight Thread (ORB) O-Ring | \$2.91 |
| FS4000-04 | O-Ring Face Seal (ORFS) O-Ring | \$0.14 |
| FS4000-06 | O-Ring Face Seal (ORFS) O-Ring | \$0.17 |
| FS4000-08 | O-Ring Face Seal (ORFS) O-Ring | \$0.20 |
| FS4000-10 | O-Ring Face Seal (ORFS) O-Ring | \$0.24 |
| FS4000-12 | O-Ring Face Seal (ORFS) O-Ring | \$0.36 |
| FS4000-16 | O-Ring Face Seal (ORFS) O-Ring | \$0.45 |
| FS4000-20 | O-Ring Face Seal (ORFS) O-Ring | \$0.68 |
| FS4000-24 | O-Ring Face Seal (ORFS) O-Ring | \$0.35 |

610

C62

Code 62 Flange

C62-12-08W

C62-12-12W

C62-12-16W

C62-16-16W

C62-16-20W

C62-20-20W

C62-20-24W

C62-24-24W

C62-32-32W

C6222

C6222-12-12W

C6222-12-16W

C6222-16-16W

C6222-16-20W

C6222-20-20W

C6222-20-24W

C6222-24-24W

Code 62 Flange 22°

Buna O-Ring for Code 61 and Code 62 Flanges

| \bigcirc | |
|------------|--------|
| 610-08 | \$0.21 |
| 610-12 | \$0.24 |
| 610-16 | \$0.28 |
| 610-20 | \$0.32 |
| 610-24 | \$0.43 |
| 610-32 | \$0.49 |

C6230


Code 62 Flange 30°



| C6230-12-12W | \$38.85 |
|--------------|---------|
| C6230-12-16W | \$38.36 |
| C6230-16-16W | \$35.73 |
| C6230-16-20W | \$46.29 |
| C6230-20-20W | \$61.04 |
| C6230-20-24W | \$67.87 |
| C6230-24-24W | \$71.46 |
| | |

C6245

Code 62 Flange 45°



| C6245-12-12W | \$32.76 |
|---------------|----------|
| C6245-12-16W | \$35.22 |
| C6245-16-12W | \$46.04 |
| C6245-16-16W | \$39.51 |
| C6245-16-20W | \$42.43 |
| C6245-20-20W | \$59.28 |
| C6245L-20-20W | \$162.20 |
| C6245-20-24W | \$62.87 |
| C6245-24-24W | \$69.31 |
| C6245-32-32W | \$97.35 |
| C6245-32-32W | \$96.48 |

C6260

\$36.34

\$26.16

\$45.72

\$33.40

\$64.33

\$43.60

\$62.14

\$53.17

\$76.00

\$41.49

\$38.36

\$34.62

\$40.89

\$57.50

\$58.89

\$70.21


Code 62 Flange 60°



C6260-24-32W

C6290

Code 62 Flange 90°



| C6290-12-12W | \$34.52 |
|--------------|----------|
| C6290-12-16W | \$34.98 |
| C6290-16-16W | \$41.48 |
| C6290-16-20W | \$45.28 |
| C6290-20-16W | \$95.42 |
| C6290-20-20W | \$60.92 |
| C6290-20-24W | \$64.39 |
| C6290-24-24W | \$79.77 |
| C6290-32-32W | \$100.05 |
| | |



62SF-KIT Code 62 Split Flange Kit

| 62SF-08-KIT | \$14.02 |
|-------------|---------|
| 62SF-12-KIT | \$10.46 |
| 62SF-16-KIT | \$13.00 |
| 62SF-20-KIT | \$16.98 |
| 62SF-24-KIT | \$23.32 |
| 62SF-32-KIT | \$40.96 |

CAT

Caterpillar Flange

| \$25.20 |
|---------|
| \$29.86 |
| \$30.20 |
| \$36.50 |
| \$49.26 |
| \$59.37 |
| |

CAT45

CAT-24-24W

Caterpillar Flange 45°

| | \gg |
|--|-------|
|--|-------|

| CAT45-12-12W | \$37.13 |
|--------------|----------|
| CAT45-12-16W | \$61.83 |
| CAT45-16-16W | \$50.21 |
| CAT45-16-20W | \$76.30 |
| CAT45-20-20W | \$60.49 |
| CAT45-20-24W | \$84.75 |
| CAT45-24-24W | \$112.19 |

CAT90

Caterpillar Flange 90°



| CAT90-12-12W | \$30.93 |
|--------------|---------|
| CAT90-12-16W | \$47.11 |
| CAT90-16-16W | \$38.70 |
| CAT90-16-20W | \$70.01 |
| CAT90-20-20W | \$51.26 |
| CAT90-20-24W | \$85.30 |
| CAT90-24-24W | \$98.79 |

CAT Split Flange Half

| R | |
|---|--|
| | |

| CAT-12H | \$12.72 |
|---------|---------|
| CAT-16H | \$13.77 |
| CAT-20H | \$14.98 |
| CAT-24H | \$19.39 |
| CAT-32H | \$25.41 |
| | |

ΜΙΧ

\$68.15


Inverted Flare Male Swivel



| MIX-04-04W | \$8.21 |
|------------|---------|
| MIX-04-05W | \$9.99 |
| MIX-04-06W | \$11.16 |
| MIX-06-05W | \$11.32 |
| MIX-06-06W | \$9.58 |
| MIX-08-08W | \$11.84 |
| MW-06-06W | \$6.45 |
| | |

MIX45


Inverted Flare Male Swivel 45°



| MIX45-04-04W | \$9.04 |
|--------------|---------|
| MIX45-04-05W | \$11.53 |
| MIX45-04-06W | \$23.99 |
| MIX45-06-05W | \$12.17 |
| MIX45-06-06W | \$10.41 |
| MIX45-08-08W | \$11.90 |

MIX90

Inverted Flare Male Swivel 90°



| MIX90-04-04W | \$9.68 |
|--------------|---------|
| MIX90-04-05W | \$11.36 |
| MIX90-04-06W | \$11.61 |
| MIX90-06-05W | \$12.38 |
| MIX90-06-06W | \$11.16 |
| MIX90-08-08W | \$13.80 |

FW Weld Fitting Female





FSX

SAE 45° Female Swivel



| FSX-04-06W | \$9.42 |
|------------|---------|
| FSX-06-06W | \$9.02 |
| FSX-12-12W | \$12.47 |

MΤ

Flareless Compression



| MT-04-04W | \$8.52 |
|-----------|---------|
| MT-04-06W | \$12.13 |
| MT-06-05W | \$10.33 |
| MT-06-06W | \$12.35 |
| MT-06-08W | \$12.44 |
| MT-08-08W | \$12.13 |
| MT-08-10W | \$15.06 |
| MT-12-12W | \$25.14 |
| MT-16-16W | \$26.23 |
| | |

MENDER

Hose Mender

|] |
|---|
| |

| MENDER-04W | \$12.88 |
|------------|---------|
| MENDER-06W | \$12.29 |
| MENDER-08W | \$13.38 |
| | |

W Series Hose Fittings



FBSPX


British Standard Pipe Female Swivel



| FBSPX-04-04W | \$5.88 |
|--------------|----------|
| FBSPX-04-06W | \$11.30 |
| FBSPX-06-06W | \$4.96 |
| FBSPX-06-08W | \$8.62 |
| FBSPX-08-08W | \$6.30 |
| FBSPX-08-10W | \$16.40 |
| FBSPX-10-10W | \$11.30 |
| FBSPX-12-12W | \$9.50 |
| FBSPX-16-16W | \$12.13 |
| FBSPX-20-20W | \$47.89 |
| FBSPX-24-24W | \$101.60 |


FBSPX45

British Standard Pipe Female Swivel 45°



| FBSPX45-04-04W | \$12.85 |
|----------------|---------|
| FBSPX45-06-06W | \$11.27 |
| FBSPX45-08-08W | \$12.88 |
| FBSPX45-10-10W | \$11.30 |
| FBSPX45-12-12W | \$20.93 |
| FBSPX45-16-16W | \$25.40 |
| | |


FBSPX90 British Standard Pipe Female Swivel 90°



| \$13.29 |
|---------|
| \$13.41 |
| \$32.51 |
| \$15.00 |
| \$28.02 |
| \$21.67 |
| \$41.95 |
| \$62.14 |
| |

FBSPX90B

British Standard Pipe Female Swivel 90° Block Style Elbow



FBSPX90B-06-06W \$36.28

MBSPP

British Standard Pipe Parallel Male Rigid



| MBSPP-04-04W | \$12.57 |
|--------------|---------|
| MBSPP-04-06W | \$12.65 |
| MBSPP-06-06W | \$11.97 |
| MBSPP-06-08W | \$17.79 |
| MBSPP-08-08W | \$13.61 |
| MBSPP-08-10W | \$19.43 |
| MBSPP-12-12W | \$30.18 |
| | |

FJISX

Japanese Industrial Standard (JIS 30°) Female Swivel



Threads are similar to BSPP.

| \$6.48 |
|---------|
| \$6.70 |
| \$8.55 |
| \$25.21 |
| \$19.37 |
| \$41.09 |
| |

FKOMX

Komatsu (Metric JIS) Female Swivel



| FKOMX-04-14W | \$9.22 |
|--------------|---------|
| FKOMX-06-14W | \$12.38 |
| FKOMX-06-18W | \$7.46 |
| FKOMX-08-22W | \$11.53 |
| FKOMX-08-24W | \$10.71 |
| FKOMX-10-24W | \$15.58 |
| FKOMX-12-30W | \$18.06 |
| FKOMX-16-33W | \$25.56 |
| | |



W Series Hose Fittings

FDL

DIN Light (Metric) Universal Seat Female Swivel



| FDL-04-08-14W | \$10.41 |
|---------------|---------|
| FDL-04-10-16W | \$10.87 |
| FDL-06-10-16W | \$11.45 |
| FDL-06-12-18W | \$11.03 |
| FDL-06-15-22W | \$11.75 |
| FDL-08-15-22W | \$12.63 |
| FDL-08-18-26W | \$22.32 |
| FDL-10-18-26W | \$21.96 |
| FDL-12-18-26W | \$24.71 |
| FDL-12-22-30W | \$25.10 |
| FDL-16-28-36W | \$33.73 |
| FDL-20-35-45W | \$73.15 |
| | |

FDL45

DIN Light (Metric) Universal Seat Female Swivel 45°

| [| |
|---|------------|
| | \searrow |

| FDL45-04-08-14W | \$17.22 |
|-----------------|---------|
| FDL45-04-10-16W | \$16.00 |
| FDL45-06-10-16W | \$17.47 |
| FDL45-06-12-18W | \$17.02 |
| FDL45-08-15-22W | \$18.06 |
| FDL45-10-18-26W | \$30.39 |
| FDL45-12-18-26W | \$33.53 |
| FDL45-12-22-30W | \$40.62 |
| FDL45-16-28-36W | \$51.38 |
| FDL45-20-35-45W | \$83.64 |

FDL90 DIN Light (Metric) Universal Seat

Female Swivel 90°

| FDL90-04-08-14W | \$17.02 |
|-----------------|---------|
| FDL90-04-10-16W | \$16.05 |
| FDL90-06-10-16W | \$17.28 |
| FDL90-06-12-18W | \$17.12 |
| FDL90-08-15-22W | \$19.04 |
| FDL90-08-18-26W | \$23.04 |
| FDL90-10-18-26W | \$30.84 |
| FDL90-12-18-26W | \$33.81 |
| FDL90-12-22-30W | \$37.55 |
| FDL90-16-28-36W | \$49.50 |
| FDL90-20-35-45W | \$85.86 |
| | |

MDL DIN Light (Metric) Universal Seat Male



| MDL-04-08-14W | \$11.14 |
|---------------|---------|
| MDL-04-10-16W | \$11.16 |
| MDL-06-10-16W | \$13.07 |
| MDL-06-12-18W | \$12.02 |
| MDL-06-15-22W | \$13.82 |
| MDL-08-12-18W | \$14.41 |
| MDL-08-15-22W | \$12.17 |
| MDL-10-18-26W | \$14.20 |
| MDL-12-22-30W | \$15.73 |
| MDL-16-28-36W | \$24.31 |
| | |


FDH

DIN Heavy (Metric) Universal Seat Female Swivel

| FDH-04-08-16W | \$11.40 |
|---------------|----------|
| FDH-04-10-18W | \$10.89 |
| FDH-06-08-16W | \$19.76 |
| FDH-06-12-20W | \$20.36 |
| FDH-06-14-22W | \$11.12 |
| FDH-08-16-24W | \$16.79 |
| FDH-10-20-30W | \$25.67 |
| FDH-12-20-30W | \$30.03 |
| FDH-12-25-36W | \$26.80 |
| FDH-16-30-42W | \$39.61 |
| FDH-20-30-42W | \$70.35 |
| FDH-20-38-52W | \$144.42 |
| FDH-24-38-52W | \$187.86 |
| | |

FDH45


DIN Heavy (Metric) Universal Seat Female Swivel 45°



| FDH45-04-08-16W | \$19.20 |
|-----------------|---------|
| FDH45-04-10-18W | \$15.39 |
| FDH45-06-08-16W | \$24.35 |
| FDH45-06-12-20W | \$20.19 |
| FDH45-06-14-22W | \$18.88 |
| FDH45-08-12-20W | \$25.34 |
| FDH45-08-16-24W | \$23.79 |
| FDH45-10-20-30W | \$39.48 |
| FDH45-12-20-30W | \$39.71 |
| FDH45-12-25-36W | \$40.30 |
| FDH45-16-30-42W | \$45.49 |
| FDH45-20-30-42W | \$80.70 |
| FDH45-20-38-52W | \$84.18 |

FDH90

DIN Heavy (Metric) Universal Seat Female Swivel 90°




| FDH90-04-08-16W | \$19.48 |
|-----------------|---------|
| FDH90-04-10-18W | \$15.17 |
| FDH90-06-08-16W | \$22.12 |
| FDH90-06-12-20W | \$19.99 |
| FDH90-06-14-22W | \$18.88 |
| FDH90-08-12-20W | \$25.18 |
| FDH90-08-16-24W | \$23.11 |
| FDH90-10-20-30W | \$40.28 |
| FDH90-12-20-30W | \$39.69 |
| FDH90-12-25-36W | \$39.51 |
| FDH90-16-30-42W | \$49.75 |
| FDH90-20-30-42W | \$82.93 |
| FDH90-20-38-52W | \$86.38 |
| | |

MDH

DIN Heavy (Metric) Universal Seat Male

| MDH-04-08-16W | \$11.27 |
|---------------|---------|
| MDH-04-10-18W | \$11.67 |
| MDH-06-08-16W | \$13.52 |
| MDH-06-12-20W | \$16.44 |
| MDH-06-14-22W | \$12.09 |
| MDH-08-16-24W | \$12.81 |
| MDH-10-20-30W | \$14.34 |
| MDH-12-25-36W | \$16.05 |
| MDH-16-30-42W | \$37.17 |
| | |



3 Series Thermoplastic Hose Fittings




NPTF Male Pipe

| P | |
|---|--|
| 鬥 | |

| ltem # | Hose | NPTF | Die | Pusher | Price |
|---------|-------|------|----------|------------|---------|
| 3-02102 | 1/8" | 1/8" | 4540-302 | 4599-MP023 | \$3.37 |
| 3-03102 | 3/16" | 1/8" | 4540-303 | 4599-MP001 | \$3.31 |
| 3-03104 | 3/16" | 1/4" | 4540-303 | 4599-MP004 | \$3.89 |
| 3-04102 | 1/4" | 1/8" | 4540-304 | 4599-MP002 | \$3.84 |
| 3-04104 | 1/4" | 1/4" | 4540-304 | 4599-MP004 | \$3.56 |
| 3-04106 | 1/4" | 3/8" | 4540-304 | 4599-MP005 | \$3.93 |
| 3-05104 | 5/16" | 1/4" | 4540-305 | 4599-MP004 | \$4.43 |
| 3-05106 | 5/16" | 3/8" | 4540-305 | 4599-MP005 | \$4.68 |
| 3-06104 | 3/8" | 1/4" | 4540-306 | 4599-MP005 | \$4.24 |
| 3-06106 | 3/8" | 3/8" | 4540-306 | 4599-MP005 | \$4.03 |
| 3-06108 | 3/8" | 1/2" | 4540-306 | 4599-MP009 | \$5.99 |
| 3-08106 | 1/2" | 3/8" | 4540-308 | 4599-MP008 | \$4.90 |
| 3-08108 | 1/2" | 1/2" | 4540-308 | 4599-MP009 | \$4.87 |
| 3-12112 | 3/4" | 3/4" | 4540-312 | 4599-MP011 | \$7.74 |
| 3-16116 | 1" | 1" | 4540-316 | 4599-MP013 | \$11.01 |

NPTF Male Pipe Swivel



| Item # | Hose | NPTF | Die | Pusher | Price |
|---------|-------|------|----------|------------|--------|
| 3-03144 | 3/16" | 1/4" | 4540-303 | 4599-MP003 | \$6.01 |
| 3-04144 | 1/4" | 1/4" | 4540-304 | 4599-MP003 | \$5.33 |
| 3-06146 | 3/8" | 3/8" | 4540-306 | 4599-MP006 | \$6.28 |
| 3-08148 | 1/2" | 1/2" | 4540-308 | 4599-MP010 | \$7.59 |

NPSM Female Pipe Swivel

| I | |
|---|---|
| ų | _ |

| Item # | Hose | NPSM | Die | Pusher | Price |
|---------|-------|------|----------|------------|--------|
| 3-03244 | 3/16" | 1/4" | 4540-303 | 4599-FP002 | \$4.71 |
| 3-04244 | 1/4" | 1/4" | 4540-304 | 4599-FP002 | \$4.83 |
| 3-05244 | 5/16" | 1/4" | 4540-305 | 4599-FP013 | \$6.50 |
| 3-06246 | 3/8" | 3/8" | 4540-306 | 4599-FP004 | \$5.50 |
| 3-08248 | 1/2" | 1/2" | 4540-308 | 4599-FP018 | \$6.23 |

JIC 37° Female Swivel



Most sizes (except 3/8" and 3/4") are dual seat, will fit JIC 37° and SAE 45°

| ltem # | Hose | JIC | Die | Pusher | Price |
|---------|-------|-------|----------|------------|--------|
| 3-02544 | 1/8" | 1/4" | 4540-302 | 4599-FP010 | \$5.76 |
| 3-03544 | 3/16" | 1/4" | 4540-303 | 4599-FP011 | \$4.00 |
| 3-04544 | 1/4" | 1/4" | 4540-304 | 4599-FP012 | \$4.03 |
| 3-04545 | 1/4" | 5/16" | 4540-304 | 4599-FP013 | \$4.29 |
| 3-04546 | 1/4" | 3/8" | 4540-304 | 4599-FP013 | \$4.41 |
| 3-05545 | 5/16" | 5/16" | 4540-305 | 4599-FP013 | \$4.87 |
| 3-05546 | 5/16" | 3/8" | 4540-305 | 4599-FP013 | \$4.71 |
| 3-06546 | 3/8" | 3/8" | 4540-306 | 4599-FP015 | \$4.53 |
| 3-06548 | 3/8" | 1/2" | 4540-306 | 4599-FP005 | \$5.25 |
| 3-08548 | 1/2" | 1/2" | 4540-308 | 4599-FP016 | \$5.95 |
| 3-08550 | 1/2" | 5/8" | 4540-308 | 4599-FP006 | \$6.54 |
| 3-12552 | 3/4" | 3/4" | 4540-312 | 4599-FP008 | \$9.84 |

SAE 45° Swivel



For all other sizes, use JIC 37° Female Swivel

| Item # | Hose | SAE | Die | Pusher | Price |
|---------|------|------|----------|------------|--------|
| 3-06A06 | 3/8" | 3/8" | 4540-306 | 4599-FP014 | \$5.71 |

JIC 37° Male



| ltem # | Hose | JIC | Die | Pusher | Price |
|---------|-------|-------|----------|------------|--------|
| 3-03504 | 3/16" | 1/4" | 4540-303 | 4599-MP001 | \$3.84 |
| 3-04504 | 1/4" | 1/4" | 4540-304 | 4599-MP002 | \$3.97 |
| 3-04505 | 1/4" | 5/16" | 4540-304 | 4599-MP002 | \$4.14 |
| 3-04506 | 1/4" | 3/8" | 4540-304 | 4599-MP005 | \$5.71 |
| 3-05506 | 5/16" | 3/8" | 4540-305 | 4599-MP004 | \$6.25 |
| 3-06506 | 3/8" | 3/8" | 4540-306 | 4599-MP005 | \$4.67 |
| 3-06508 | 3/8" | 1/2" | 4540-306 | 4599-MP007 | \$4.94 |
| 3-08508 | 1/2" | 1/2" | 4540-308 | 4599-MP008 | \$5.76 |
| 3-08510 | 1/2" | 5/8" | 4540-308 | 4599-MP009 | \$6.11 |
| 3-12512 | 3/4" | 3/4" | 4540-312 | 4599-MP011 | \$9.57 |
| | | | | | |

3 Series Thermoplastic Hose Fittings are intended for use with SAE 100R7 or reduced O.D. 100R8 Thermoplastic Hose.

- Interchangeable with Synflex 3903 Series Hose Fittings
- Can be attached with a hose crimper or with the DST1
- Swaging Tool (page 68).




3 Series Thermoplastic Hose Fittings

JIC 37° Female Swivel 45°


| Item # | Hose | JIC | Die | Pusher | Price |
|---------|------|-------|----------|------------|---------|
| 3-04605 | 1/4" | 5/16" | 4540-304 | 4599-TP205 | \$11.64 |
| 3-06606 | 3/8" | 3/8" | 4540-306 | 4599-TP206 | \$11.18 |
| 3-06608 | 3/8" | 1/2" | 4540-306 | 4599-TP208 | \$11.13 |
| 3-08608 | 1/2" | 1/2" | 4540-308 | 4599-TP308 | \$14.79 |
| 3-08610 | 1/2" | 5/8" | 4540-308 | 4599-TP310 | \$15.90 |

JIC 37° Female Swivel 90°



| ltem # | Hose | JIC | Die | Pusher | Price |
|---------|-------|-------|----------|------------|---------|
| 3-03644 | 3/16" | 1/4" | 4540-303 | 4599-TP204 | \$10.93 |
| 3-04644 | 1/4" | 1/4" | 4540-304 | 4599-TP204 | \$10.79 |
| 3-04645 | 1/4" | 5/16" | 4540-304 | 4599-TP205 | \$13.21 |
| 3-04646 | 1/4" | 3/8" | 4540-304 | 4599-TP206 | \$12.69 |
| 3-05646 | 5/16" | 3/8" | 4540-305 | 4599-TP206 | \$13.08 |
| 3-06646 | 3/8" | 3/8" | 4540-306 | 4599-TP206 | \$11.28 |
| 3-06648 | 3/8" | 1/2" | 4540-306 | 4599-TP208 | \$13.11 |
| 3-08648 | 1/2" | 1/2" | 4540-308 | 4599-TP308 | \$13.40 |
| 3-08650 | 1/2" | 5/8" | 4540-308 | 4599-TP310 | \$17.45 |

JIC 37° Female Swivel 90° Long Drop Elbow




| ltem # | Hose | JIC | Die | Pusher | Price |
|---------|------|-------|----------|------------|---------|
| 3-04845 | 1/4" | 5/16" | 4540-304 | 4599-TP205 | \$9.86 |
| 3-06846 | 3/8" | 3/8" | 4540-306 | 4599-TP206 | \$13.78 |
| 3-06848 | 3/8" | 1/2" | 4540-306 | 4599-TP208 | \$13.91 |
| 3-08850 | 1/2" | 5/8" | 4540-308 | 4599-TP310 | \$17.73 |

O-Ring Face Seal (ORFS) Female Swivel




| Item # | Hose | ORFS | Die | Pusher | Price |
|---------|-------|------|----------|------------|---------|
| 3-04404 | 1/4" | 1/4" | 4540-304 | 4599-MP045 | \$9.21 |
| 3-05406 | 5/16" | 3/8" | 4540-306 | 4599-MP037 | \$10.56 |
| 3-06406 | 3/8" | 3/8" | 4540-306 | 4599-MP037 | \$10.59 |
| 3-08408 | 1/2" | 1/2" | 4540-308 | 4599-MP046 | \$12.46 |

O-Ring Face Seal (ORFS) Female Swivel 45°




| Item # | Hose | ORFS | Die | Pusher | Price |
|---------|------|------|----------|------------|---------|
| 3-04444 | 1/4" | 1/4" | 4540-304 | 4599-TP204 | \$10.42 |
| 3-06446 | 3/8" | 3/8" | 4540-306 | 4599-TP206 | \$11.90 |
| 3-08448 | 1/2" | 1/2" | 4540-308 | 4599-TP308 | \$13.88 |

O-Ring Face Seal (ORFS) Female Swivel 90°




| ltem # | Hose | ORFS | Die | Pusher | Price |
|---------|-------|------|----------|------------|---------|
| 3-04474 | 1/4" | 1/4" | 4540-304 | 4599-TP204 | \$11.11 |
| 3-05476 | 5/16" | 3/8" | 4540-305 | 4599-TP206 | \$13.23 |
| 3-06476 | 3/8" | 3/8" | 4540-306 | 4599-TP206 | \$11.31 |
| 3-08478 | 1/2" | 1/2" | 4540-308 | 4599-TP308 | \$13.51 |

Inverted Flare Male Swivel 45°



| Item # | Hose | Tube | Die | Pusher | Price |
|---------|------|------|----------|------------|---------|
| 3-06C46 | 3/8" | 3/8" | 4540-306 | 4599-TP206 | \$10.28 |

Inverted Flare Male Swivel 90°



| ltem # | Hose | Tube | Die | Pusher | Price |
|---------|------|------|----------|------------|---------|
| 3-06C76 | 3/8" | 3/8" | 4540-306 | 4599-TP206 | \$10.28 |

T Series PTFE Hose Fittings



T01 NPTF Male Pipe Rigid



| ltem # | Hose | NPTF | Price |
|-----------|-------|------|---------|
| T01-03-02 | 3/16" | 1/8" | \$3.42 |
| T01-03-04 | 3/16" | 1/4" | \$3.70 |
| T01-04-02 | 1/4" | 1/8" | \$2.76 |
| T01-04-04 | 1/4" | 1/4" | \$3.10 |
| T01-04-06 | 1/4" | 3/8" | \$3.91 |
| T01-05-04 | 5/16" | 1/4" | \$3.42 |
| T01-05-06 | 5/16" | 3/8" | \$3.72 |
| T01-06-04 | 3/8" | 1/4" | \$3.36 |
| T01-06-06 | 3/8" | 3/8" | \$3.60 |
| T01-06-08 | 3/8" | 1/2" | \$4.29 |
| T01-08-06 | 1/2" | 3/8" | \$4.29 |
| T01-08-08 | 1/2" | 1/2" | \$3.91 |
| T01-12-12 | 3/4" | 3/4" | \$6.41 |
| T01-16-16 | 1" | 1" | \$10.31 |

T04 NPTE Male Pipe

NPTF Male Pipe Swivel



| ltem # | Hose | NPTF | Price |
|-----------|-------|------|--------|
| T04-04-04 | 1/4" | 1/4" | \$5.34 |
| T04-05-04 | 5/16" | 1/4" | \$5.43 |
| T04-06-06 | 3/8" | 3/8" | \$5.64 |
| T04-08-08 | 1/2" | 1/2" | \$6.47 |

T08

JIC 37° Male Rigid



| ltem # | Hose | JIC | Price |
|-----------|-------|-------|---------|
| T08-04-04 | 1/4" | 1/4" | \$3.49 |
| T08-04-05 | 1/4" | 5/16" | \$13.02 |
| T08-04-06 | 1/4" | 3/8" | \$3.91 |
| T08-05-05 | 5/16" | 5/16" | \$3.91 |
| T08-06-06 | 3/8" | 3/8" | \$4.13 |
| T08-06-08 | 3/8" | 1/2" | \$4.69 |
| T08-08-08 | 1/2" | 1/2" | \$5.17 |
| T08-08-10 | 1/2" | 5/8" | \$6.02 |
| T08-12-12 | 3/4" | 3/4" | \$8.30 |
| T08-16-16 | 1" | 1" | \$11.20 |

T09 JIC 37° Female Swivel



| ltem # | Hose | JIC | Price |
|-----------|-------|-------|---------|
| T09-03-04 | 3/16" | 1/4" | \$4.43 |
| T09-04-04 | 1/4" | 1/4" | \$3.74 |
| T09-04-05 | 1/4" | 5/16" | \$4.00 |
| T09-04-06 | 1/4" | 3/8" | \$4.31 |
| T09-05-05 | 5/16" | 5/16" | \$5.21 |
| T09-05-06 | 5/16" | 3/8" | \$4.42 |
| T09-06-06 | 3/8" | 3/8" | \$4.29 |
| T09-06-08 | 3/8" | 1/2" | \$5.27 |
| T09-08-08 | 1/2" | 1/2" | \$5.08 |
| T09-08-10 | 1/2" | 5/8" | \$6.37 |
| T09-12-12 | 3/4" | 3/4" | \$8.77 |
| T09-16-16 | 1" | 1" | \$12.73 |

T07

SAE 45° Female Swivel



| ltem # | Hose | SAE | Price |
|-----------|-------|------|--------|
| T07-05-06 | 5/16" | 3/8" | \$5.21 |
| T07-06-06 | 3/8" | 3/8" | \$4.45 |

T23





| Item # | Hose | SAE | Price |
|-----------|-------|------|--------|
| T23-05-06 | 5/16" | 3/8" | \$9.23 |
| T23-06-06 | 3/8" | 3/8" | \$9.08 |

T10


British Standard Pipe (BSPP) Female Swivel



| ltem # | Hose | BSPP | Price |
|-----------|------|------|---------|
| T10-04-04 | 1/4" | 1/4" | \$10.32 |
| T10-06-06 | 3/8" | 3/8" | \$10.75 |
| T10-08-08 | 1/2" | 1/2" | \$14.76 |

T25

JIC 37°/SAE 45° Dual Seat Female Swivel 45°



| ltem # | Hose | JIC | Price |
|------------|-------|------|---------|
| T25-04-04 | 1/4" | 1/4" | \$8.11 |
| T25-05-06* | 5/16" | 3/8" | \$9.01 |
| T25-06-06* | 3/8" | 3/8" | \$9.31 |
| T25-08-08 | 1/2" | 1/2" | \$9.89 |
| T25-08-10 | 1/2" | 5/8" | \$11.24 |
| T25-12-12* | 3/4" | 3/4" | \$15.36 |
| T25-16-16 | 1" | 1" | \$21.27 |

T26

JIC 37°/SAE 45° Dual Seat Female Swivel 90°



| ltem # | Hose | JIC | Price |
|------------|-------|-------|---------|
| T26-04-04 | 1/4" | 1/4" | \$7.81 |
| T26-04-05 | 1/4" | 5/16" | \$8.24 |
| T26-05-06* | 5/16" | 3/8" | \$8.73 |
| T26-06-06* | 3/8" | 3/8" | \$8.90 |
| T26-06-08 | 3/8" | 1/2" | \$9.46 |
| T26-08-08 | 1/2" | 1/2" | \$9.89 |
| T26-08-10 | 1/2" | 5/8" | \$11.85 |
| T26-12-12* | 3/4" | 3/4" | \$15.56 |
| T26-16-16 | 1" | 1" | \$21.92 |

T27

JIC 37°/SAE 45° Dual Seat Female Swivel 90° Long



| ltem # | Hose | JIC | Price |
|------------|------|------|---------|
| T27-04-04 | 1/4" | 1/4" | \$7.58 |
| T27-06-06* | 3/8" | 3/8" | \$8.41 |
| T27-08-08 | 1/2" | 1/2" | \$10.75 |
| T27-12-12* | 3/4" | 3/4" | \$18.43 |
| T27-16-16 | 1" | 1" | \$21.27 |

* JIC seat and thread only

IMPORTANT: For use only with SAE 100R14A PTFE Hose.




T Series PTFE Hose Fittings

T30 O-Ring Face Seal Female Swivel

| ltem # | Hose | ORFS | Price |
|-----------|-------|------|---------|
| T30-04-04 | 1/4" | 1/4" | \$5.57 |
| T30-04-06 | 1/4" | 3/8" | \$6.08 |
| T30-05-06 | 5/16" | 3/8" | \$6.21 |
| T30-06-06 | 3/8" | 3/8" | \$6.21 |
| T30-06-08 | 3/8" | 1/2" | \$7.29 |
| T30-08-08 | 1/2" | 1/2" | \$7.47 |
| T30-08-10 | 1/2" | 5/8" | \$9.44 |
| T30-12-12 | 3/4" | 3/4" | \$12.60 |
| T30-16-16 | 1" | 1" | \$18.23 |

T31


O-Ring Face Seal Female Swivel 45°



| ltem # | Hose | ORFS | Price |
|-----------|-------|------|---------|
| T31-04-04 | 1/4" | 1/4" | \$9.33 |
| T31-05-06 | 5/16" | 3/8" | \$9.99 |
| T31-06-06 | 3/8" | 3/8" | \$9.99 |
| T31-08-08 | 1/2" | 1/2" | \$11.34 |
| T31-12-12 | 3/4" | 3/4" | \$16.85 |
| T31-16-16 | 1" | 1" | \$21.14 |

T32


O-Ring Face Seal Female Swivel 90°



| Haza | ODEC | Price |
|-------|---|--|
| nose | UKFS | Price |
| 1/4" | 1/4" | \$8.90 |
| 1/4" | 3/8" | \$9.86 |
| 5/16" | 3/8" | \$10.42 |
| 3/8" | 3/8" | \$9.33 |
| 3/8" | 1/2" | \$11.16 |
| 1/2" | 1/2" | \$11.29 |
| 3/4" | 3/4" | \$18.00 |
| 1" | 1" | \$21.14 |
| | 1/4" 5/16" 3/8" 3/8" 1/2" 3/4" | 1/4" 1/4" 1/4" 3/8" 5/16" 3/8" 3/8" 3/8" 3/8" 1/2" 1/2" 1/2" 3/4" 3/4" |

T33

O-Ring Face Seal Female Swivel 90°



| ltem # | Hose | ORFS | Price |
|-----------|------|------|---------|
| T33-04-04 | 1/4" | 1/4" | \$9.39 |
| T33-06-06 | 3/8" | 3/8" | \$10.21 |
| T33-08-08 | 1/2" | 1/2" | \$11.58 |

T18


Inverted Flare Male Swivel



| Item # | Hose | Tube | Price |
|-----------|-------|-------|--------|
| T18-04-04 | 1/4" | 1/4" | \$6.41 |
| T18-04-05 | 1/4" | 5/16" | \$6.52 |
| T18-05-05 | 5/16" | 5/16" | \$8.24 |
| T18-06-06 | 3/8" | 3/8" | \$6.73 |

T19


Inverted Flare Male Swivel 45°



| Item # | Hose | Tube | Price |
|-----------|------|------|--------|
| T19-04-04 | 1/4" | 1/4" | \$8.31 |
| T19-06-06 | 3/8" | 3/8" | \$8.34 |

T20

Inverted Flare Male Swivel 90°



| ltem # | Hose | Tube | Price |
|-----------|------|------|--------|
| T20-04-04 | 1/4" | 1/4" | \$7.94 |
| T20-06-06 | 3/8" | 3/8" | \$8.34 |

IMPORTANT: For use only with SAE 100R14A PTFE Hose.

Weatherhead E Series Interchange

| | | | 2 |
|---------|-----------|---------|-----------|
| 03E-102 | T01-03-02 | 06E-646 | T27-06-06 |
| 03E-104 | T01-03-04 | 06E-666 | T26-06-06 |
| 03E-604 | T09-03-04 | 06E-668 | T26-06-08 |
| 04E-102 | T01-04-02 | 06E-686 | T25-06-06 |
| 04E-104 | T01-04-04 | 06E-A26 | T32-06-06 |
| 04E-106 | T01-04-06 | 06E-A28 | T32-06-08 |
| 04E-354 | T10-04-04 | 06E-A66 | T33-06-06 |
| 04E-504 | T08-04-04 | 06E-B06 | T18-06-06 |
| 04E-506 | T08-04-06 | 06E-B46 | T19-06-06 |
| 04E-604 | T09-04-04 | 06E-B66 | T20-06-06 |
| 04E-605 | T09-04-05 | 06EJ06 | T04-06-06 |
| 04E-606 | T09-04-06 | 06E-L66 | T31-06-06 |
| 04E-644 | T27-04-04 | 06E-S66 | T30-06-06 |
| 04E-664 | T26-04-04 | 06E-S68 | T30-06-08 |
| 04E-665 | T26-04-05 | 08E-106 | T01-08-06 |
| 04E-684 | T25-04-04 | 08E-108 | T01-08-08 |
| 04E-A24 | T32-04-04 | 08E-358 | T10-08-08 |
| 04E-A26 | T32-04-06 | 08E-508 | T08-08-08 |
| 04E-A64 | T33-04-04 | 08E-510 | T08-08-10 |
| 04E-B04 | T18-04-04 | 08E-608 | T09-08-08 |
| 04E-B05 | T18-04-05 | 08E-610 | T09-08-10 |
| 04E-B44 | T19-04-04 | 08E-648 | T27-08-08 |
| 04E-B64 | T20-04-04 | 08E-668 | T26-08-08 |
| 04E-J04 | T04-04-04 | 08E-670 | T26-08-10 |
| 04E-L64 | T31-04-04 | 08E-688 | T25-08-08 |
| 04E-S64 | T30-04-04 | 08E-690 | T25-08-10 |
| 04E-S66 | T30-04-06 | 08E-A28 | T32-08-08 |
| 05E-104 | T01-05-04 | 08E-A68 | T33-08-08 |
| 05E-106 | T01-05-06 | 08E-J08 | T04-08-08 |
| 05E-406 | T07-05-06 | 08E-L68 | T31-08-08 |
| 05E-466 | T23-05-06 | 08E-S68 | T30-08-08 |
| 05E-505 | T08-05-05 | 08E-S70 | T30-08-10 |
| 05E-605 | T09-05-05 | 12E-111 | T01-12-12 |
| 05E-606 | T09-05-06 | 12E-512 | T08-12-12 |
| 05E-666 | T26-05-06 | 12E-612 | T09-12-12 |
| 05E-686 | T25-05-06 | 12E-652 | T27-12-12 |
| 05E-A26 | T32-05-06 | 12E-672 | T26-12-12 |
| 05E-B05 | T18-05-05 | 12E-692 | T25-12-12 |
| 05E-J04 | T04-05-04 | 12E-A32 | T32-12-12 |
| 05E-L66 | T31-05-06 | 12E-L72 | T31-12-12 |
| 05E-S66 | T30-05-06 | 12E-S72 | T30-12-12 |
| 06E-104 | T01-06-04 | 16E-115 | T01-16-16 |
| 06E-106 | T01-06-06 | 16E-516 | T08-16-16 |
| 06E-108 | T01-06-08 | 16E-616 | T09-16-16 |
| 06E-356 | T10-06-06 | 16E-656 | T27-16-16 |
| 06E-406 | T07-06-06 | 16E-676 | T26-16-16 |
| 06E-466 | T23-06-06 | 16E-696 | T25-16-16 |
| 06E-506 | T08-06-06 | 16E-A36 | T32-16-16 |
| 06E-508 | T08-06-08 | 16E-L76 | T31-16-16 |
| 06E-606 | T09-06-06 | 16E-S76 | T30-16-16 |
| 06E-608 | T09-06-08 | | |

JJ Series Hose Fittings



FJX

JIC 37° Female Swivel




 FJX-20-20JJ
 \$52.22

 FJX-24-24JJ
 \$75.23

 FJX-32-32JJ
 \$121.63


FJX45

JIC 37° Female Swivel 45°



| FJX45-20-20JJ | \$78.63 |
|---------------|----------|
| FJX45-24-24JJ | \$98.67 |
| FJX45-32-32JJ | \$208.59 |

FJX90 JIC 37° Female Swivel 90°



| FJX90-20-20JJ | \$73.96 |
|---------------|----------|
| FJX90-24-24JJ | \$119.45 |
| FJX90-32-32JJ | \$202.50 |

MJ JIC 37° Male Rigid



| MJ-20-20JJ | \$54.29 |
|------------|----------|
| MJ-24-24JJ | \$80.01 |
| MJ-32-32JJ | \$136.82 |

MP NPTF Male Pipe Rigid


 MP-20-20JJ
 \$40.77

 MP-24-24JJ
 \$56.88

 MP-24-32JJ
 \$86.53

 MP-32-32JJ
 \$95.85


FFX O-Ring Face Seal (ORFS) Female Swivel



FFX-20-20JJ\$49.81FFX-24-24JJ\$61.55


FFX45 O-Ring Face Seal (ORFS)

Female Swivel 45°



FFX45-20-20JJ\$90.96FFX45-24-24JJ\$99.46

FFX90 O-Ring Face Seal (ORFS) Female Swivel 90°



FFX90-20-20JJ \$73.96 FFX90-24-24JJ \$102.39



C6122

C6122-20-20JJ

C6122-24-24JJ

C6122-24-32JJ

C6122-32-32JJ

C6130-20-20JJ C6130-24-24JJ

C6130-24-32JJ

C6130-32-32JJ

C6145-20-20JJ

C6145-24-24JJ

C6145-24-32JJ

C6145-32-32JJ

Code 61 Flange 45°

C6145

Code 61 Flange 30°

C6130

Code 61 Flange 22°



 C61-20-20JJ
 \$50.63

 C61-24-24JJ
 \$65.94

 C61-24-32JJ
 \$76.92

 C61-32-32JJ
 \$119.93

\$174.07

\$263.43

\$116.28

\$150.15

\$72.50

\$85.75

\$96.53

\$62.10

\$79.63


\$93.09

\$113.82

\$152.25

C6160


Code 61 Flange 60°



| C6160-20-20JJ | \$74.90 |
|---------------|----------|
| C6160-24-24JJ | \$90.85 |
| C6160-24-32JJ | \$94.50 |
| C6160-32-32JJ | \$158.77 |

C6167


Code 61 Flange 67°



| C6167-20-20JJ | \$67.74 |
|---------------|----------|
| C6167-24-24JJ | \$90.88 |
| C6167-24-32JJ | \$94.31 |
| C6167-32-32JJ | \$159.71 |

C6190

Code 61 Flange 90°



| C6190-20-20JJ | \$66.79 |
|---------------|----------|
| C6190-24-24JJ | \$73.09 |
| C6190-24-32JJ | \$116.42 |
| C6190-32-32JJ | \$122.26 |
| | |

C62

Code 62 Flange



| C62-20-20JJ | \$59.86 |
|-------------|----------|
| C62-24-24JJ | \$71.77 |
| C62-24-32JJ | \$92.45 |
| C62-32-32JJ | \$144.61 |
| | |



JJ Series Hose Fittings


C6222 Code 62 Flange 22°

| | 7] |
|--|----|
|--|----|

| C6222-20-20JJ | \$73.38 |
|---------------|----------|
| C6222-24-24JJ | \$96.43 |
| C6222-24-32JJ | \$152.35 |
| C6222-32-32JJ | \$171.66 |

C6230

Code 62 Flange 30°



| C6230-20-20JJ | \$58.43 |
|---------------|----------|
| C6230-24-24JJ | \$69.57 |
| C6230-32-32JJ | \$176.55 |


C6245

Code 62 Flange 45°

| [| \searrow |
|---|------------|
| | \sim |


| C6245-20-20JJ | \$79.96 |
|---------------|----------|
| C6245-24-24JJ | \$94.07 |
| C6245-24-32JJ | \$162.26 |
| C6245-32-32JJ | \$167.12 |

C6260 Code 62 Flange 60°




| C6260-20-20JJ | \$76.80 | | |
|---------------|----------|--|--|
| C6260-24-24JJ | \$98.65 | | |
| C6260-24-32JJ | \$161.77 | | |
| C6260-32-32JJ | \$188.41 | | |

C6267 Code 62 Flange 67°



| C6267-20-20JJ | \$69.77 |
|---------------|---------|
| C6267-24-24JJ | \$98.65 |

C6290 Code 62 Flange 90°



| 0' |
|----|
| 91 |
| 32 |
|)6 |
| 53 |
| |


CAT **Caterpillar Flange**



| CAT-20-20JJ | \$69.39 |
|-------------|----------|
| CAT-20-24JJ | \$79.63 |
| CAT-24-24JJ | \$62.97 |
| CAT-32-32JJ | \$168.23 |

CAT45


Caterpillar Flange 45°



| CAT45-20-20JJ | \$76.27 |
|---------------|----------|
| CAT45-20-24JJ | \$91.10 |
| CAT45-24-24JJ | \$91.73 |
| CAT45-32-32JJ | \$162.47 |

CAT90

Caterpillar Flange 90°



| CAT90-20-20JJ | \$67.23 |
|---------------|----------|
| CAT90-20-24JJ | \$87.66 |
| CAT90-24-24JJ | \$85.93 |
| CAT90-32-32JJ | \$163.87 |
| | |

| JJ Series Hose Fittings feature a bite-to-the wire-design, and are intended for use with | FJX-06-08JJ |
|--|-----------------------|
| 4SH (sizes -24 and -32) and R13 (sizes -20, -24 | \uparrow \uparrow |
| and -32) hydraulic hoses. | HOSE FITTING |

FDH

DIN Heavy (Metric) Universal Seat Female Swivel



FDH-20-38-52JJ

\$111.23

Suction Hose Fittings (2-piece)



Ferrule

| ĥ | _ | _ | _ | _ | _ | |
|---|---|---|---|---|---|--|
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| ł | _ | - | - | - | - | |

| ltem # | Hose | Price |
|---------|-------|--------|
| 112-400 | 3/4" | \$2.36 |
| 116-400 | 1" | \$2.82 |
| 120-400 | 1¼ | \$3.34 |
| 124-400 | 11⁄2" | \$5.32 |
| 132-400 | 2" | \$7.50 |

NPTF

Male Pipe



| ltem # | Hose | NPTF | Price |
|---------|-------|-------|---------|
| 112-112 | 3/4" | 3/4" | \$3.64 |
| 112-116 | 3/4" | 1" | \$6.57 |
| 116-116 | 1" | 1" | \$6.16 |
| 120-120 | 1¼ | 1¼" | \$12.27 |
| 124-124 | 11⁄2" | 11⁄2" | \$17.91 |
| 132-132 | 2" | 2" | \$33.32 |

ORB

SAE Straight Thread O-Ring Boss -Male



| ltem # | Hose | ORB | Price |
|---------|------|-------|---------|
| 112-712 | 3/4" | 3/4" | \$6.15 |
| 116-716 | 1" | 1" | \$10.06 |
| 120-720 | 11⁄4 | 11⁄4" | \$16.77 |

JIC 37° Flare - Female Swivel

| ltem # | Hose | JIC | Price |
|---------|-------|-------|---------|
| 112-612 | 3/4" | 3/4" | \$5.86 |
| 112-614 | 3/4" | 7/8" | \$8.94 |
| 112-616 | 3/4" | 1" | \$8.94 |
| 116-616 | 1" | 1" | \$8.94 |
| 120-620 | 11⁄4 | 1¼" | \$19.68 |
| 124-624 | 11⁄2" | 11⁄2" | \$28.19 |
| 132-632 | 2" | 2" | \$66.80 |
| | | | |

JIC 37° Flare - Male

| Item # | Hose | JIC | Price |
|---------|------|------|---------|
| 112-512 | 3/4" | 3/4" | \$4.20 |
| 112-514 | 3/4" | 7/8" | \$6.71 |
| 112-516 | 3/4" | 1" | \$7.28 |
| 116-516 | 1" | 1" | \$8.01 |
| 120-520 | 1¼ | 1¼" | \$15.09 |

Code 61

Flange



| ltem # | Hose | Flange | Price |
|---------|-------|--------|---------|
| 112-G12 | 3/4" | 3/4" | \$20.02 |
| 116-G16 | 1" | 1" | \$26.95 |
| 120-G20 | 1¼ | 1¼" | \$45.13 |
| 124-G24 | 11⁄2" | 11⁄2" | \$51.98 |
| 132-G32 | 2" | 2" | \$69.24 |

IMPORTANT: For use only with SAE 100R4 Suction Hose.

Code 61

Flange 45°



| ltem # | Hose | Flange | Price |
|---------|-------|--------|----------|
| 124-G54 | 11⁄2" | 11⁄2" | \$63.36 |
| 132-G62 | 2" | 2" | \$91.48 |
| 140-G62 | 21⁄2" | 2" | \$131.00 |

Code 61

Flange 90°



| ltem # | Hose | Flange | Price |
|---------|-------|--------|----------|
| 120-G80 | 1¼ | 1¼" | \$59.16 |
| 124-G84 | 11⁄2" | 11⁄2" | \$64.98 |
| 124-G92 | 11⁄2" | 2" | \$71.56 |
| 132-G92 | 2" | 2" | \$96.08 |
| 132-G96 | 2" | 21⁄2" | \$119.02 |
| 140-G92 | 21⁄2" | 2" | \$135.96 |
| 140-G96 | 21⁄2" | 21⁄2" | \$174.16 |



Steel Hose Barbs

HAS NPTF Male Pipe



| ltem # | NPT | Hose | Price |
|--------|-------|-------|---------|
| HAS-02 | 1/2" | 1/2" | \$2.18 |
| HAS-03 | 3/4" | 3/4" | \$2.27 |
| HAS-04 | 1" | 1" | \$2.61 |
| HAS-05 | 11⁄4" | 11⁄4" | \$3.35 |
| HAS-06 | 11⁄2" | 11⁄2" | \$3.81 |
| HAS-08 | 2" | 2" | \$4.61 |
| HAS-10 | 21⁄2" | 21⁄2" | \$9.95 |
| HAS-12 | 3" | 3" | \$11.82 |
| HAS-16 | 4" | 4" | \$17.49 |

HRS

NPTF Male Pipe Reducer



| ltem # | NPT | Hose | Price |
|-----------|-------|-------|---------|
| HRS-04x03 | 1" | 3/4" | \$6.45 |
| HRS-05x04 | 11⁄4" | 1" | \$8.07 |
| HRS-06x05 | 1½" | 11⁄4" | \$7.36 |
| HRS-08x06 | 2" | 11⁄2" | \$9.31 |
| HRS-10x08 | 21⁄2" | 2" | \$17.38 |
| HRS-12x10 | 3" | 21⁄2" | \$20.44 |
| HRS-16x12 | 4" | 3" | \$44.89 |

HES

NPTF Male Pipe Expander



| ltem # | NPT | Hose | Price |
|-----------|--------|--------|---------|
| HES-03x04 | 3/4" | 1" | \$4.71 |
| HES-04x05 | 1" | 1 ¼" | \$5.94 |
| HES-05x06 | 1 ¼" | 1 1⁄2" | \$6.34 |
| HES-06x08 | 1 1⁄2" | 2" | \$11.50 |
| HES-08x10 | 2" | 2 1⁄2" | \$18.15 |
| HES-10x12 | 2 1⁄2" | 3" | \$22.30 |
| HES-12x16 | 3" | 4" | \$44.89 |

HAPS Zinc-Plated NPTF Male Pipe



| ltem # | NPT | Hose | Price |
|---------|-------|-------|---------|
| HAPS-02 | 1/2" | 1/2" | \$2.56 |
| HAPS-03 | 3/4" | 3/4" | \$2.65 |
| HAPS-04 | 1" | 1" | \$3.22 |
| HAPS-05 | 11⁄4" | 11⁄4" | \$3.82 |
| HAPS-06 | 11⁄2" | 11⁄2" | \$4.46 |
| HAPS-08 | 2" | 2" | \$5.38 |
| HAPS-10 | 21⁄2" | 21⁄2" | \$11.25 |
| HAPS-12 | 3" | 3" | \$13.68 |
| HAPS-16 | 4" | 4" | \$20.97 |

HCPS


Zinc-Plated Hose Mender



| ltem # | Hose | Price |
|---------|--------|---------|
| HCPS-02 | 1/2" | \$2.25 |
| HCPS-03 | 3/4" | \$2.61 |
| HCPS-04 | 1" | \$2.92 |
| HCPS-05 | 11⁄4" | \$4.60 |
| HCPS-06 | 11⁄2" | \$4.56 |
| HCPS-08 | 2" | \$6.04 |
| HCPS-10 | 2 1⁄2" | \$10.73 |
| HCPS-12 | 3" | \$12.24 |
| HCPS-16 | 4" | \$20.44 |

CN-100

NPTF Male Pipe with Clamshell



| ltem # | Hose | NPT | Price |
|----------|--------|--------|---------|
| C16N-116 | 1" | 1" | \$18.68 |
| C20N-120 | 1 ¼" | 1 ¼" | \$26.47 |
| C24N-124 | 1 1⁄2" | 1 1⁄2" | \$55.86 |
| C32N-132 | 2" | 2" | \$64.07 |

TBC

T-Bolt Clamp



Stainless steel band, carbon steel bolt

| ltem # | Fits Hose OD | Price |
|--------|-----------------|--------|
| TBC131 | 1.250" – 1.406" | \$7.07 |
| TBC150 | 1.344" – 1.562" | \$5.13 |
| TBC175 | 1.594" – 1.812" | \$5.13 |
| TBC188 | 1.724" – 1.942" | \$5.13 |
| TBC200 | 1.844" – 2.062" | \$5.13 |
| TBC225 | 2.094" – 2.312" | \$5.13 |
| TBC238 | 2.224" – 2.442" | \$5.13 |
| TBC250 | 2.344" – 2.562" | \$5.25 |
| TBC256 | 2.326" – 2.622" | \$5.06 |
| TBC263 | 2.396" – 2.692" | \$5.06 |
| TBC275 | 2.516" – 2.812" | \$5.06 |
| TBC288 | 2.646" – 2.942" | \$5.06 |
| TBC300 | 2.766" - 3.062" | \$5.09 |
| TBC312 | 2.886" – 3.182" | \$5.13 |
| TBC325 | 3.016" – 3.312" | \$5.13 |
| TBC350 | 3.266" – 3.562" | \$5.41 |
| TBC375 | 3.516" – 3.812" | \$5.41 |
| TBC382 | 3.586" – 3.882" | \$5.45 |
| TBC400 | 3.766" - 4.062" | \$5.45 |
| TBC425 | 4.016" – 4.312" | \$5.45 |

Steel hose barbs must be securely affixed with T-Bolt Clamps.

SAE 100R1 Field-Attachable Hose Fittings



JIC 37° Female Swivel



| ltem # | Hose | JIC | Price |
|-----------|------|------|---------|
| R1-04-604 | 1/4" | 1/4" | \$19.96 |
| R1-04-606 | 1/4" | 3/8" | \$20.96 |
| R1-06-606 | 3/8" | 3/8" | \$12.69 |
| R1-08-608 | 1/2" | 1/2" | \$18.78 |
| R1-08-610 | 1/2" | 5/8" | \$23.97 |
| R1-12-612 | 3/4" | 3/4" | \$41.44 |
| R1-16-616 | 1" | 1" | \$75.51 |

JIC 37° Male



| ltem # | Hose | JIC | Price |
|-----------|------|------|---------|
| R1-04-504 | 1/4" | 1/4" | \$16.30 |
| R1-06-506 | 3/8" | 3/8" | \$17.48 |
| R1-08-508 | 1/2" | 1/2" | \$19.67 |
| R1-12-512 | 3/4" | 3/4" | \$73.85 |
| R1-16-516 | 1" | 1" | \$83.00 |
| | | | |

IMPORTANT: For use only with SAE 100R1 AT Hydraulic Hose.

NPTF Male Pipe



| ltem # | Hose | NPTF | Price |
|-----------|------|------|---------|
| R1-04-104 | 1/4" | 1/4" | \$14.47 |
| R1-06-104 | 3/8" | 1/4" | \$9.90 |
| R1-06-106 | 3/8" | 3/8" | \$13.71 |
| R1-08-108 | 1/2" | 1/2" | \$17.01 |
| R1-12-112 | 3/4" | 3/4" | \$42.75 |
| R1-16-116 | 1" | 1" | \$58.04 |

SAE 100R2 Field-Attachable Hose Fittings

NPTF Male Pipe



| ltem # | Hose | NPTF | Price |
|--------------|---------|-----------|----------|
| R2-04-102 | 1/4" | 1/8" | \$29.75 |
| R2-04-104 | 1/4" | 1/4" | \$19.37 |
| R2-06-106 | 3/8" | 3/8" | \$13.60 |
| R2-08-106 | 1/2" | 3/8" | \$23.69 |
| R2-08-108 | 1/2" | 1/2" | \$12.21 |
| R2-08-112 | 1/2" | 3/4" | \$38.92 |
| R2-12-112 | 3/4" | 3/4" | \$37.02 |
| R2-16-116 | 1" | 1" | \$48.06 |
| R2-20-120 | 11⁄4" | 11⁄4" | \$109.84 |
| R2-24-124 | 11⁄2" | 11⁄2" | \$128.93 |
| SS = | Stainle | ess Steel | |
| SS-R2-04-104 | 1/4" | 1/4" | \$57.71 |
| SS-R2-06-106 | 3/8" | 3/8" | \$66.94 |
| SS-R2-08-108 | 1/2" | 1/2" | \$79.91 |
| SS-R2-12-112 | 3/4" | 3/4" | \$102.88 |
| SS-R2-16-116 | 1" | 1" | \$176.65 |

JIC 37° Male



| Item # | Hose | JIC | Price |
|-----------|------|-------|---------|
| R2-04-504 | 1/4" | 1/4" | \$20.15 |
| R2-04-505 | 1/4" | 5/16" | \$35.72 |
| R2-04-506 | 1/4" | 3/8" | \$31.73 |
| R2-06-506 | 3/8" | 3/8" | \$15.78 |
| R2-06-508 | 3/8" | 1/2" | \$15.79 |
| R2-08-508 | 1/2" | 1/2" | \$15.07 |
| R2-08-510 | 1/2" | 5/8" | \$19.83 |
| R2-12-512 | 3/4" | 3/4" | \$56.33 |
| R2-16-516 | 1" | 1" | \$85.91 |


JIC 37° Female Swivel



| Item # | Hose | JIC | Price |
|--------------|---------|----------|----------|
| R2-04-604 | 1/4" | 1/4" | \$24.79 |
| R2-04-605 | 1/4" | 5/16" | \$23.09 |
| R2-04-606 | 1/4" | 3/8" | \$21.13 |
| R2-06-606 | 3/8" | 3/8" | \$11.85 |
| R2-06-608 | 3/8" | 1/2" | \$31.13 |
| R2-08-608 | 1/2" | 1/2" | \$15.69 |
| R2-08-610 | 1/2" | 5/8" | \$19.41 |
| R2-12-610 | 3/4" | 5/8" | \$37.92 |
| R2-12-612 | 3/4" | 3/4" | \$25.24 |
| R2-12-614 | 3/4" | 7/8" | \$57.70 |
| R2-16-616 | 1" | 1" | \$37.77 |
| R2-20-620 | 1¼" | 1¼" | \$104.13 |
| R2-24-624 | 11⁄2" | 11⁄2" | \$160.49 |
| SS = | Stainle | ss Steel | |
| SS-R2-04-604 | 1/4" | 1/4" | \$63.57 |
| SS-R2-06-606 | 3/8" | 3/8" | \$74.24 |
| SS-R2-08-608 | 1/2" | 1/2" | \$94.56 |
| SS-R2-12-612 | 3/4" | 3/4" | \$178.13 |
| SS-R2-16-616 | 1" | 1" | \$210.00 |




JIC 37° Female Swivel 45°



| ltem # | Hose | JIC | Price |
|-----------|------|------|---------|
| R2-04-684 | 1/4" | 1/4" | \$32.67 |
| R2-06-686 | 3/8" | 3/8" | \$26.74 |
| R2-08-688 | 1/2" | 1/2" | \$31.26 |
| R2-08-690 | 1/2" | 5/8" | \$41.07 |
| R2-12-692 | 3/4" | 3/4" | \$48.44 |
| R2-16-696 | 1" | 1" | \$96.23 |

JIC 37° Female Swivel 90°



| ltem # | Hose | JIC | Price |
|-----------|------|------|---------|
| R2-04-664 | 1/4" | 1/4" | \$24.99 |
| R2-06-666 | 3/8" | 3/8" | \$23.76 |
| R2-08-668 | 1/2" | 1/2" | \$25.59 |
| R2-08-670 | 1/2" | 5/8" | \$32.91 |
| R2-12-672 | 3/4" | 3/4" | \$33.83 |
| R2-16-676 | 1" | 1" | \$74.06 |

IMPORTANT: For use only with SAE 100R2 AT Hydraulic Hose.




SAE 100R5 Field-Attachable Hose Fittings

JIC 37° Female Swivel




| ltem # | Hose | JIC | Price |
|-----------|--------|-------|---------|
| R5-04-604 | 3/16" | 1/4" | \$5.29 |
| R5-05-605 | 1/4" | 5/16" | \$6.73 |
| R5-06-606 | 5/16" | 3/8" | \$7.54 |
| R5-06-608 | 5/16" | 1/2" | \$17.63 |
| R5-08-608 | 13/32" | 1/2" | \$10.10 |
| R5-10-608 | 1/2" | 1/2" | \$24.09 |
| R5-10-610 | 1/2" | 5/8" | \$14.43 |
| R5-12-612 | 5/8" | 3/4" | \$22.45 |
| R5-16-616 | 7/8" | 1" | \$29.56 |

JIC 37° Female Swivel 45°



| ltem # | Hose | JIC | Price |
|-----------|--------|-------|---------|
| R5-04-684 | 3/16" | 1/4" | \$16.17 |
| R5-05-685 | 1/4" | 5/16" | \$17.62 |
| R5-06-686 | 5/16" | 3/8" | \$17.86 |
| R5-08-688 | 13/32" | 1/2" | \$18.60 |
| R5-10-690 | 1/2" | 5/8" | \$26.40 |

JIC 37° Female Swivel 90°



| ltem # | Hose | JIC | Price |
|-----------|--------|-------|---------|
| R5-04-664 | 3/16" | 1/4" | \$13.55 |
| R5-05-665 | 1/4" | 5/16" | \$18.05 |
| R5-06-666 | 5/16" | 3/8" | \$19.98 |
| R5-08-668 | 13/32" | 1/2" | \$21.05 |
| R5-10-670 | 1/2" | 5/8" | \$28.39 |
| R5-12-672 | 5/8" | 3/4" | \$39.21 |
| R5-16-676 | 7/8" | 1" | \$59.55 |

JIC 37° Male



| Item # | Hose | JIC | Price |
|-----------|--------|-------|---------|
| R5-04-504 | 3/16" | 1/4" | \$7.04 |
| R5-05-505 | 1/4" | 5/16" | \$11.96 |
| R5-06-506 | 5/16" | 3/8" | \$7.72 |
| R5-08-508 | 13/32" | 1/2" | \$11.24 |
| R5-10-510 | 1/2" | 5/8" | \$14.62 |
| R5-12-512 | 5/8" | 3/4" | \$25.83 |

NPTF Male Pipe




| ltem # | Hose | NPTF | Price |
|-----------|--------|------|---------|
| R5-04-102 | 3/16" | 1/8" | \$3.83 |
| R5-04-104 | 3/16" | 1/4" | \$4.68 |
| R5-05-104 | 1/4" | 1/4" | \$5.07 |
| R5-06-104 | 5/16" | 1/4" | \$5.57 |
| R5-06-106 | 5/16" | 3/8" | \$7.14 |
| R5-08-106 | 13/32" | 3/8" | \$7.78 |
| R5-08-108 | 13/32" | 1/2" | \$8.84 |
| R5-10-108 | 1/2" | 1/2" | \$11.32 |
| R5-10-112 | 1/2" | 3/4" | \$19.72 |
| R5-12-112 | 5/8" | 3/4" | \$18.14 |
| | | | |

SAE 45° Female Swivel




| ltem # | Hose | SAE | Price |
|-----------|-------|------|---------|
| R5-06-406 | 5/16" | 3/8" | \$7.68 |
| R5-12-412 | 5/8" | 3/4" | \$42.50 |

SAE 45° Female Swivel 45°



| Item # | Hose | SAE | Price |
|-----------|-------|------|---------|
| R5-06-486 | 5/16" | 3/8" | \$17.86 |
| R5-12-492 | 5/8" | 3/4" | \$34.36 |

SAE 45° Female Swivel 90°



| Item # | Hose | SAE | Price |
|-----------|-------|------|---------|
| R5-06-466 | 5/16" | 3/8" | \$19.90 |

SAE 45° Male




| Item # | Hose | SAE | Price |
|-----------|--------|------|---------|
| R5-04-304 | 3/16" | 1/4" | \$3.95 |
| R5-06-306 | 5/16" | 3/8" | \$5.61 |
| R5-08-308 | 13/32" | 1/2" | \$7.19 |
| R5-12-312 | 5/8" | 3/4" | \$11.96 |

Inverted Flare Male Swivel



| Item # | Hose | MIX | Price |
|-----------|--------|-------|---------|
| R5-04-B04 | 3/16" | 1/4" | \$10.53 |
| R5-05-B05 | 1/4" | 5/16" | \$12.26 |
| R5-06-B06 | 5/16" | 3/8" | \$12.34 |
| R5-08-B08 | 13/32" | 1/2" | \$14.48 |

Inverted Flare Male Swivel 90°



| ltem # | Hose | MIX | Price |
|-----------|-------|-------|---------|
| R5-04-E04 | 3/16" | 1/4" | \$17.03 |
| R5-05-E05 | 1/4" | 5/16" | \$25.45 |
| R5-06-E06 | 5/16" | 3/8" | \$21.23 |

IMPORTANT: For use only with SAE 100R5 General Purpose/Truck Hose.

SAE 100R6 Field-Attachable Hose Fittings



| 183 | | |
|------|------|------|
| NPTF | Male | Pipe |



| ltem # | Hose | Pipe | Price |
|-----------|-------|------|---------|
| 183-4084K | 1/4" | 1/4" | \$5.51 |
| 183-4086K | 1/4" | 3/8" | \$7.83 |
| 183-5094K | 5/16" | 1/4" | \$7.72 |
| 183-5096K | 5/16" | 3/8" | \$11.35 |
| 183-6104K | 3/8" | 1/4" | \$6.28 |
| 183-6106K | 3/8" | 3/8" | \$6.74 |
| 183-6108K | 3/8" | 1/2" | \$11.48 |

| 185 |
|-------------------------|
| NPSM Female Pipe Swivel |



| ltem # | Hose | Pipe | Price |
|-----------|-------|------|---------|
| 185-4084K | 1/4" | 1/4" | \$7.78 |
| 185-4086K | 1/4" | 3/8" | \$9.93 |
| 185-5094K | 5/16" | 1/4" | \$10.00 |
| 185-6104K | 3/8" | 1/4" | \$8.88 |
| 185-6106K | 3/8" | 3/8" | \$10.83 |

IMPORTANT: For use only with SAE 100R6 General Purpose Hose.

SAE 100R7 Field-Attachable Hose Fittings

JIC 37° Female Swivel



| ltem # | Hose | JIC | Price |
|-----------|------|------|---------|
| R7-06-606 | 3/8" | 3/8" | \$10.01 |
| R7-08-608 | 1/2" | 1/2" | \$14.34 |

| NPTF | Male | Pipe |
|------|------|------|
| | | _ |

| ΚŢŀ | $\neg m$ |
|-----|----------|
| ӡ⋣ | |

| ltem # | Hose | Pipe | Price |
|-----------|------|------|---------|
| R7-04-104 | 1/4" | 1/4" | \$7.00 |
| R7-06-106 | 3/8" | 3/8" | \$11.73 |
| R7-08-106 | 1/2" | 3/8" | \$11.68 |
| R7-08-108 | 1/2" | 1/2" | \$11.93 |

JIC 37° Male



| Item # | Hose | JIC | Price |
|-----------|------|------|---------|
| R7-04-504 | 1/4" | 1/4" | \$17.68 |
| R7-06-506 | 3/8" | 3/8" | \$11.98 |
| R7-08-508 | 1/2" | 1/2" | \$14.81 |

IMPORTANT: For use only with SAE 100R7 Thermoplastic Hose.



SAE 100R14A Field-Attachable Hose Fittings

63-190600

JIC 37° Female Swivel



| ltem # | Tube | Hose | Price |
|--------------|-------|--------|---------|
| 63-190600-04 | 1/4" | 3/16" | \$17.68 |
| 63-190600-05 | 5/16" | 1/4" | \$22.62 |
| 63-190600-06 | 3/8" | 5/16" | \$22.52 |
| 63-190600-08 | 1/2" | 13/32" | \$31.43 |
| 63-190600-10 | 5/8" | 1/2" | \$35.11 |
| 63-190600-12 | 3/4" | 5/8" | \$45.50 |
| 63-190600-16 | 1" | 7/8" | \$60.01 |

1907772

JIC 37° Female Swivel 90°



| ltem # | Tube | Hose | Price |
|------------|-------|--------|---------|
| 190772-03S | 3/16" | 1/8" | \$47.99 |
| 190772-04S | 1/4" | 3/16" | \$33.56 |
| 190772-05S | 5/16" | 1/4" | \$35.02 |
| 190772-06S | 3/8" | 5/16" | \$35.35 |
| 190772-08S | 1/2" | 13/32" | \$38.55 |
| 190772-10S | 5/8" | 1/2" | \$52.68 |
| 190772-12S | 3/4" | 5/8" | \$68.99 |
| 190772-16S | 1" | 7/8" | \$96.54 |

190773

JIC 37° Female Swivel 45°



| ltem # | Tube | Hose | Price |
|------------|-------|--------|----------|
| 190773-03S | 3/16" | 1/8" | \$51.79 |
| 190773-04S | 1/4" | 3/16" | \$35.45 |
| 190773-06S | 3/8" | 5/16" | \$40.03 |
| 190773-08S | 1/2" | 13/32" | \$43.59 |
| 190773-10S | 5/8" | 1/2" | \$51.71 |
| 190773-12S | 3/4" | 5/8" | \$58.67 |
| 190773-16S | 1" | 7/8" | \$106.34 |

38-190627

NPTF Male Pipe



| Item # | Pipe | Hose | Price |
|-----------------|------|--------|---------|
| 38-190627-02-04 | 1/8" | 3/16" | \$18.27 |
| 38-190627-04-04 | 1/4" | 3/16" | \$17.62 |
| 38-190627-04-05 | 1/4" | 1/4" | \$27.01 |
| 38-190627-04-06 | 1/4" | 5/16" | \$21.21 |
| 38-190627-06-06 | 3/8" | 5/16" | \$24.02 |
| 38-190627-06-08 | 3/8" | 13/32" | \$30.04 |
| 38-190627-08-10 | 1/2" | 1/2" | \$32.51 |
| 38-190627-12-12 | 3/4" | 5/8" | \$36.95 |
| 38-190627-16-16 | 1" | 7/8" | \$59.68 |

63-190990

SAE 45° Female Swivel



| Item # | Tube | Hose | Price |
|--------------|-------|--------|---------|
| 63-190990-04 | 1/4" | 3/16" | \$19.75 |
| 63-190990-05 | 5/16" | 1/4" | \$20.53 |
| 63-190990-06 | 3/8" | 5/16" | \$21.02 |
| 63-190990-08 | 1/2" | 13/32" | \$27.81 |
| 63-190990-10 | 5/8" | 1/2" | \$37.18 |
| 63-190990-12 | 3/4" | 5/8" | \$44.77 |

FC9171

SAE 45° Female Swivel 90°



| Item # | Tube | Hose | Price |
|--------------|------|-------|---------|
| FC9171-0606S | 3/8" | 5/16" | \$36.06 |
| FC9171-1212S | 3/4" | 5/8" | \$49.28 |

900568

Replacement Sleeve

Sleeve is good for only one use. Sleeve must be replaced when the fitting is re-used.

| ltem # | Hose ID | Price |
|------------|---------|---------|
| 900568-03B | 1/8" | \$3.52 |
| 900568-04B | 3/16" | \$4.60 |
| 900568-05B | 1/4" | \$5.61 |
| 900568-06B | 5/16" | \$4.67 |
| 900568-08B | 13/32" | \$5.54 |
| 900568-10B | 1/2" | \$6.70 |
| 900568-12B | 5/8" | \$7.44 |
| 900568-16B | 7/8" | \$10.97 |

| IMPORTANT: F | or use only with |
|--------------|------------------|
| SAE 100R14 | A PTFE Hose. |

Push-Lock Hose Barbs



271 NPTF Male Pipe Swivel

|--|

| Item # | Hose | Pipe | Price |
|-----------|------|------|--------|
| 271-0404C | 1/4" | 1/4" | \$3.75 |
| 271-0604C | 3/8" | 1/4" | \$3.84 |
| 271-0606C | 3/8" | 3/8" | \$4.29 |
| 271-0806C | 1/2" | 3/8" | \$4.66 |
| 271-0808C | 1/2" | 1/2" | \$5.66 |
| 271-1212C | 3/4" | 3/4" | \$8.38 |

272 NPTF Male Pipe



| ltem # | Hose | Pipe | Price |
|-----------|-------|------|---------|
| 272-0402C | 1/4" | 1/8" | \$1.17 |
| 272-0404C | 1/4" | 1/4" | \$1.39 |
| 272-0406C | 1/4" | 3/8" | \$1.18 |
| 272-0502C | 5/16" | 1/8" | \$1.55 |
| 272-0504C | 5/16" | 1/4" | \$1.80 |
| 272-0602C | 3/8" | 1/8" | \$1.48 |
| 272-0604C | 3/8" | 1/4" | \$1.39 |
| 272-0606C | 3/8" | 3/8" | \$1.62 |
| 272-0608C | 3/8" | 1/2" | \$2.55 |
| 272-0612C | 3/8" | 3/4" | \$5.75 |
| 272-0804C | 1/2" | 1/4" | \$2.01 |
| 272-0806C | 1/2" | 3/8" | \$1.87 |
| 272-0808C | 1/2" | 1/2" | \$2.55 |
| 272-0812C | 1/2" | 3/4" | \$4.38 |
| 272-1006C | 5/8" | 3/8" | \$4.29 |
| 272-1008C | 5/8" | 1/2" | \$4.17 |
| 272-1012C | 5/8" | 3/4" | \$5.38 |
| 272-1208C | 3/4" | 1/2" | \$4.38 |
| 272-1212C | 3/4" | 3/4" | \$4.17 |
| 272-1612C | 1" | 3/4" | \$10.71 |
| 272-1616C | 1" | 1" | \$12.56 |

273 NPTF Male Pipe 90°



| Item # | Hose | Pipe | Price |
|-----------|------|------|---------|
| 273-0402C | 1/4" | 1/8" | \$2.57 |
| 273-0404C | 1/4" | 1/4" | \$3.00 |
| 273-0602C | 3/8" | 1/8" | \$3.94 |
| 273-0604C | 3/8" | 1/4" | \$3.00 |
| 273-0606C | 3/8" | 3/8" | \$3.86 |
| 273-0806C | 1/2" | 3/8" | \$4.88 |
| 273-0808C | 1/2" | 1/2" | \$5.66 |
| 273-1208C | 3/4" | 1/2" | \$14.73 |
| 273-1212C | 3/4" | 3/4" | \$10.51 |

274 NPTF Female Pipe



| Item # | Hose | Pipe | Price |
|-----------|-------|------|--------|
| 274-0402C | 1/4" | 1/8" | \$2.30 |
| 274-0404C | 1/4" | 1/4" | \$1.75 |
| 274-0406C | 1/4" | 3/8" | \$3.95 |
| 274-0502C | 5/16" | 1/8" | \$1.96 |
| 274-0504C | 5/16" | 1/4" | \$2.17 |
| 274-0602C | 3/8" | 1/8" | \$2.03 |
| 274-0604C | 3/8" | 1/4" | \$2.01 |
| 274-0606C | 3/8" | 3/8" | \$2.46 |
| 274-0608C | 3/8" | 1/2" | \$2.72 |
| 274-0612C | 3/8" | 3/4" | \$6.42 |
| 274-0804C | 1/2" | 1/4" | \$3.73 |
| 274-0806C | 1/2" | 3/8" | \$2.79 |
| 274-0808C | 1/2" | 1/2" | \$2.72 |
| 274-0812C | 1/2" | 3/4" | \$7.21 |
| 274-1006C | 5/8" | 3/8" | \$3.39 |
| 274-1008C | 5/8" | 1/2" | \$3.10 |
| 274-1208C | 3/4" | 1/2" | \$4.60 |
| 274-1212C | 3/4" | 3/4" | \$5.66 |
| | | | |

278

NPSM Female Pipe Swivel Ballseat Type



| Item # | Hose | Pipe | Price |
|-----------|------|------|---------|
| 278-0402C | 1/4" | 1/8" | \$4.10 |
| 278-0404C | 1/4" | 1/4" | \$2.35 |
| 278-0406C | 1/4" | 3/8" | \$3.72 |
| 278-0604C | 3/8" | 1/4" | \$3.63 |
| 278-0606C | 3/8" | 3/8" | \$4.47 |
| 278-0808C | 1/2" | 1/2" | \$5.21 |
| 278-0812C | 1/2" | 3/4" | \$7.21 |
| 278-1212C | 3/4" | 3/4" | \$10.09 |

280

NPSM Female Pipe Swivel Gasket Type



| Item # | Hose | Pipe | Price |
|-----------|------|------|---------|
| 280-0402C | 1/4" | 1/8" | \$4.82 |
| 280-0404C | 1/4" | 1/4" | \$3.20 |
| 280-0604C | 3/8" | 1/4" | \$3.80 |
| 280-0606C | 3/8" | 3/8" | \$5.01 |
| 280-0608C | 3/8" | 1/2" | \$6.99 |
| 280-0808C | 1/2" | 1/2" | \$6.34 |
| 280-1212C | 3/4" | 3/4" | \$11.72 |
| | | | |

282

SAE 45° Male



| Item # | Hose | Tube | Price |
|-----------|------|-------|--------|
| 282-0407C | 1/4" | 1/4" | \$2.50 |
| 282-0408C | 1/4" | 5/16" | \$2.03 |
| 282-0610C | 3/8" | 3/4" | \$3.00 |
| 282-0812C | 1/2" | 1/2" | \$4.96 |
| 282-1014C | 5/8" | 5/8" | \$4.95 |
| 282-1217C | 3/4" | 3/4" | \$9.79 |
| | | | |

No clamps or ferrules required when used with Push-Lock Low Pressure Hose.



Push-Lock Hose Barbs

284 SAE 45° Female Swivel



| Item # | Hose | Tube | Price |
|-----------|-------|------|--------|
| 284-0410C | 1/4" | 3/8" | \$3.02 |
| 284-0510C | 5/16" | 3/8" | \$3.10 |
| 284-0610C | 3/8" | 3/8" | \$2.50 |
| 284-1217C | 3/4" | 3/4" | \$7.29 |

286

JIC 37° Flare Male



| Item # | Hose | Tube | Price |
|-----------|------|------|---------|
| 286-0407C | 1/4" | 1/4" | \$2.37 |
| 286-0409C | 1/4" | 3/4" | \$37.42 |
| 286-0609C | 3/8" | 3/8" | \$3.72 |
| 286-0812C | 1/2" | 1/2" | \$4.50 |
| 286-1014C | 5/8" | 5/8" | \$9.20 |
| 286-1217C | 3/4" | 3/4" | \$9.22 |

287

Dual Angle Seat (SAE 45° / JIC 37° Flare) Female Swivel



| Item # | Hose | Tube | Price |
|-----------|------|-------|--------|
| 287-0407C | 1/4" | 1/4" | \$2.37 |
| 287-0408C | 1/4" | 5/16" | \$2.55 |
| 287-0612C | 3/8" | 1/2" | \$4.03 |
| 287-0812C | 1/2" | 1/2" | \$3.20 |
| 287-0814C | 1/2" | 5/8" | \$5.41 |
| 287-1014C | 5/8" | 5/8" | \$5.64 |

288

JIC 37° Flare Female Swivel



| Item # | Hose | Tube | Price |
|-----------|-------|------|--------|
| 288-0409C | 1/4" | 3/8" | \$3.00 |
| 288-0509C | 5/16" | 3/8" | \$3.72 |
| 288-0609C | 3/8" | 3/8" | \$2.55 |
| 288-1217C | 3/4" | 3/4" | \$6.64 |

289

Dual Angle Seat* (SAE 45° / JIC 37° Flare) Female Swivel 90°



| Item # | Hose | Tube | Price |
|-------------|------|------|---------|
| 289-0407C | 1/4" | 1/4" | \$26.11 |
| 289-0609C | 3/8" | 3/8" | \$24.10 |
| 289-0610SAE | 3/8" | 3/8" | \$32.72 |
| 289-0812C | 1/2" | 1/2" | \$29.94 |
| 289-1217C | 3/4" | 3/4" | \$78.80 |

* 3/8" tube fittings do not have a dual angle seat. Use 289-0609C with JIC 37° flare and 289-0610SAE with SAE 45° flare.

290

Inverted Flare Male Swivel



| Item # | Hose | Tube | Price |
|-----------|-------|-------|--------|
| 290-0406C | 1/4" | 3/16" | \$3.45 |
| 290-0407C | 1/4" | 1/4" | \$2.66 |
| 290-0408C | 1/4" | 5/16" | \$2.85 |
| 290-0508C | 5/16" | 5/16" | \$3.58 |
| 290-0510C | 5/16" | 3/8" | \$4.58 |
| 290-0608C | 3/8" | 5/16" | \$3.10 |
| 290-0610C | 3/8" | 3/8" | \$3.26 |
| 290-0812C | 1/2" | 1/2" | \$5.38 |
| 290-1014C | 5/8" | 5/8" | \$7.41 |

292

Inverted Flare Female



| Item # | Hose | Tube | Price |
|-----------|------|-------|--------|
| 292-0406C | 1/4" | 3/16" | \$2.75 |
| 292-0407C | 1/4" | 1/4" | \$2.72 |
| 292-0408C | 1/4" | 5/16" | \$2.64 |
| 292-0608C | 3/8" | 5/16" | \$4.13 |
| 292-0610C | 3/8" | 3/8" | \$3.50 |
| 292-0812C | 1/2" | 1/2" | \$5.50 |

294

Rigid Tube Shank, North American



| Item # | Hose | Tube | Price |
|-----------|-------|-------|--------|
| 294-0403C | 1/4" | 3/16" | \$2.22 |
| 294-0404C | 1/4" | 1/4" | \$1.48 |
| 294-0405C | 1/4" | 5/16" | \$1.87 |
| 294-0505C | 5/16" | 5/16" | \$2.09 |
| 294-0606C | 3/8" | 3/8" | \$3.10 |
| 294-0808C | 1/2" | 1/2" | \$5.48 |
| 294-1010C | 5/8" | 5/8" | \$5.38 |
| 294-1212C | 3/4" | 3/4" | \$5.23 |

294M

Π

Rigid Tube Shank, Metric

| Item # | Hose | Tube | Price |
|------------|------|------|--------|
| 294M-0406M | 1/4" | 6mm | \$2.30 |
| 294M-0408M | 1/4" | 8mm | \$2.42 |
| 294M-0610M | 3/8" | 10mm | \$2.50 |
| 294M-0612M | 3/8" | 12mm | \$2.50 |
| 294M-0815M | 1/2" | 15mm | \$3.31 |
| 294M-1018M | 5/8" | 18mm | \$3.38 |
| 294M-1222M | 3/4" | 22mm | \$4.82 |

296

Hose Mender



| Item # | Hose | Price |
|-----------|-------|--------|
| 296-0404C | 1/4" | \$1.75 |
| 296-0505C | 5/16" | \$1.80 |
| 296-0606C | 3/8" | \$2.03 |
| 296-0808C | 1/2" | \$2.66 |
| 296-1010C | 5/8" | \$4.13 |
| 296-1212C | 3/4" | \$5.01 |

No clamps or ferrules required when used with Push-Lock Low Pressure Hose.

Brass Hose Barbs



102 NPTF Male Pipe



103

Item # 103-0404C

103-0604C 103-0606C

103-0806C

103-0808C

103-1212C

NPTF Male Pipe Swivel

Hose

1/4"

3/8"

3/8"

1/2"

1/2"

3/4"

NPTF

1/4"

1/4"

3/8"

3/8"

1/2"

3/4"

Price

\$3.75

\$3.86

\$4.21

\$4.76

\$6.02

\$7.80

| Item # | Hose | NPTF | Price |
|-----------|--------|------|--------|
| 102-0202C | 1/8" | 1/8" | \$1.08 |
| 102-0204C | 1/8" | 1/4" | \$1.33 |
| 102-0302C | 3/16" | 1/8" | \$0.87 |
| 102-0304C | 3/16" | 1/4" | \$1.17 |
| 102-0402C | 1/4" | 1/8" | \$1.00 |
| 102-0404C | 1/4" | 1/4" | \$0.87 |
| 102-0406C | 1/4" | 3/8" | \$1.55 |
| 102-0408C | 1/4" | 1/2" | \$2.79 |
| 102-0502C | 5/16" | 1/8" | \$1.08 |
| 102-0504C | 5/16" | 1/4" | \$1.17 |
| 102-0506C | 5/16" | 3/8" | \$1.75 |
| 102-0602C | 3/8" | 1/8" | \$1.39 |
| 102-0604C | 3/8" | 1/4" | \$0.85 |
| 102-0606C | 3/8" | 3/8" | \$1.39 |
| 102-0608C | 3/8" | 1/2" | \$2.33 |
| 102-0612C | 3/8" | 3/4" | \$3.93 |
| 102-0804C | 1/2" | 1/4" | \$1.67 |
| 102-0806C | 1/2" | 3/8" | \$1.45 |
| 102-0808C | 1/2" | 1/2" | \$2.01 |
| 102-0812C | 1/2" | 3/4" | \$3.45 |
| 102-1006C | 5/8" | 3/8" | \$2.01 |
| 102-1008C | 5/8" | 1/2" | \$2.46 |
| 102-1012C | 5/8" | 3/4" | \$3.63 |
| 102-1208C | 3/4" | 1/2" | \$2.72 |
| 102-1212C | 3/4" | 3/4" | \$3.02 |
| 102-1612C | 1" | 3/4" | \$4.13 |
| 102-1616C | 1" | 1" | \$7.21 |
| 102-2012C | 1-1/4" | 3/4" | \$6.89 |
| 102-2016C | 1-1/4" | 1" | \$7.10 |

104 NPTF Female Pipe



124 NPSM Female Pipe Swivel

1"

1"

3/4"

1"

\$4.88

\$9.01



104-1612C

104-1616C

| ltem # | Hose | NPSM | Price |
|-----------|-------|------|--------|
| 124-0202K | 1/8" | 1/8" | \$1.58 |
| 124-0302K | 3/16" | 1/8" | \$1.58 |
| 124-0304K | 3/16" | 1/4" | \$1.80 |
| 124-0402K | 1/4" | 1/8" | \$1.72 |
| 124-0404K | 1/4" | 1/4" | \$1.48 |
| 124-0406K | 1/4" | 3/8" | \$2.03 |
| 124-0504K | 5/16" | 1/4" | \$1.80 |
| 124-0506K | 5/16" | 3/8" | \$2.30 |
| 124-0604K | 3/8" | 1/4" | \$1.62 |
| 124-0606K | 3/8" | 3/8" | \$2.12 |
| 124-0608K | 3/8" | 1/2" | \$3.31 |
| 124-0806K | 1/2" | 3/8" | \$2.37 |
| 124-0808K | 1/2" | 1/2" | \$3.10 |
| 124-1212K | 3/4" | 3/4" | \$4.73 |
| | | | |

129 NPTF Male Pipe 90°



| Item # | Hose | NPTF | Price |
|-----------|-------|------|---------|
| 129-0302C | 3/16" | 1/8" | \$2.22 |
| 129-0402C | 1/4" | 1/8" | \$2.22 |
| 129-0404C | 1/4" | 1/4" | \$2.55 |
| 129-0406C | 1/4" | 3/8" | \$3.58 |
| 129-0502C | 5/16" | 1/8" | \$2.85 |
| 129-0504C | 5/16" | 1/4" | \$2.75 |
| 129-0506C | 5/16" | 3/8" | \$4.13 |
| 129-0602C | 3/8" | 1/8" | \$2.37 |
| 129-0604C | 3/8" | 1/4" | \$2.46 |
| 129-0606C | 3/8" | 3/8" | \$3.17 |
| 129-0608C | 3/8" | 1/2" | \$3.72 |
| 129-0804C | 1/2" | 1/4" | \$3.17 |
| 129-0806C | 1/2" | 3/8" | \$4.25 |
| 129-0808C | 1/2" | 1/2" | \$5.04 |
| 129-1006C | 5/8" | 3/8" | \$5.95 |
| 129-1008C | 5/8" | 1/2" | \$7.21 |
| 129-1208C | 3/4" | 1/2" | \$9.83 |
| 129-1212C | 3/4" | 3/4" | \$12.14 |
| 129-1612C | 1" | 3/4" | \$13.77 |
| 129-1616C | 1" | 1" | \$16.21 |

139 NPTF Male Pipe 45°



| ltem # | Hose | NPTF | Price |
|-----------|------|------|--------|
| 139-0402C | 1/4" | 1/8" | \$4.66 |
| 139-0404C | 1/4" | 1/4" | \$4.76 |
| 139-0602C | 3/8" | 1/8" | \$3.58 |
| 139-0604C | 3/8" | 1/4" | \$3.17 |
| 139-0606C | 3/8" | 3/8" | \$4.94 |
| 139-0804C | 1/2" | 1/4" | \$5.95 |
| 139-0806C | 1/2" | 3/8" | \$4.94 |
| 139-0808C | 1/2" | 1/2" | \$6.83 |

Brass hose barbs must be securely affixed with clamps or ferrules.



142 SAE 45° Male



| ltem # | Hose | Tube | Price |
|-----------|-------|-------|--------|
| 142-0307C | 3/16" | 1/4" | \$1.87 |
| 142-0407C | 1/4" | 1/4" | \$1.39 |
| 142-0410C | 1/4" | 3/8" | \$1.48 |
| 142-0508C | 5/16" | 5/16" | \$2.37 |
| 142-0610C | 3/8" | 3/8" | \$1.48 |
| 142-0612C | 3/8" | 1/2" | \$2.50 |
| 142-0812C | 1/2" | 1/2" | \$3.02 |

143

SAE 45° / JIC 37° Dual Angle Seat Female Swivel



Note: In all sizes except -06 and -12, SAE 45° flare and JIC 37° flare use the same thread. However, the sealing surface angles are not the same.

| ltem # | Hose | Tube | Price |
|-----------|-------|-------|--------|
| 143-0307K | 3/16" | 1/4" | \$1.67 |
| 143-0407K | 1/4" | 1/4" | \$1.62 |
| 143-0408K | 1/4" | 5/16" | \$1.96 |
| 143-0508K | 5/16" | 5/16" | \$2.03 |
| 143-0612K | 3/8" | 1/2" | \$2.95 |
| 143-0812K | 1/2" | 1/2" | \$3.13 |
| 143-0814K | 1/2" | 5/8" | \$3.86 |

144

SAE 45° Female Swivel



| ltem # | Hose | Tube | Price |
|-----------|-------|-------|--------|
| 144-0306K | 3/16" | 3/16" | \$1.72 |
| 144-0410K | 1/4" | 3/8" | \$2.01 |
| 144-0510K | 5/16" | 3/8" | \$2.17 |
| 144-0610K | 3/8" | 3/8" | \$2.17 |
| 144-0812K | 1/2" | 1/2" | \$3.50 |

145

JIC 37° Female Swivel



| ltem # | Hose | Tube | Price |
|-----------|------|------|--------|
| 145-0609K | 3/8" | 3/8" | \$2.01 |

172

NPSM x NPTF Adapter



| ltem # | NPSM | NPTF | Price |
|-----------|------|------|--------|
| 172-0202C | 1/8" | 1/8" | \$1.33 |
| 172-0402C | 1/4" | 1/8" | \$1.26 |
| 172-0404C | 1/4" | 1/4" | \$1.42 |
| 172-0604C | 3/8" | 1/4" | \$1.96 |
| 172-0606C | 3/8" | 3/8" | \$2.07 |
| 172-0608C | 3/8" | 1/2" | \$3.28 |
| 172-0806C | 1/2" | 3/8" | \$2.24 |
| 172-0808C | 1/2" | 1/2" | \$3.06 |
| 172-1212C | 3/4" | 3/4" | \$3.89 |

176 NPSM x NPSM Union

| Item # | NPSM | Price |
|-----------|------|--------|
| 176-0202C | 1/8" | \$1.80 |
| 176-0404C | 1/4" | \$2.01 |
| 176-0606C | 3/8" | \$3.13 |
| 176-0808C | 1/2" | \$4.76 |

Brass Hose Barbs

177 Hose Mender Elbow



| ltem # | Hose | Price |
|-----------|-------|--------|
| 177-0404C | 1/4" | \$2.33 |
| 177-0505C | 5/16" | \$2.95 |
| 177-0606C | 3/8" | \$3.00 |
| 177-0808C | 1/2" | \$4.21 |

178

Hose Mender



| ltem # | Hose | Price |
|-----------|-------|--------|
| 178-0202C | 1/8" | \$1.20 |
| 178-0303C | 3/16" | \$1.08 |
| 178-0404C | 1/4" | \$1.00 |
| 178-0505C | 5/16" | \$1.26 |
| 178-0606C | 3/8" | \$1.30 |
| 178-0808C | 1/2" | \$1.84 |
| 178-1010C | 5/8" | \$2.50 |
| 178-1212C | 3/4" | \$2.79 |
| 178-1616C | 1" | \$4.13 |

1**79**

Mender Tee



| ltem # | Hose | Price |
|-----------|-------|--------|
| 179-0303C | 3/16" | \$3.17 |
| 179-0404C | 1/4" | \$3.00 |
| 179-0505C | 5/16" | \$3.56 |
| 179-0606C | 3/8" | \$3.58 |
| 179-0808C | 1/2" | \$5.21 |
| 179-1010C | 5/8" | \$7.99 |
| 179-1212C | 3/4" | \$9.96 |

Brass hose barbs must be securely affixed with clamps or ferrules.

Brass Hose Ferrules and Clamps



BFM **Brass Ferrules for**

Medium Weight Air Hose

| 1 | (/) |
|---|------|
| | |
| 1 | |
| 1 | |

| | Ferrule I.D. | Ferrule Length | End Hole Size | Metal Gauge | Standard Ind. Part # | Ribbed Die* | Plain Die* | Bag Qty. | Item Number | Price** |
|----|-----------------|-------------------|------------------|----------------|-------------------------|----------------|---------------|-------------|-------------|---------|
| or | 0.478" | 11/16" | 21/64" | 0.024" | 4750 | R41 | P41/P42 | 50 | BFM478-BAG | \$16.58 |
| t | 0.500" | 1" | 11/32" | 0.024" | 7322 | R40 | P40 | 50 | BFM500-BAG | \$21.55 |
| | 0.525" | 1" | 3/8" | 0.024" | 7323 | R39 | P39 | 50 | BFM525-BAG | \$21.55 |
| | 0.531" | 1" | 7/16" | 0.024" | 7324 | R39 | P39 | 50 | BFM531-BAG | \$22.40 |
| | 0.562" | 1" | 7/16" | 0.024" | 7325 | R37 | P38 | 50 | BFM562-BAG | \$24.05 |
| | 0.593" | 1" | 7/16" | 0.024" | 7326 | R36 | P37 | 50 | BFM593-BAG | \$24.86 |
| | 0.625" | 1" | 7/16" | 0.024" | 7327 | R35 | P25 | 50 | BFM625-BAG | \$25.69 |
| | 0.656" | 1" | 7/16" | 0.024" | 7328 | R34 | P35 | 50 | BFM656-BAG | \$27.35 |
| | 0.687" | 1" | 1/2" | 0.024" | 7329 | R33 | P34 | 50 | BFM687-BAG | \$27.35 |
| | 0.718" | 1" | 5/8" | 0.024" | 7330 | R31 | P32 | 50 | BFM718-BAG | \$29.02 |
| | 0.718" | 1" | 1/2" | 0.024" | 7330B | R31 | P32 | 50 | BFM718B-BAG | \$28.18 |
| | 0.750" | 1" | 5/8" | 0.024" | 7331 | R30 | P31 | 50 | BFM750-BAG | \$29.02 |
| | 0.750" | 1" | 1/2" | 0.024" | 7331B | R30 | P31 | 50 | BFM750B-BAG | \$28.18 |
| | 0.781" | 1" | 5/8" | 0.024" | 7332 | R29 | P30 | 50 | BFM781-BAG | \$30.67 |
| | 0.781" | 1" | 1/2" | 0.024" | 7332B | R29 | P30 | 50 | BFM781B-BAG | \$29.85 |
| | 0.812" | 1" | 5/8" | 0.024" | 7333 | R28 | P29 | 50 | BFM812-BAG | \$31.50 |

BFL

Brass Ferrules fo Light Weight Air Hose

| for | Ferrule I.D. | Ferrule Length | End Hole Size | Metal Gauge | Standard Ind. Part # | Ribbed Die* | Plain Die* | Bag Qty. | Item Number | Price** |
|----------|-----------------|-------------------|------------------|----------------|-------------------------|----------------|---------------|-------------|-------------|---------|
| ir İr | 0.380" | 1/2" | 17/64" | .016" | 622 | R44 | P45 | 50 | BFL380-BAG | \$10.77 |
| Ir | 0.400" | 15/32" | 17/64" | .020" | 619 | R44 | P44 | 50 | BFL400-BAG | \$11.60 |
| | 0.410" | 1/2" | 17/64" | .016" | 620 | R43 | P44 | 50 | BFL410-BAG | \$11.60 |
| | 0.450" | 9/16" | 11/32" | .016" | 769 | R41 | P42 | 50 | BFL450-BAG | \$11.60 |
| | 0.500" | 1/2" | 11/32" | .016" | 624 | R40 | P41 | 50 | BFL500-BAG | \$11.60 |
| | 0.525" | 1/2" | 11/32" | .016" | 625 | R39 | P40 | 50 | BFL525-BAG | \$11.60 |
| | 0.548" | 31/64" | 3/8" | .015" | 626 | R38 | P39 | 50 | BFL548-BAG | \$11.60 |
| | 0.564" | 3/4" | 3/8" | .019" | 3588 | R37 | P38 | 50 | BFL564-BAG | \$16.58 |
| | 0.575" | 31/64" | 15/32" | .019" | KK | R37 | P38 | 50 | BFL575-BAG | \$11.60 |
| | 0.600" | 1/2" | 1/2" | .019" | JJ | R36 | P37 | 50 | BFL600-BAG | \$13.26 |
| | 0.625" | 1/2" | 1/2" | .019" | II | R35 | P36 | 50 | BFL625-BAG | \$14.08 |
| | 0.650" | 1/2" | 1/2" | .019" | HH | R34 | P35 | 50 | BFL650-BAG | \$14.92 |
| | 0.675" | 33/64" | 1/2" | .019" | GG | R34 | P34 | 50 | BFL675-BAG | \$15.74 |
| | 0.725" | 17/32" | 1/2" | .019" | EE | R31 | P32 | 50 | BFL725-BAG | \$15.74 |
| | 0.750" | 17/32" | 1/2" | .019" | DD | R30 | P32 | 50 | BFL750-BAG | \$16.58 |
| | 0.775" | 17/32" | 1/2" | .016" | CC | R31 | P31 | 50 | BFL775-BAG | \$28.18 |
| | | | | | | | | | | |

* Use these dies with the 660T Manual Ferrule Vise or 670T Air-Operated Ferrule Vise (page 69).

** Price per bag. Brass ferrules are not sold individually.

Discount Hydraulic Hose

Brass Hose Ferrules and Clamps

- -

D - -

BF/BFW/ BFMW

Brass Ferrules for Medium Weight Air or Water Hose Farmela.

...



| Ferrule I.D. | Ferrule Length | End Hole Size | Metal Gauge | Standard Ind. Part # | Ribbed Die* | Plain Die* | Bag Qty. | Item Number | Price** |
|-----------------|-------------------|------------------|----------------|-------------------------|----------------|---------------|-------------|--------------|---------|
| 0.800" | 0.844" | 0.688" | .024 | | R28 | P29 | 25 | BF800-BAG | \$11.60 |
| 0.825" | 0.844" | 0.688" | .024 | | R27 | P28 | 25 | BF825-BAG | \$12.03 |
| 0.850" | 0.568" | 0.688" | .019 | Z | R26 | P27 | 25 | BF850-BAG | \$10.77 |
| 0.875" | 0.844" | 0.688" | .024 | 7244A | R25 | P26 | 25 | BFW875-BAG | \$13.67 |
| 0.900" | 0.844" | 0.688" | .024 | 5029A | R24 | P25 | 25 | BFW900-BAG | \$13.67 |
| 0.925" | 0.840" | 0.690" | .025 | 7113 | R23 | P24 | 25 | BFW925-BAG | \$13.67 |
| 0.975" | 0.844" | 0.688" | .024 | 5028A | R21 | P22 | 25 | BFW975-BAG | \$16.58 |
| 1.025" | 0.844" | 0.688" | .024 | 7114A | R19 | P20 | 25 | BFW1025-BAG | \$17.42 |
| 1.175" | 0.844" | 0.688" | .024 | 7088A | R13 | P14 | 25 | BFW1175-BAG | \$19.47 |
| 1.050" | 0.625" | 0.750" | .025 | 3605 | R18 | P19 | 25 | BFMW1050-BAG | \$25.69 |
| 1.100" | 0.843" | 0.812" | .023 | 5027 | R16 | P17 | 25 | BFMW1100-BAG | \$19.47 |
| 1.150" | 0.844" | 0.880" | .024 | 7104A | R15 | P15 | 25 | BFMW1150-BAG | \$20.72 |
| 1.225" | 0.875" | 0.875" | .025 | 875-K | R11 | P12 | 25 | BFMW1225-BAG | \$25.69 |
| 1.275" | 0.875" | 1.000" | .025 | 875-1 | R9 | P10 | 25 | BFMW1275-BAG | \$55.14 |
| 1.400" | 0.687" | 1.120" | .020 | D | R4 | P5 | 25 | BFMW1400-BAG | \$55.95 |
| 1.500" | 0.875" | 1.120" | .025 | 1500 | | P1 | 25 | BFMW1500-BAG | \$33.58 |
| | | | | | | | | | |

Standard Dibbad Diain

* Use these dies with the 660T Manual Ferrule Vise or 670T Air-Operated Ferrule Vise (page 69).

Matal

Fudllala


** Price per bag. Brass ferrules are not sold individually.

Stainless Steel Wormgear Band Clamps



25% OFF when you buy 100 or more. Mix and match all sizes

| s Steel | Hose O.D. | Band Width | ltem # | Price | Hose O.D. | Band Width | ltem # | Price |
|---------------|---------------|------------|--------|--------|-------------|------------|--------|--------|
| ear Band | 0.22"-0.63" | 5/16" | M4P | \$0.47 | 2.06"-3.00" | 1/2" | B40H | \$0.77 |
| | 0.31"-0.88" | 5/16" | M6P | \$0.51 | 2.31"-3.25" | 1/2" | B44H | \$0.83 |
| | 0.38"-0.88" | 1/2" | B6H | \$0.61 | 2.56"-3.50" | 1/2" | B48H | \$0.83 |
| | 0.44" - 1.00" | 1/2" | B8H | \$0.61 | 2.81"-3.75" | 1/2" | B52H | \$0.90 |
| end | 0.56" - 1.06" | 1/2" | B10H | \$0.61 | 3.06"-4.00" | 1/2" | B56H | \$0.90 |
| NUL ST | 0.56"-1.25" | 1/2" | B12H | \$0.62 | 3.31"-4.25" | 1/2" | B60H | \$0.95 |
| FF | 0.69"-1.50" | 1/2" | B16H | \$0.62 | 2.50"-4.50" | 1/2" | B64H | \$0.95 |
| u buy | 0.75" – 1.75" | 1/2" | B20H | \$0.63 | 3.00"-5.00" | 1/2" | B72H | \$1.01 |
| ore. | 1.06"-2.00" | 1/2" | B24H | \$0.63 | 3.50"-5.50" | 1/2" | B80H | \$1.07 |
| tch all sizes | 1.31"-2.25" | 1/2" | B28H | \$0.65 | 4.00"-6.00" | 1/2" | B88H | \$1.17 |
| | 1.56"-2.50" | 1/2" | B32H | \$0.65 | 4.50"-6.50" | 1/2" | B96H | \$1.33 |
| | 1.81"-2.75" | 1/2" | B36H | \$0.65 | 5.00-7.00" | 1/2" | B104H | \$1.33 |



SAE 100R5 Truck Hose Fittings



MP

NPTF Male Pipe



| Item Number | Hose | Pipe | Price |
|-------------|----------|--------|---------|
| MP-03-02-R5 | 3/16" | 1/8" | \$3.28 |
| MP-03-04-R5 | 3/16" | 1/4" | \$4.16 |
| MP-05-04-R5 | 5/16" | 1/4" | \$4.38 |
| MP-05-06-R5 | 5/16" | 3/8" | \$4.16 |
| MP-07-06-R5 | 13/32" | 3/8" | \$8.69 |
| MP-07-08-R5 | 13/32" | 1/2" | \$9.21 |
| MP-10-08-R5 | 5/8" | 1/2" | \$2.64 |
| MP-10-12-R5 | 5/8" | 3/4" | \$2.73 |
| MP-14-12-R5 | 7/8" | 3/4" | \$38.72 |
| MP-14-16-R5 | 7/8" | 1" | \$40.81 |
| MP-18-20-R5 | 1-1/8" | 1-1/4" | \$44.63 |
| MP-22-24-R5 | 1-3/8" | 1-1/2" | \$51.12 |
| MP-29-32-R5 | 1-13/16" | 2" | \$56.64 |

FJX


JIC 37° Female Swivel

| [| |
|---|--|
| | |

| Item Number | Hose | JIC | Price |
|--------------|----------|--------|---------|
| FJX-03-04-R5 | 3/16" | 1/4" | \$3.83 |
| FJX-03-05-R5 | 3/16" | 5/16" | \$9.35 |
| FJX-05-04-R5 | 5/16" | 1/4" | \$6.39 |
| FJX-05-05-R5 | 5/16" | 5/16" | \$6.39 |
| FJX-05-06-R5 | 5/16" | 3/8" | \$4.68 |
| FJX-07-06-R5 | 13/32" | 3/8" | \$9.27 |
| FJX-07-08-R5 | 13/32" | 1/2" | \$9.88 |
| FJX-10-08-R5 | 5/8" | 1/2" | \$8.37 |
| FJX-10-10-R5 | 5/8" | 5/8" | \$8.24 |
| FJX-10-12-R5 | 5/8" | 3/4" | \$8.24 |
| FJX-14-12-R5 | 7/8" | 3/4" | \$25.89 |
| FJX-14-16-R5 | 7/8" | 1" | \$27.92 |
| FJX-18-20-R5 | 1-1/8" | 1-1/4" | \$32.41 |
| FJX-22-24-R5 | 1-3/8" | 1-1/2" | \$63.82 |
| FJX-29-32-R5 | 1-13/16" | 2" | \$92.81 |

FJX45

JIC 37° Female Swivel 45°



| Item Number | Hose | JIC | Price |
|----------------|--------|------|---------|
| FJX45-03-04-R5 | 3/16" | 1/4" | \$9.29 |
| FJX45-05-04-R5 | 5/16" | 1/4" | \$7.73 |
| FJX45-05-06-R5 | 5/16" | 3/8" | \$7.73 |
| FJX45-07-06-R5 | 13/32" | 3/8" | \$11.62 |
| FJX45-07-08-R5 | 13/32" | 1/2" | \$11.22 |
| FJX45-10-10-R5 | 5/8" | 5/8" | \$14.98 |
| FJX45-10-12-R5 | 5/8" | 3/4" | \$16.46 |
| FJX45-14-16-R5 | 7/8" | 1" | \$35.93 |
| | | | |

FJX90

JIC 37° Female Swivel 90°



| Item Number | Hose | JIC | Price |
|----------------|--------|-------|---------|
| FJX90-03-04-R5 | 3/16" | 1/4" | \$8.23 |
| FJX90-05-04-R5 | 5/16" | 1/4" | \$24.52 |
| FJX90-05-05-R5 | 5/16" | 5/16" | \$14.40 |
| FJX90-05-06-R5 | 5/16" | 3/8" | \$9.29 |
| FJX90-07-06-R5 | 5/16" | 3/8" | \$13.47 |
| FJX90-07-08-R5 | 13/32" | 3/8" | \$14.56 |
| FJX90-10-10-R5 | 5/8" | 5/8" | \$13.58 |
| FJX90-10-12-R5 | 5/8" | 3/4" | \$16.18 |
| FJX90-14-16-R5 | 7/8" | 1" | \$37.45 |

ΜΙΧ


Inverted Flare Male Swivel



| Item Number | Hose | Tube | Price |
|--------------|--------|-------|---------|
| MIX-05-05-R5 | 5/16" | 5/16" | \$12.46 |
| MIX-05-06-R5 | 5/16" | 3/8" | \$10.72 |
| MIX-07-08-R5 | 13/32" | 1/2" | \$14.14 |

MIX45


Inverted Flare Male Swivel 45°



| Item Number | Hose | Tube | Price |
|----------------|--------|-------|---------|
| MIX45-05-05-R5 | 5/16" | 5/16" | \$12.03 |
| MIX45-05-06-R5 | 5/16" | 3/8" | \$10.66 |
| MIX45-07-08-R5 | 13/32" | 1/2" | \$15.04 |

MIX90

Inverted Flare Male Swivel 90°



| Item Number | Hose | Tube | Price |
|----------------|--------|-------|---------|
| MIX90-03-04-R5 | 3/16" | 1/4" | \$10.97 |
| MIX90-05-05-R5 | 5/16" | 5/16" | \$12.57 |
| MIX90-05-06-R5 | 5/16" | 3/8" | \$12.63 |
| MIX90-07-08-R5 | 13/32" | 1/2" | \$15.04 |

When crimping R5-05 (1/4"), R5-10 (1/2") or R5-12 (5/8") hoses, use Braided Hose Fittings (page 16).

IMPORTANT: For use only with SAE 100R5 General Purpose/Truck Hose.




Beadlock Air Conditioning Hose Fittings

BL-TFS O-Ring Female Swivel

| BL06-06TFS | \$3.77 |
|------------|--------|
| BL08-08TFS | \$4.11 |
| BL10-10TFS | \$4.68 |
| BL12-12TFS | \$6.73 |

BL-TF45


O-Ring Female Swivel 45°



| BL06-06TF45T | \$4.00 |
|--------------|--------|
| BL08-08TF45T | \$4.68 |
| BL10-10TF45T | \$5.63 |
| BL12-12TF45T | \$7.86 |
| | |

BL-TF90

O-Ring Female Swivel 90°



| BL06-06TF90T | \$4.54 |
|--------------|--------|
| BL08-08TF90T | \$4.68 |
| BL10-10TF90T | \$5.63 |
| BL12-12TF90T | \$7.86 |
| | |

BL-RM


Hose Mender/Splicer

|--|--|

| BL06-06RM | \$4.03 |
|-----------|--------|
| BL08-08RM | \$4.48 |
| BL10-10RM | \$4.61 |
| BL12-12RM | \$5.37 |

BL-TMS


O-Ring Male Swivel



| BL06-06TMS | \$4.54 |
|------------|--------|
| BL08-08TMS | \$4.54 |
| BL10-10TMS | \$5.23 |
| BL12-12TMS | \$7.50 |

BL-TM45


O-Ring Male Swivel 45°



| BL06-06TM45T | \$3.72 |
|--------------|--------|
| BL08-08TM45T | \$3.97 |
| BL10-10TM45T | \$4.57 |
| BL12-12TM45T | \$6.78 |

BL-TM90


O-Ring Male Swivel 90°



| BL06-06TM90T | \$4.36 |
|--------------|---------|
| BL08-08TM90T | \$4.57 |
| BL10-10TM90T | \$5.39 |
| BL12-12TM90T | \$15.44 |

BL-MV

Compression Repair Coupling



| \$7.89 |
|---------|
| \$10.69 |
| \$13.76 |
| |

BL-MOR


Insert O-Ring Male



| BL06-06MOR | \$5.02 |
|------------|--------|
| BL08-08MOR | \$5.82 |
| BL10-10MOR | \$6.11 |
| BL12-12MOR | \$7.29 |

BL-MOR45


Insert O-Ring Male 45°



| BL06-06MOR45 | \$5.73 |
|--------------|--------|
| BL08-08MOR45 | \$5.99 |
| BL10-10MOR45 | \$6.63 |
| BL12-12MOR45 | \$7.81 |
| | |

BL-MOR90

Insert O-Ring Male 90°



| BL06-06MOR90 | \$5.73 |
|--------------|---------|
| BL08-08MOR90 | \$6.63 |
| BL10-10MOR90 | \$7.63 |
| BL12-12MOR90 | \$10.13 |

ACF

Beadlock A/C Hose Ferrule



| ACF06 | \$0.67 |
|---------------|--------|
| ACF06-REDUCED | \$0.67 |
| ACF08 | \$0.86 |
| ACF08-REDUCED | \$0.86 |
| ACF10 | \$0.91 |
| ACF10-REDUCED | \$0.91 |
| ACF12 | \$1.16 |
| ACF12-REDUCED | \$1.16 |
| | |

Aluminum crimp fittings for BH Air Conditioning Hose

BL-BR

Braze On for Beadlock System

| \$4.31 | BL06-06BR |
|------------------|------------------------|
| \$4.97 | BL08-08BR |
| \$5.02 | BL10-10BR |
| \$6.07 | BL12-12BR |
| \$4.97 \$5.02 | BL08-08BR BL10-10BR |

Braze On Service Ports

| ACP349 (13 mm) | \$1.93 |
|-------------------|--------|
| | |
| ACP350 (16 mm) | \$1.93 |
| | |
| ACP348 (M10x1.5) | \$1.93 |
| | |
| ACPM12A (M12x1.5) | \$2.51 |
| | |
| ACP351 (3/8-24) | \$1.93 |
| | |

ACP352 (7/16-20) \$2.51

Air Brake Hose Fittings



Sleeve

| B |
|---|
|---|

| ltem # | Hose ID | Price |
|--------|---------|--------|
| 38-300 | 3/8" | \$1.59 |
| 38-301 | 1/2" | \$2.86 |

Nut



| ltem # | Hose ID | Price |
|--------|---------|--------|
| 38-306 | 3/8" | \$2.05 |
| 38-307 | 1/2" | \$2.71 |

Nut

for Spring Guard

| AMA | 7 |
|-------|------------|
| OMP. | La |
| Sum 1 | <i>i</i>) |

| Item # | Hose ID | Price |
|--------|---------|--------|
| 38-312 | 3/8" | \$2.09 |
| 38-313 | 1/2" | \$3.43 |

Nut & Spring Assembly

| | B |
|--|---|
|--|---|

| Item # | Hose ID | Price |
|--------|---------|--------|
| 38-015 | 3/8" | \$3.44 |
| 38-016 | 1/2" | \$6.03 |

Male Connector

Body Only



| ltem # | Hose | Pipe | Price |
|--------|------|------|---------|
| 38-324 | 3/8" | 1/4" | \$2.86 |
| 38-325 | 3/8" | 3/8" | \$2.95 |
| 38-326 | 3/8" | 1/2" | \$3.19 |
| 38-327 | 1/2" | 3/8" | \$10.45 |
| 38-328 | 1/2" | 1/2" | \$5.67 |

Male Connector

| ltem # | Hose | Pipe | Price |
|--------|------|------|---------|
| 38-333 | 3/8" | 1/4" | \$8.15 |
| 38-334 | 3/8" | 3/8" | \$7.60 |
| 38-335 | 3/8" | 1/2" | \$9.37 |
| 38-336 | 1/2" | 3/8" | \$11.38 |
| 38-337 | 1/2" | 1/2" | \$11.69 |

Male Connector

with Spring Guard

| ltem # | Hose | MIP | Price |
|--------|------|------|---------|
| 38-342 | 3/8" | 1/4" | \$9.81 |
| 38-343 | 3/8" | 3/8" | \$9.64 |
| 38-344 | 3/8" | 1/2" | \$10.28 |
| 38-345 | 1/2" | 3/8" | \$12.79 |
| 38-346 | 1/2" | 1/2" | \$13.09 |

Spring

| ltem # | Hose ID | Price |
|--------|---------|--------|
| 38-351 | 3/8" | \$1.07 |
| 38-352 | 1/2" | \$2.19 |

Union



| ltem # | Hose ID | Price |
|--------|---------|---------|
| 38-318 | 3/8" | \$21.28 |
| 38-319 | 1/2" | \$36.77 |

Female Connector



| ltem # | Hose | ABS | Price |
|--------|------|---------|---------|
| 38-357 | 3/8" | 3/4"-20 | \$16.18 |
| 38-358 | 1/2" | 7/8-20 | \$19.35 |

Female Connector

with Adapter



| ltem # | Hose | Pipe | Price |
|--------|------|------|---------|
| 38-363 | 3/8" | 1/4" | \$16.58 |
| 38-364 | 1/2" | 3/8" | \$31.88 |

Adapter



| Item # | ABS | Pipe | Price |
|--------|--------|------|--------|
| 38-369 | 3/4-20 | 1/4" | \$1.98 |
| 38-368 | 3/4-20 | 3/8" | \$1.82 |
| 38-372 | 3/4-20 | 1/2" | \$2.71 |
| 38-370 | 7/8-20 | 3/8" | \$2.35 |
| 38-371 | 7/8-20 | 1/2" | \$5.09 |



SAE 30R7 Fuel Line Hose Barbs

MP NPTF Male Pipe

| <u> </u> | |
|----------|--|
| | |

| ltem # | Hose | Pipe | Price |
|--------|-------|------|---------|
| 38-800 | 3/16" | 1/8" | \$1.50 |
| 38-802 | 1/4" | 1/8" | \$1.03 |
| 32-377 | 1/4" | 1/4" | \$1.32 |
| 38-806 | 5/16" | 1/8" | \$0.90 |
| 38-808 | 5/16" | 1/4" | \$1.82 |
| 38-810 | 3/8" | 1/8" | \$1.49 |
| 32-381 | 3/8" | 1/4" | \$1.75 |
| 32-382 | 3/8" | 3/8" | \$2.99 |
| 32-383 | 1/2" | 3/8" | \$2.17 |
| 32-384 | 1/2" | 1/2" | \$3.15 |
| 32-182 | 5/8" | 3/8" | \$4.66 |
| 32-385 | 5/8" | 1/2" | \$3.23 |
| 32-387 | 3/4" | 1/2" | \$3.34 |
| 32-388 | 3/4" | 3/4" | \$4.59 |
| 32-185 | 1" | 3/4" | \$10.11 |

MP

NPTF Male Pipe 90°



| Hose | Pipe | Price |
|-------|--|---|
| 1/4" | 1/8" | \$2.99 |
| 5/16" | 1/8" | \$2.71 |
| 5/16" | 1/4" | \$31.88 |
| 3/8" | 1/8" | \$3.08 |
| 3/8" | 1/4" | \$2.92 |
| 3/8" | 3/8" | \$6.96 |
| 1/2" | 3/8" | \$9.31 |
| 1/2" | 1/2" | \$12.41 |
| 5/8" | 3/8" | \$8.57 |
| 5/8" | 1/2" | \$10.00 |
| 3/4" | 1/2" | \$11.19 |
| | 1/4" 5/16" 5/16" 3/8" 3/8" 3/8" 1/2" 1/2" 5/8" | 1/4" 1/8" 1/4" 1/8" 5/16" 1/8" 5/16" 1/4" 3/8" 1/4" 3/8" 1/4" 3/8" 1/4" 3/8" 1/2" 1/2" 3/8" 1/2" 1/2" 5/8" 3/8" |

ΜΙΧ

Inverted Flare Male Swivel



| Item # | Hose | Tube | Price |
|--------|-------|-------|--------|
| 38-828 | 5/16" | 1/4" | \$2.25 |
| 38-830 | 5/16" | 5/16" | \$1.48 |
| 38-832 | 5/16" | 3/8" | \$2.95 |
| 38-834 | 3/8" | 5/16" | \$2.71 |
| 38-836 | 3/8" | 3/8" | \$3.86 |

ΜΙΧ

Inverted Flare Male Swivel 90°

| \square | |
|-----------|---|
| 4 | |
| | Ī |

| Item # | Hose | Tube | Price |
|--------|-------|-------|---------|
| 38-873 | 5/16" | 5/16" | \$10.03 |
| 38-874 | 3/8" | 3/8" | \$6.39 |



HT Series ISO 16028 Flush-Face Interchange Quick Couplers



Flushface valve design minimizes fluid loss for a cleaner, safer work environment.

- Automatic push-to-connect couplings provide high flow with low pressure drop.
- Sleeve lock safety feature reduces the possibility of accidental disconnect.
- Steel construction with zinc plating provides optimum corrosion resistance.

Pressure & Flow Ratings

| Body Size | Maximum Working Pressure | Maximum Flow Rate |
|--------------|--------------------------------|----------------------|
| 1/4" | 5,000 psi | 3.2 gpm |
| 3/8" | 5,000 psi | 11 gpm |
| 1/2" | 5,000 psi | 18 gpm |
| 5/8" | 5,000 psi | 21 gpm |
| 3/4" | 5,000 psi | 28 gpm |
| 1" | 5,000 psi | 50 gpm |

| Interchanges | with: |
|--------------|-------|
|--------------|-------|

- Parker FEM Series (1/2", 5/8" and 3/4")
- Parker FF Series (3/8" only)
- Faster FF Series
- Holmbury Series A

ISO 16028 Female Couplers



| Item # Body | Thread Size | Price |
|-------------|---------------|----------|
| 2HTF2 1/4" | 1/4-18 NPTF | \$35.77 |
| 3HTF3 3/8" | 3/8-18 NPTF | \$42.41 |
| 3HTF4 3/8" | 1/2-14 NPTF | \$42.41 |
| 3HTOF3 3/8" | 9/16-18 SAE | \$84.08 |
| 3HTOF4 3/8" | 3/4-16 SAE | \$88.73 |
| 4HTF4 1/2" | 1/2-14 NPTF | \$43.66 |
| 4HTF6 1/2" | 3/4-14 NPTF | \$52.84 |
| 4HTOF4 1/2" | 3/4-16 SAE | \$90.72 |
| 4HTOF5 1/2" | 7/8-14 SAE | \$94.56 |
| 4HTOF6 1/2" | 1 1/16-12 SAE | \$99.55 |
| 5HTF6 5/8" | 3/4-14 NPTF | \$65.78 |
| 5HTOF5 5/8" | 7/8-14 SAE | \$130.12 |
| 5HTOF6 5/8" | 1 1/16-12 SAE | \$130.12 |
| 6HTF6 3/4" | 3/4-14 NPTF | \$89.93 |
| 6HTOF6 3/4" | 1 1/16-12 SAE | \$174.89 |
| 8HTF8 1" | 1-111/2 NPTF | \$152.97 |
| 8HTOF8 1" | 1 5/16-12 SAE | \$293.27 |

ISO 16028 Male Plug/Nipples



| Item # | Body | Thread Size | Price |
|--------|------|---------------|----------|
| HT2F2 | 1/4" | 1/4-18 NPTF | \$13.13 |
| HT3F3 | 3/8" | 3/8-18 NPTF | \$15.65 |
| HT3F4 | 3/8" | 1/2-14 NPTF | \$15.65 |
| HT3OF3 | 3/8" | 9/16-18 SAE | \$29.47 |
| HT3OF4 | 3/8" | 3/4-16 SAE | \$29.84 |
| HT4F4 | 1/2" | 1/2-14 NPTF | \$25.69 |
| HT4F6 | 1/2" | 3/4-14 NPTF | \$29.42 |
| HT4OF4 | 1/2" | 3/4-16 SAE | \$56.04 |
| HT4OF5 | 1/2" | 7/8-14 SAE | \$56.04 |
| HT4OF6 | 1/2" | 1 1/16-12 SAE | \$56.36 |
| HT5F6 | 5/8" | 3/4-14 NPTF | \$33.30 |
| HT5OF5 | 5/8" | 7/8-14 SAE | \$69.22 |
| HT5OF6 | 5/8" | 1 1/16-12 SAE | \$69.22 |
| HT6F6 | 3/4" | 3/4-14 NPTF | \$58.20 |
| HT6OF6 | 3/4" | 1 1/16-12 SAE | \$113.83 |
| HT8F8 | 1" | 1-111/2 NPTF | \$83.04 |
| HT8OF8 | 1" | 1 5/16-12 SAE | \$168.26 |

ISO 16028 Matched Sets/Pairs

Includes 1 female and 1 male.



| Item # | Thread Size | Price |
|-------------|-------------|----------|
| 2HTF2-HT2F2 | 1/4-18 NPTF | \$46.45 |
| 3HTF3-HT3F3 | 3/8-18 NPTF | \$55.16 |
| 4HTF4-HT4F4 | 1/2-14 NPTF | \$52.45 |
| 5HTF6-HT5F6 | 3/4-14 NPTF | \$90.72 |
| 6HTF6-HT6F6 | 3/4-14 NPTF | \$89.93 |
| 8HTF8-HT8F8 | 1-11½ NPTF | \$152.97 |

Connect-Under-Pressure Couplers

Flush-face, no-drip couplers connect by hand under pressure without releasing any fluid into the environment. Fully compatible with all standard ISO 16028 couplers.



Male coupler will connect under pressure up to 3571 psi, and female coupler will connect under pressure up to 1595 psi. Mating coupler must be without residual pressure.

| ltem # | Description | Price |
|-----------|-----------------------|---------|
| 805201005 | 1/2" Male Plug/Nipple | \$53.19 |
| 806801000 | 1/2" Female Coupler | \$68.85 |

Elastomer Dust Plugs & Caps

Caps (for female couplers) and plugs (for male plugs/nipples) are compatible with all ISO 16028 quick disconnect couplers.



| ltem # | Description | Price |
|--------------|----------------|--------|
| 3HTDP | 3/8" Dust Plug | \$2.50 |
| 4HTDP | 1/2" Dust Plug | \$3.33 |
| 5HTDP | 5/8" Dust Plug | \$4.04 |
| 6HTDP | 3/4" Dust Plug | \$4.20 |
| 8HTDP | 1" Dust Plug | \$4.80 |
| HT3DC | 3/8" Dust Cap | \$2.50 |
| HT4DC | 1/2" Dust Cap | \$3.33 |
| HT5DC | 5/8" Dust Cap | \$4.04 |
| HT6DC | 3/4" Dust Cap | \$4.20 |
| HT8DC | 1" Dust Cap | \$4.80 |



ISO 5675 Female Couplers



| ltem # | Body | Thread Size | Price |
|--------|------|--------------|---------|
| 2AGF2 | 1/4" | 1/4-18 NPTF | \$10.22 |
| 3AGF3 | 3/8" | 3/8-18 NPTF | \$12.15 |
| 4AGF4 | 1/2" | 1/2-14 NPTF | \$12.39 |
| 4AGF6 | 1/2" | 3/4-14 NPTF | \$16.58 |
| 4AGOF4 | 1/2" | 3/4-16 SAE | \$14.85 |
| 4AGOF5 | 1/2" | 7/8-14 SAE | \$14.85 |
| 6AGF6 | 3/4" | 3/4-14 NPTF | \$31.13 |
| 8AGF8 | 3/4" | 1-111/2 NPTF | \$46.86 |

ISO 5675 Male Plug/Nipples



| ltem # | Body | Thread Size | Price |
|--------|------|--------------|---------|
| AG2F2 | 1/4" | 1/4-18 NPTF | \$5.06 |
| AG3F3 | 3/8" | 3/8-18 NPTF | \$5.49 |
| AG4F4 | 1/2" | 1/2-14 NPTF | \$5.45 |
| AG4F6 | 1/2" | 3/4-14 NPTF | \$7.37 |
| AG4OF4 | 1/2" | 3/4-16 SAE | \$6.74 |
| AG4OF5 | 1/2" | 7/8-14 SAE | \$6.74 |
| AG6F6 | 3/4" | 3/4-14 NPTF | \$16.00 |
| AG8F8 | 3/4" | 1-111/2 NPTF | \$21.49 |

ISO 5675 Matched Sets/Pairs

Buy a set and save. Each pair includes 1 female coupler and 1 male plug/nipple.



| Item # | Thread Size | Price |
|-------------|--------------|---------|
| 2AGF2-AG2F2 | 1/4-18 NPTF | \$12.54 |
| 3AGF3-AG3F3 | 3/8-18 NPTF | \$14.45 |
| 4AGF4-AG4F4 | 1/2-14 NPTF | \$16.31 |
| 6AGF6-AG6F6 | 3/4-14 NPTF | \$42.88 |
| 8AGF8-AG8F8 | 1-111/2 NPTF | \$62.20 |

Elastomer Dust Plugs & Caps

Caps (for female couplers) and plugs (for male plugs/nipples) are compatible with all ISO 5675 quick disconnect couplers.



| ltem # | Description | Price |
|--------|----------------|---------|
| 2AGDP | 1/4" Dust Plug | \$3.48 |
| 3AGDP | 3/8" Dust Plug | \$7.57 |
| 4AGDP | 1/2" Dust Plug | \$3.85 |
| 6AGDP | 3/4" Dust Plug | \$9.79 |
| 8AGDP | 1" Dust Plug | \$13.06 |
| AG2DC | 1/4" Dust Cap | \$3.57 |
| AG3DC | 3/8" Dust Cap | \$6.74 |
| AG4DC | 1/2" Dust Cap | \$3.91 |
| AG6DC | 3/4" Dust Cap | \$14.89 |
| AG8DC | 1" Dust Cap | \$16.67 |
| | | |

AG Series

ISO 5675 Agricultural Hydraulic Quick Couplers



Recommended for use with construction equipment, farm implements, and most other mobile equipment. Features Buna seals, double shut-off, and proven ball-lock mechanism for positive connection.

Pressure & Flow Ratings

| Body Size | Maximum Working Pressure | Maximum Flow Rate |
|--------------|--------------------------------|----------------------|
| 1/4" | 5,075 psi | 3.2 gpm |
| 3/8" | 4,350 psi | 7 gpm |
| 1/2" | 4,350 psi | 12 gpm |
| 3/4" | 3,625 psi | 20 gpm |
| 1" | 3,190 psi | 40 gpm |

Interchanges with:

- Parker 4000 Series
- Safeway Series 'S20'
- Faster 'NS'
- Tomco Series 'PC'
- ISO 7241-1 Series A (1/2" only)



600 Series

ISO 7241-1 Series A Hydraulic Quick Disconnect Couplers



Recommended for general purpose, mobile hydraulics, machine tool, plastic molding and test equipment applications. Features Buna seals, double shut-off, and proven balllock mechanism for positive connection.

Pressure & Flow Ratings

| Body Size | Maximum Working Pressure | Maximum Flow Rate |
|--------------|--------------------------------|----------------------|
| 1/4" | 5,000 psi | 3 gpm |
| 3/8" | 4,000 psi | 6 gpm |
| 1/2" | 4,000 psi | 12 gpm |
| 3/4" | 2,500 psi | 28 gpm |
| 1" | 2,000 psi | 50 gpm |

Interchanges with:

- Parker 6600 Series
- Snap-Tite 61 Series'
- Aeroquip 5600 (FD56)
- ISO 5675 (1/2" size only)

ISO 7241-1 Series A Female Couplers



| ltem # | Body | Thread Size | Price |
|------------|------|-------------|---------|
| 601-04-04S | 1/4" | 1/4" NPTF | \$11.88 |
| 601-06-06S | 3/8" | 3/8" NPTF | \$13.01 |
| 601-08-08S | 1/2" | 1/2" NPTF | \$13.04 |
| 601-12-12S | 3/4" | 3/4" NPTF | \$31.91 |
| 601-16-16S | 1" | 1" NPTF | \$42.96 |

ISO 7241-1 Series A Male Plug/Nipples



| ltem # | Body | Thread Size | Price |
|------------|------|-------------|---------|
| 602-04-04S | 1/4" | 1/4" NPTF | \$5.27 |
| 602-06-06S | 3/8" | 3/8" NPTF | \$7.79 |
| 602-08-08S | 1/2" | 1/2" NPTF | \$8.82 |
| 602-12-12S | 3/4" | 3/4" NPTF | \$14.06 |
| 602-16-16S | 1" | 1" NPTF | \$18.64 |

ISO 7241-1 Series A Matched Sets/Pairs

Buy a set and save. Each pair includes 1 female coupler and 1 male plug/nipple.



| ltem # | Body | Thread Size | Price |
|------------|------|-------------|---------|
| 600-04-04S | 1/4" | 1/4" NPTF | \$16.31 |
| 600-06-06S | 3/8" | 3/8" NPTF | \$19.78 |
| 600-08-08S | 1/2" | 1/2" NPTF | \$20.77 |
| 600-12-12S | 3/4" | 3/4" NPTF | \$43.67 |
| 600-16-16S | 1" | 1" NPTF | \$58.51 |

Elastomer Dust Plugs & Caps

Caps (for female couplers) and plugs (for male plugs/nipples) are compatible with all ISO 7241-1 Series A quick disconnect couplers.



| ltem # | Description | Price |
|---------|----------------|--------|
| 601-04P | 1/4" Dust Plug | \$1.25 |
| 601-06P | 3/8" Dust Plug | \$1.25 |
| 601-08P | 1/2" Dust Plug | \$1.35 |
| 601-12P | 3/4" Dust Plug | \$3.31 |
| 601-16P | 1" Dust Plug | \$3.99 |
| 602-04C | 1/4" Dust Cap | \$1.25 |
| 602-06C | 3/8" Dust Cap | \$1.25 |
| 602-08C | 1/2" Dust Cap | \$1.35 |
| 602-12C | 3/4" Dust Cap | \$3.31 |
| 602-16C | 1" Dust Cap | \$3.99 |



ISO 7241-1 Series B Female Couplers



| Body | Thread Size | Price |
|------|------------------------------|---|
| 1/4" | 1/4" NPTF | \$9.20 |
| 3/8" | 3/8" NPTF | \$13.81 |
| 1/2" | 1/2" NPTF | \$15.82 |
| 3/4" | 3/4" NPTF | \$25.00 |
| 1" | 1" NPTF | \$33.63 |
| | 1/4" 3/8" 1/2" 3/4" | 1/4" 1/4" NPTF 3/8" 3/8" NPTF 1/2" 1/2" NPTF 3/4" 3/4" NPTF |

Brass

Steel

| Item # | Body | Thread Size | Price |
|------------|------|-------------|---------|
| 701-04-04B | 1/4" | 1/4" NPTF | \$10.87 |
| 701-06-06B | 3/8" | 3/8" NPTF | \$15.70 |
| 701-08-08B | 1/2" | 1/2" NPTF | \$24.55 |
| 701-12-12B | 3/4" | 3/4" NPTF | \$41.06 |
| 701-16-16B | 1" | 1" NPTF | \$56.60 |

ISO 7241-1 Series B Male Plug/Nipples



Steel

| ltem # | Body | Thread Size | Price |
|------------|------|-------------|---------|
| 702-04-04S | 1/4" | 1/4" NPTF | \$4.49 |
| 702-06-06S | 3/8" | 3/8" NPTF | \$7.00 |
| 702-08-08S | 1/2" | 1/2" NPTF | \$7.65 |
| 702-12-125 | 3/4" | 3/4" NPTF | \$11.66 |
| 702-16-16S | 1" | 1" NPTF | \$16.34 |

Brass

| ltem # | Body | Thread Size | Price |
|------------|------|-------------|---------|
| 702-04-04B | 1/4" | 1/4" NPTF | \$5.49 |
| 702-06-06B | 3/8" | 3/8" NPTF | \$7.29 |
| 702-08-08B | 1/2" | 1/2" NPTF | \$9.26 |
| 702-12-12B | 3/4" | 3/4" NPTF | \$15.30 |
| 702-16-16B | 1" | 1" NPTF | \$17.09 |

ISO 7241-1 Series B Matched Sets/Pairs

Buy a set and save. Each pair includes 1 female coupler and 1 male plug/nipple.



| Steel | | | |
|---|---------------------|---------------------------------|-------------------------|
| ltem # | Body | Thread Size | Price |
| 700-04-04S | 1/4" | 1/4" NPTF | \$13.00 |
| 700-06-06S | 3/8" | 3/8" NPTF | \$19.78 |
| 700-08-08S | 1/2" | 1/2" NPTF | \$22.32 |
| 700-12-12S | 3/4" | 3/4" NPTF | \$34.83 |
| 700-16-16S | 1" | 1" NPTF | \$47.48 |
| | | | |
| Brass | | | |
| Brass Item # | Body | Thread Size | Price |
| 2.455 | Body 1/4" | Thread Size 1/4" NPTF | Price \$15.54 |
| Item # | | | |
| Item # 700-04-04B | 1/4" | 1/4" NPTF | \$15.54 |
| Item # 700-04-04B 700-06-06B | 1/4" 3/8" | 1/4" NPTF 3/8" NPTF | \$15.54 \$21.84 |

Elastomer Dust Plugs & Caps

Caps (for female couplers) and plugs (for male plugs/nipples) are compatible with all ISO 7241-1 Series B quick disconnect couplers.



| ltem # | Description | Price |
|---------|----------------|--------|
| 701-04P | 1/4" Dust Plug | \$1.14 |
| 701-06P | 3/8" Dust Plug | \$1.14 |
| 701-08P | 1/2" Dust Plug | \$1.24 |
| 701-12P | 3/4" Dust Plug | \$3.03 |
| 701-16P | 1" Dust Plug | \$3.66 |
| 702-04C | 1/4" Dust Cap | \$1.14 |
| 702-06C | 3/8" Dust Cap | \$1.14 |
| 702-08C | 1/2" Dust Cap | \$1.24 |
| 702-12C | 3/4" Dust Cap | \$3.03 |
| 702-16C | 1" Dust Cap | \$3.66 |

700 Series

ISO 7241-1 Series B Hydraulic Quick Disconnect Couplers



Recommended for general purpose, mobile hydraulics, machine tool, plastic molding and test equipment applications. Features Buna seals, double shut-off, and proven balllock mechanism for positive connection.

Pressure & Flow Ratings

| Body Size | Maximum Working Pressure (Steel) | Maximum Working Pressure (Brass) |
|--------------|---|---|
| 1/4" | 5,000 psi | 1,000 psi |
| 3/8" | 4,000 psi | 1,000 psi |
| 1/2" | 4,000 psi | 1,000 psi |
| 3/4" | 2,500 psi | 1,500 psi |
| 1" | 2,000 psi | 1,000 psi |

Interchanges with:

- Parker 60 Series
- Snap-Tite 72 Series
- Aeroquip FD45 Series



4100 Series

Wet Line Coupling



Interchanges with:

- Parker 6100 SeriesSnap-Tite 78 Series
- Aeroquip 5100 Series

Designed for most industrial fluid applications, this coupling is ideal for oil well equipment, sand and salt spreaders, dump and demolition trailers, live bed trailers and other heavy duty applications.

- Connect and disconnect under pressure
- Brass body with steel valving components
- Heavy-duty steel wing nut
- Buna seals

| Body Size | Recommended Operating Pressure (psi) | Flow Rate (gpm) |
|-----------|--|--------------------|
| 1/4" | 3,000 | 4 |
| 3/8" | 3,000 | 7 |
| 1/2" | 3,000 | 7 |
| 5/8" | 3,000 | 18 |
| 3/4" | 3,000 | 18 |
| 1" | 3,000 | 40 |
| 1¼" | 2,750* | 75 |
| 1½" | 2,500** | 100 |

Nipple holds max. 2,500 psi when disconnected
 Nipple holds max. 2,000 psi when disconnected

Female Couplers

| ltem # | Description | Thread | Material | Price |
|-------------|--------------|-------------------|----------|----------|
| 4100-S5-04B | 1/4" Coupler | 1/8" NPT (female) | Brass | \$71.72 |
| 4100-S5-06B | 3/8" Coupler | 1/4" NPT (female) | Brass | \$96.92 |
| 4100-S5-08B | 1/2" Coupler | 3/8" NPT (female) | Brass | \$97.46 |
| 4100-S5-10B | 5/8" Coupler | 1/2" NPT (female) | Brass | \$53.46 |
| 4100-S5-12B | 3/4" Coupler | 3/4" NPT (female) | Brass | \$53.46 |
| 4100-S5-16B | 1" Coupler | 1" NPT (female) | Brass | \$63.74 |
| 4100-S5-20B | 1¼" Coupler | 1¼" NPT (female) | Brass | \$115.42 |
| 4100-S5-24B | 1½" Coupler | 1½" NPT (female) | Brass | \$150.44 |

Male Nipples

| Item # | Description | Thread | Material | Price |
|-------------|-------------|-------------------|----------|----------|
| 4100-S2-04B | 1/4" Nipple | 1/8" NPT (female) | Brass | \$55.26 |
| 4100-S2-06B | 3/8" Nipple | 1/4" NPT (female) | Brass | \$54.83 |
| 4100-S2-08B | 1/2" Nipple | 3/8" NPT (female) | Brass | \$52.50 |
| 4100-S2-10B | 5/8" Nipple | 1/2" NPT (female) | Brass | \$35.16 |
| 4100-S2-12B | 3/4" Nipple | 3/4" NPT (female) | Brass | \$41.87 |
| 4100-S2-16B | 1" Nipple | 1" NPT (female) | Brass | \$41.60 |
| 4100-S2-20B | 1¼" Nipple | 1¼" NPT (female) | Brass | \$97.89 |
| 4100-S2-24B | 1½" Nipple | 1½" NPT (female) | Brass | \$146.24 |

Dust Caps and Plugs

| ltem # | Description | Price |
|-------------|----------------------------|---------|
| 4100-S5-06P | Dust Plug for 3/8" Coupler | \$11.99 |
| 4100-S2-06C | Dust Cap for 3/8" Nipple | \$11.99 |
| 4100-S5-08P | Dust Plug for 1/2" Coupler | \$11.99 |
| 4100-S2-08C | Dust Cap for 1/2" Nipple | \$11.99 |
| 4100-S5-10P | Dust Plug for 5/8" Coupler | \$11.99 |
| 4100-S2-10C | Dust Cap for 5/8" Nipple | \$11.99 |
| 4100-S5-12P | Dust Plug for 3/4" Coupler | \$12.62 |
| 4100-S2-12C | Dust Cap for 3/4" Nipple | \$12.62 |
| 4100-S5-16P | Dust Plug for 1" Coupler | \$13.91 |
| 4100-S2-16C | Dust Cap for 1" Nipple | \$13.91 |
| 4100-S5-20P | Dust Plug for 1¼" Coupler | \$18.85 |
| 4100-S2-20C | Dust Cap for 1¼" Nipple | \$18.85 |
| 4100-S5-24P | Dust Plug for 1½" Coupler | \$34.98 |
| 4100-S2-24C | Dust Cap for 1½" Nipple | \$34.98 |









10,000 psi Hydraulic Pumps

Portable hydraulic pumps designed to meet the demanding requirements of industrial, construction and automotive applications. Built with features required for long life and trouble free operation.

- Rugged aluminum construction
- Internal pressure relief valve
- Air exhaust muffler for guiet operation (VAP-10-100 only)
- Filters on both the air and oil inlet (VAP-10-100 only)
- · Locking foot pedal release valve and built-in safety valve to protect against overloading (VAP-10-100 only)
- Two-speed operation (VHP-10-25 and VHP-10-43 only)
- Convenient carrying handle and ergometric handle grip (VHP-10-25 and VHP-10-43 only)

| VAP-10-100 | 10,000 psi Air/Hydraulic | 101 in ³ (1650 cc) | \$453.15 |
|------------|-----------------------------|-------------------------------|----------|
| VHP-10-25 | 10,000 psi Two-Speed Manual | 25 in ³ (410 cc) | \$259.73 |
| VHP-10-43 | 10,000 psi Two-Speed Manual | 43 in ³ (705 cc) | \$270.78 |



3/8" Couplers \$30.84 per set

Item number 3TM3-T3F3 includes one male coupler and one female coupler.

T-Series couplers interchange with Enerpac C-604 (3/8" only), Parker 3000 Series, Stucchi IVHP Series, and Holmbury HPA Series.

Screw-Together, High Presure Quick Disconnects

Threaded sleeve allows connection and disconnection while coupler and/or nipple are under pressure. Urethane seal resists extrusion under high pressure during connection and disconnection.

| Item # | Coupler | Thread | Material | Price |
|---------|-------------|------------------|---------------|----------|
| 2TM2 | 1/4" Female | 1/4" Male NPTF | Steel | \$18.65 |
| 3TF3 | 3/8" Female | 3/8" Female NPTF | Steel | \$20.58 |
| 3TM3 | 3/8" Female | 3/8" Male NPTF | Steel | \$20.58 |
| 3TM3-SS | 3/8" Female | 3/8" Male NPTF | 316 Stainless | \$120.84 |
| T2F2 | 1/4" Male | 1/4" Female NPTF | Steel | \$11.19 |
| T3F3 | 3/8" Male | 3/8" Female NPTF | Steel | \$11.78 |
| T3F3-SS | 3/8" Male | 3/8" Female NPTF | 316 Stainless | \$66.81 |

| Coupler Size | Max. Working Pressure | Maximum Flow Rate |
|--------------|-----------------------|-------------------|
| 1/4" | 10,000 psi | 3 gpm |
| 3/8" | 10,000 psi | 6 gpm |

Steel Grease Fittings



Pipe Thread with Ball Check



36-110

1/8-27 NPT Overall length (A): 0.68" Insert length (B): 0.29" Hex size: 0.43"

36-111

\$0.84

\$1.08

\$1.75

\$0.62

Thread Forming Overall length (A): 0.62" Insert length (B): 0.23" Hex size: 0.43"



36-130

1/4-18 NPT Overall length (A): 0.87" Insert length (B): 0.42" Hex size: 0.56"

Pipe Thread Long with Ball Check



36-112

1/8-27 NPT Overall length (A): 1.25" Insert length (B): 0.78" Hex size: 0.43"





36-113 \$1.92

1/8-27 NPT Overall length (A): 1.75" Insert length (B): 1.26" Hex size: 0.43"


Pipe Thread 30° with Ball Check



36-114 1/8-27 NPT


Overall length (A): 0.90" Insert length (B): 0.29" Hex size: 0.43"

Pipe Thread 45° with Ball Check



36-116 1/8-27 NPT

Overall length (A): 0.89" Insert length (B): 0.29" Hex size: 0.43"



Overall length (A): 0.84"

Insert length (B): 0.29"

Pipe Thread 65°

Overall length (A): 0.84"

Insert length (B): 0.29"

with Ball Check

36-118

36-132

\$1.03

\$1.12

1/4-18 NPT

Overall length (A): 0.96"

Pipe Thread 90°

with Ball Check

36-120

1/8-27 NPT

Insert length (B): 0.34" Hex size: 0.56"

1/8-27 NPT

Hex size: 0.43"

36-121

1/8-27 NPT Overall length (A): 1.81" Insert length (B): 1.25" Hex size: 0.43"

1/4-28 Taper

Short with Ball Check



36-140

\$1.02

\$1.55

\$1.00

\$3.19

\$0.36

\$0.38

\$0.45

\$0.68

1/4-28 Taper Thread Overall length (A): 0.54" Insert length (B): 0.18" Hex size: 0.31"

36-141

Thread Forming Overall length (A): 0.57" Insert length (B): 0.18" Hex size: 0.31"

1/4-28 Taper

Long with Ball Check



36-142


1/4-28 Taper Thread Overall length (A): 0.90" Insert length (B): 0.29" Hex size: 0.43"

1/4-28 Taper

Extra Long with Ball Check



Thread Forming Overall length (A): 0.96" Insert length (B): 0.62" Hex size: 0.31"



Zinc-plated steel. All fittings meet SAE J-534C specifications.



Page 56



Steel Grease Fittings

1/4-28 Taper 45° Short with Ball Check




36-146

1/4-28 Taper Thread Overall length (A): 0.81" Insert length (B): 0.20" Hex size: 0.37"

\$0.89

\$1.25


1/4-28 Taper 45° Long with Ball Check



36-148

1/4-28 Taper Thread Overall length (A): 0.90" Insert length (B): 0.29" Hex size: 0.37"

1/4-28 Taper 65° Short with Ball Check



1/4-28 Taper Thread Overall length (A): 0.78" Insert length (B): 0.20" Hex size: 0.37"

1/4-28 Taper 90°



36-150 \$0.76

1/4-28 Taper Thread Overall length (A): 0.75" Insert length (B): 0.20" Hex size: 0.37"


36-152 \$1.44

Thread Forming Overall length (A): 0.75" Insert length (B): 0.20" Hex size: 0.37" Drive Type with Ball Check



36-160 \$0.50 5/16" Drive Overall length (A): 0.54" Insert length (B): 0.25"

Drive Type with Ball Check



36-164 \$0.50

3/16" Drive Overall length (A): 0.51" Insert length (B): 0.25"

Drive Type

with Ball Check



36-166

\$0.42

1/4" Drive Overall length (A): 0.55" Insert length (B): 0.23"

Button Head



\$2.47

1/8-27 NPTF thread Overall length (A): 0.75" Insert length (B): 0.34" Hex size: 0.62"

36-205

36-200

\$2.63

1/4-18 NPTF thread Overall length (A): 0.82" Insert length (B): 0.42" Hex size: 0.62"

Zinc-plated steel. All fittings meet SAE J-534C specifications.


Rubber Whip Hose



3/16" I.D. hose with 1/8" NPT male pipe fittings

| 36-210 | 12" long | \$21.88 |
|--------|----------|---------|
| 36-212 | 18" long | \$15.27 |
| 36-214 | 24" long | \$18.67 |
| 36-216 | 36" long | \$21.36 |

Grease Gun Coupler



36-220 \$6.95 Overall length (A): 1.50"

Hex size: 0.56"

Steel Grease Fittings



5/16"-24



36-186

\$0.65

\$1.10

5/16-24 thread Overall length (A): 0.65" Insert length (B): 0.25" Hex size: 0.37"

3/8"-24



36-188

3/8-24 thread Overall length (A): 0.65" Insert length (B): 0.25" Hex size: 0.43"

Metric



36-168 \$0.65

6 mm x 1 metric thread Overall length (A): 16 mm Insert length (B): 6 mm Hex size: 7 mm


36-174 \$0.56

8 mm x 1 metric thread Overall length (A): 17 mm Insert length (B): 6 mm Hex size: 9 mm

36-180

\$0.83

10 mm x 1 metric thread Overall length (A): 18 mm Insert length (B): 6 mm Hex size: 11 mm



36-170 \$0.88

6 mm x 1 metric thread Overall length (A): 21 mm Insert length (B): 5.5 mm Hex size: 9 mm

36-176 \$0.92

8 mm x 1 metric thread Overall length (A): 17 mm Insert length (B): 5.5 mm Hex size: 9 mm

36-182 \$1.22

10 mm x 1 metric thread Overall length (A): 21 mm Insert length (B): 5.5 mm Hex size: 11 mm

Metric 90°



\$0.92

\$1.08

6 mm x 1 metric thread Overall length (A): 18 mm Insert length (B): 5.5 mm Hex size: 9 mm

36-178 \$0.96

8 mm x 1 metric thread Overall length (A): 18 mm Insert length (B): 5.5 mm Hex size: 9 mm

36-184

10 mm x 1 metric thread Overall length (A): 18 mm Insert length (B): 5.5 mm Hex size: 11 mm

Zinc-plated steel. All fittings meet SAE J-534C specifications.



Cam & Groove

Specifications

Our alumunium and brass cam and groove fittings are designed to interchange with all product manufactured to Mil-C-27487F.

No standard exists for 1/2" and 8" fittings, and generally these sizes do not interchange with other manufacturers.

| Body Size | Max. Working Pressure (Aluminum and Brass) | Max. Working Pressure (Polyproylene) |
|--------------|---|--|
| 1/2" | 150 psi | 125 psi |
| 3/4" | 250 psi | 125 psi |
| 1" | 250 psi | 125 psi |
| 1¼" | 250 psi | 100 psi |
| 1½" | 250 psi | 100 psi |
| 2" | 250 psi | 100 psi |
| 21⁄2" | 150 psi | 100 psi |
| 3" | 125 psi | 70 psi |
| 4" | 100 psi | ? |
| 5" | 75 psi | n/a |
| 6" | 75 psi | n/a |
| 8" | ? | n/a |

Pressure ratings with standard seals at 70° F.

Polypropylene cam and groove should not be used with aluminum fittings.

Aluminum and brass couplings ship with Buna-N gaskets.

Polypropylene couplings ship with EPDM gaskets. Polyproylene is not recommended for use with PTFE gaskets.





Aluminum


| Body | NPT | ltem # | Price |
|-------|-------|-----------|----------|
| 1/2" | 1/2" | 50-A-AL | \$6.44 |
| 3/4" | 1/2" | 7550-A-AL | \$8.18 |
| 3/4" | 3/4" | 75-A-AL | \$6.80 |
| 1" | 1" | 100-A-AL | \$8.07 |
| 11⁄4" | 11⁄4" | 125-A-AL | \$10.42 |
| 11⁄2" | 11⁄2" | 150-A-AL | \$10.47 |
| 2" | 2" | 200-A-AL | \$12.21 |
| 21⁄2" | 21⁄2" | 250-A-AL | \$18.86 |
| 3" | 3" | 300-A-AL | \$21.76 |
| 4" | 4" | 400-A-AL | \$49.29 |
| 5" | 5" | 500-A-AL | \$83.21 |
| 6" | 6" | 600-A-AL | \$98.52 |
| 8" | 8" | 800-A-AL | \$270.83 |
| Brass | | | |
| Body | NPT | ltem # | Price |

| воау | NPI | item # | Price |
|---------|--------|-----------|----------|
| 1/2" | 1/2" | 50-A-BR | \$12.72 |
| 3/4" | 1/2" | 7550-A-BR | \$21.48 |
| 3/4" | 3/4" | 75-A-BR | \$13.99 |
| 1" | 1" | 100-A-BR | \$15.24 |
| 11⁄4" | 11⁄4" | 125-A-BR | \$26.19 |
| 11⁄2" | 11⁄2" | 150-A-BR | \$27.02 |
| 2" | 2" | 200-A-BR | \$34.61 |
| 21⁄2" | 21⁄2" | 250-A-BR | \$64.14 |
| 3" | 3" | 300-A-BR | \$62.80 |
| 4" | 4" | 400-A-BR | \$137.83 |
| 5" | 5" | 500-A-BR | \$232.69 |
| 6" | 6" | 600-A-BR | \$320.30 |
| Polypro | pylene | | |

| NPT | ltem # | Price |
|------|---------------------------------------|---|
| 1/2" | PPA50 | \$4.85 |
| 3/4" | PPA75 | \$4.85 |
| 1" | PPA100 | \$6.02 |
| 1¼" | PPA125 | \$5.52 |
| 1½" | PPA150 | \$6.08 |
| 2" | PPA200 | \$7.15 |
| 3" | PPA300 | \$16.09 |
| 4" | PPA400 | \$26.46 |
| | 1/2" 3/4" 1" 1½" 2" 3" | 1/2" PPA50 3/4" PPA75 1" PPA100 1¼" PPA125 1½" PPA150 2" PPA200 3" PPA300 |

Type B Female Coupler x Male NPTF





Aluminum

| Body | NPT | ltem # | Price |
|-------|-------|----------|----------|
| 1/2" | 1/2" | 50-B-AL | \$16.96 |
| 3/4" | 3/4" | 75-B-AL | \$16.96 |
| 1" | 1" | 100-B-AL | \$18.19 |
| 11⁄2" | 11⁄2" | 150-B-AL | \$20.84 |
| 2" | 2" | 200-B-AL | \$25.28 |
| 3" | 3" | 300-B-AL | \$41.17 |
| 4" | 4" | 400-B-AL | \$63.03 |
| 5" | 5" | 500-B-AL | \$103.03 |
| 6" | 6" | 600-B-AL | \$145.47 |
| 8" | 8" | 800-B-AL | \$799.50 |
| Brass | | | |

| Body | NPT | ltem # | Price |
|-------|-------|----------|----------|
| 1/2" | 1/2" | 50-B-BR | \$30.28 |
| 3/4" | 3/4" | 75-B-BR | \$37.17 |
| 1" | 1" | 100-B-BR | \$40.49 |
| 11⁄2" | 11⁄2" | 150-B-BR | \$55.68 |
| 2" | 2" | 200-B-BR | \$66.68 |
| 3" | 3" | 300-B-BR | \$119.75 |
| 4" | 4" | 400-B-BR | \$175.36 |

Polypropylene

| Body | NPT | ltem # | Price |
|-------|-------|--------|---------|
| 3/4" | 1/2" | PPB50 | \$12.21 |
| 3/4" | 3/4" | PPB75 | \$12.21 |
| 1" | 1" | PPB100 | \$13.89 |
| 11⁄2" | 11⁄4" | PPB125 | \$16.30 |
| 11⁄2" | 11⁄2" | PPB150 | \$16.09 |
| 2" | 2" | PPB200 | \$19.82 |
| 3" | 3" | PPB300 | \$33.36 |
| 4" | 4" | PPB400 | \$67.01 |

SAFETY NOTICE: Cam and groove couplings should *never* be used for compressed air or steam service.


ter x remaie NPTF

Cam & Groove



Type C

Female Coupler x Hose Shank



Aluminum

4"


4"

| Body | Hose | ltem # | Price |
|---------|--------|----------|----------|
| 1/2" | 1/2" | 50-C-AL | \$14.30 |
| 3/4" | 3/4" | 75-C-AL | \$16.24 |
| 1" | 1" | 100-C-AL | \$16.86 |
| 11⁄2" | 11⁄2" | 150-C-AL | \$20.90 |
| 2" | 2" | 200-C-AL | \$24.00 |
| 3" | 3" | 300-C-AL | \$38.26 |
| 4" | 4" | 400-C-AL | \$56.95 |
| 5" | 5" | 500-C-AL | \$97.36 |
| 6" | 6" | 600-C-AL | \$143.73 |
| 8" | 8" | 800-C-AL | \$596.19 |
| Brass | | | |
| Body | Hose | ltem # | Price |
| 1/2" | 1/2" | 50-C-BR | \$35.27 |
| 3/4" | 3/4" | 75-C-BR | \$37.17 |
| 1" | 1" | 100-C-BR | \$41.37 |
| 11⁄2" | 11⁄2" | 150-C-BR | \$56.05 |
| 2" | 2" | 200-C-BR | \$67.46 |
| 3" | 3" | 300-C-BR | \$115.50 |
| 4" | 4" | 400-C-BR | \$176.22 |
| 6" | 6" | 600-C-BR | \$573.14 |
| Polypro | pylene | | |
| Body | Hose | ltem # | Price |
| 3/4" | 1/2" | PPC50 | \$12.21 |
| 3/4" | 3/4" | PPC75 | \$12.21 |
| 1" | 1" | PPC100 | \$13.89 |
| 1½" | 11⁄4" | PPC125 | \$16.30 |
| 1½" | 11⁄2" | PPC150 | \$16.09 |
| 2" | 2" | PPC200 | \$19.82 |
| 3" | 3" | PPC300 | \$33.36 |
| | | | |

PPC400

Type D

Female Coupler x Female NPTF




Aluminum

| Body | NPT | ltem # | Price |
|--|---|---|---|
| 1/2" | 1/2" | 50-D-AL | \$16.61 |
| 3/4" | 3/4" | 75-D-AL | \$17.12 |
| 1" | 1" | 100-D-AL | \$17.31 |
| 1½" | 11⁄2" | 150-D-AL | \$22.43 |
| 2" | 2" | 200-D-AL | \$23.80 |
| 3" | 3" | 300-D-AL | \$39.44 |
| 4" | 4" | 400-D-AL | \$58.55 |
| 5" | 5" | 500-D-AL | \$104.30 |
| 6" | 6" | 600-D-AL | \$137.35 |
| | 0" | | 6000.00 |
| 8" | 8" | 800-D-AL | \$608.36 |
| 8" Brass | 8 | 800-D-AL | \$608.36 |
| - | 8" NPT | 800-D-AL | \$608.36 Price |
| Brass | | | |
| Brass Body | NPT | ltem # | Price |
| Brass Body 1/2" | NPT 1/2" | Item # 50-D-BR | Price \$34.20 |
| Brass Body 1/2" 3/4" | NPT 1/2" 3/4" | Item # 50-D-BR 75-D-BR | Price \$34.20 \$37.61 |
| Brass Body 1/2" 3/4" 1" | NPT 1/2" 3/4" 1" | Item # 50-D-BR 75-D-BR 100-D-BR | Price \$34.20 \$37.61 \$41.37 |
| Brass Body 1/2" 3/4" 1" 1½" | NPT 1/2" 3/4" 1" 1½" | Item # 50-D-BR 75-D-BR 100-D-BR 150-D-BR | Price \$34.20 \$37.61 \$41.37 \$55.27 \$64.56 |
| Brass Body 1/2" 3/4" 1" 1½" 2" | NPT 1/2" 3/4" 1" 1½" 2" | Item # 50-D-BR 75-D-BR 100-D-BR 150-D-BR 200-D-BR | Price \$34.20 \$37.61 \$41.37 \$55.27 \$64.56 \$114.64 |
| Brass Body 1/2" 3/4" 1" 1½" 2" 3" | NPT 1/2" 3/4" 1" 1½" 2" 3" | Item # 50-D-BR 75-D-BR 100-D-BR 150-D-BR 200-D-BR 300-D-BR | Price \$34.20 \$37.61 \$41.37 \$55.27 |

Polypropylene

| NPT | ltem # | Price |
|-------|---------------------------------------|---|
| 1/2" | PPD50 | \$11.19 |
| 3/4" | PPD75 | \$11.19 |
| 1" | PPD100 | \$12.75 |
| 1¼" | PPD125 | \$14.95 |
| 11⁄2" | PPD150 | \$14.76 |
| 2" | PPD200 | \$18.19 |
| 3" | PPD300 | \$30.60 |
| 4" | PPD400 | \$61.48 |
| | 1/2" 3/4" 1" 1½" 2" 3" | 1/2" PPD50 3/4" PPD75 1" PPD100 1¼" PPD125 1½" PPD150 2" PPD200 3" PPD300 |

Type E Male Adapter x Hose Shank



Aluminum

4"

4"

PPE400

\$26.46

| Aluminum | | | |
|----------|--------|-----------|----------|
| Body | Hose | ltem # | Price |
| 1/2" | 1/2" | 50-E-AL | \$9.05 |
| 3/4" | 1/2" | 7550-E-AL | \$7.93 |
| 3/4" | 3/4" | 75-E-AL | \$9.25 |
| 1" | 1" | 100-E-AL | \$9.30 |
| 11⁄4" | 1¼" | 125-E-AL | \$12.10 |
| 11⁄2" | 11⁄2" | 150-E-AL | \$11.50 |
| 2" | 2" | 200-E-AL | \$15.13 |
| 21⁄2" | 21⁄2" | 250-E-AL | \$22.63 |
| 3" | 3" | 300-E-AL | \$26.41 |
| 4" | 4" | 400-E-AL | \$53.38 |
| 5" | 5" | 500-E-AL | \$85.75 |
| 6" | 6" | 600-E-AL | \$104.30 |
| 8" | 8" | 800-E-AL | \$434.54 |
| Brass | | | |
| Body | Hose | ltem # | Price |
| 1/2" | 1/2" | 50-E-BR | \$22.01 |
| 3/4" | 3/4" | 75-E-BR | \$22.01 |
| 1" | 1" | 100-E-BR | \$27.87 |
| 11⁄4" | 11⁄4" | 125-E-BR | \$38.17 |
| 1½" | 1½" | 150-E-BR | \$38.45 |
| 2" | 2" | 200-E-BR | \$48.80 |
| 21⁄2" | 21⁄2" | 250-E-BR | \$82.65 |
| 3" | 3" | 300-E-BR | \$83.51 |
| 4" | 4" | 400-E-BR | \$160.19 |
| 6" | 6" | 600-E-BR | \$455.16 |
| Polypro | pylene | | |
| Body | Hose | ltem # | Price |
| 3/4" | 1/2" | PPE50 | \$5.37 |
| 3/4" | 3/4" | PPE75 | \$5.37 |
| 1" | 1" | PPE100 | \$6.28 |
| 11⁄2" | 11⁄4" | PPE125 | \$6.28 |
| 11⁄2" | 11⁄2" | PPE150 | \$6.94 |
| 2" | 2" | PPE200 | \$8.12 |
| 3" | 3" | PPE300 | \$20.02 |
| | | | |

SAFETY NOTICE: Cam and groove couplings should *never* be used for compressed air or steam service.

\$67.01



Cam & Groove

Type F Male Adapter x Male NPTF

Aluminum

| Body | NPT | ltem # | Price |
|-------|-------|-----------|----------|
| 1/2" | 1/2" | 50-F-AL | \$6.69 |
| 3/4" | 1/2" | 7550-F-AL | \$12.21 |
| 3/4" | 3/4" | 75-F-AL | \$8.18 |
| 1" | 1" | 100-F-AL | \$10.37 |
| 11⁄4" | 11⁄4" | 125-F-AL | \$12.57 |
| 11⁄2" | 11⁄2" | 150-F-AL | \$12.66 |
| 2" | 2" | 200-F-AL | \$15.21 |
| 21⁄2" | 21⁄2" | 250-F-AL | \$26.96 |
| 3" | 3" | 300-F-AL | \$29.57 |
| 4" | 4" | 400-F-AL | \$53.94 |
| 5" | 5" | 500-F-AL | \$95.61 |
| 6" | 6" | 600-F-AL | \$119.99 |
| 8" | 8" | 800-F-AL | \$353.42 |

Brass

| Body | NPT | ltem # | Price |
|-------|-------|-----------|----------|
| 1/2" | 1/2" | 50-E-BR | \$22.01 |
| 3/4" | 1/2" | 7550-F-BR | \$21.63 |
| 3/4" | 3/4" | 75-F-BR | \$13.77 |
| 1" | 1" | 100-F-BR | \$18.10 |
| 11⁄4" | 11⁄4" | 125-F-BR | \$27.09 |
| 11⁄2" | 11⁄2" | 150-F-BR | \$26.12 |
| 2" | 2" | 200-F-BR | \$33.38 |
| 21⁄2" | 21⁄2" | 250-F-BR | \$64.11 |
| 3" | 3" | 300-F-BR | \$73.45 |
| 4" | 4" | 400-F-BR | \$116.53 |
| 6" | 6" | 600-F-BR | \$327.14 |

Polypropylene

| Body | NPT | ltem # | Price |
|-------|-------|--------|---------|
| 3/4" | 1/2" | PPF50 | \$5.37 |
| 3/4" | 3/4" | PPF75 | \$5.37 |
| 1" | 1" | PPF100 | \$6.28 |
| 11⁄2" | 11⁄4" | PPF125 | \$6.28 |
| 11⁄2" | 11⁄2" | PPF150 | \$6.28 |
| 2" | 2" | PPF200 | \$9.09 |
| 3" | 3" | PPF300 | \$20.02 |
| 4" | 4" | PPF400 | \$26.46 |

Type DC



Aluminum Body Item # Price 1/2" 50-DC-AL \$15.02 3/4" 75-DC-AL \$16.61 1" 100-DC-AL \$16.86 11/2" 150-DC-AL \$20.90 2" 200-DC-AL \$21.30 3" 300-DC-AL \$28.46 4" 400-DC-AL \$40.35 5" 500-DC-AL \$67.27 6" 600-DC-AL \$101.40 8" 800-DC-AL \$417.17 Brass

| Body | ltem # | Price |
|-------|-----------|----------|
| 1/2" | 50-DC-BR | \$26.75 |
| 3/4" | 75-DC-BR | \$31.92 |
| 1" | 100-DC-BR | \$40.95 |
| 11⁄2" | 150-DC-BR | \$51.07 |
| 2" | 200-DC-BR | \$54.40 |
| 3" | 300-DC-BR | \$78.94 |
| 4" | 400-DC-BR | \$109.55 |
| 5" | 500-DC-BR | \$269.72 |
| | | |

Polypropylene

| Body | ltem # | Price |
|-------|--------|---------|
| 3/4" | PPH75 | \$12.21 |
| 1" | PPH100 | \$13.43 |
| 11⁄2" | PPH150 | \$16.09 |
| 2" | PPH200 | \$19.82 |
| 3" | PPH300 | \$31.51 |
| 4" | PPH400 | \$48.94 |

Dust caps and plugs are not to be used in pressure applications for safety and environmental reasons.

Type DP Dust Plug



Aluminum

| Body | ltem # | Price |
|-------|-----------|----------|
| 3/4" | 75-DP-AL | \$8.58 |
| 1" | 100-DP-AL | \$9.54 |
| 1¼" | 125-DP-AL | \$11.34 |
| 11⁄2" | 150-DP-AL | \$12.17 |
| 2" | 200-DP-AL | \$12.46 |
| 21/2" | 250-DP-AL | \$17.42 |
| 3" | 300-DP-AL | \$18.29 |
| 4" | 400-DP-AL | \$27.84 |
| 5" | 500-DP-AL | \$51.03 |
| 6" | 600-DP-AL | \$58.29 |
| 8" | 800-DP-AL | \$243.35 |
| Brass | | |

| Body | ltem # | Price |
|-------|-----------|----------|
| 1/2" | 50-DP-BR | \$21.08 |
| 3/4" | 75-DP-BR | \$21.08 |
| 1" | 100-DP-BR | \$19.45 |
| 11⁄4" | 125-DP-BR | \$32.58 |
| 11⁄2" | 150-DP-BR | \$33.77 |
| 2" | 200-DP-BR | \$36.95 |
| 21⁄2" | 250-DP-BR | \$50.58 |
| 3" | 300-DP-BR | \$53.21 |
| 4" | 400-DP-BR | \$89.39 |
| 6" | 600-DP-BR | \$379.26 |

Polypropylene

| Body | ltem # | Price |
|-------|--------|---------|
| 3/4" | PPP75 | \$4.85 |
| 1" | PPP100 | \$6.02 |
| 11⁄2" | PPP150 | \$6.08 |
| 2" | PPP200 | \$7.85 |
| 3" | PPP300 | \$16.09 |
| 4" | PPP400 | \$20.84 |

Dust caps and plugs are not to be used in pressure applications for safety and environmental reasons.

SAFETY NOTICE: Cam and groove couplings should *never* be used for compressed air or steam service.



Nylon Abrasion Sleeve




Flexible nylon sleeve protects hose from abrasion and allows bundling of hose lines. Allow for the maximum outside diameter of the hose ends if sleeve is installed after hose assembly.

Nylon sleeve is available "by the foot" or in coils (300 feet per coil).

| ltem # | Sleeve I.D. | Coil Price (per foot) | Cut Price (per foot) |
|---------|----------------|--------------------------|-------------------------|
| NPS-076 | .76" | \$1.07 | \$1.19 |
| NPS-105 | 1.05" | \$1.25 | \$1.39 |
| NPS-114 | 1.14" | \$1.26 | \$1.40 |
| NPS-122 | 1.22" | \$1.38 | \$1.53 |
| NPS-153 | 1.53" | \$1.68 | \$1.87 |
| NPS-175 | 1.75" | \$1.82 | \$2.01 |
| NPS-209 | 2.09" | \$1.97 | \$2.19 |
| NPS-260 | 2.60" | \$2.68 | \$2.97 |
| NPS-291 | 2.91" | \$2.84 | \$3.15 |
| NPS-366 | 3.66" | \$4.08 | \$4.54 |

Spiral Guard Plastic Protective Coil



damage. Plastic Protective Coil is sold in 66 ft. lengths only (NFSGX110 sold in 33 ft. lengths).

| Item # | I.D. | Price |
|---------------|-------|----------|
| NFSGX16-66FT | .50" | \$58.28 |
| NFSGX20-66FT | .62" | \$80.85 |
| NFSGX25-66FT | .75" | \$111.83 |
| NFSGX32-66FT | .94" | \$160.13 |
| NFSGX40-66FT | 1.25" | \$237.83 |
| NFSGX50-66FT | 1.50" | \$313.95 |
| NFSGX63-66FT | 1.94" | \$427.88 |
| NFSGX75-66FT | 2.37" | \$612.68 |
| NFSGX90-66FT | 2.62" | \$792.75 |
| NFSGX110-33FT | 3.19" | \$471.98 |

Steel Wire Protective Coil

Rust resistant steel wire protects hose cover from abrasion and accidental damage. Steel Wire Protective Coil is sold in 20-foot lengths only.

| ltem # | I.D. | Price |
|-------------|-------|----------|
| SG-1S-20FT | .61" | \$19.39 |
| SG-12S-20FT | .67" | \$21.05 |
| SG-2S-20FT | .75" | \$19.62 |
| SG-14S-20FT | .85" | \$20.11 |
| SG-3S-20FT | .91" | \$20.58 |
| SG-4S-20FT | 1.04" | \$29.57 |
| SG-5S-20FT | 1.18" | \$48.26 |
| SG-6S-20FT | 1.34" | \$39.03 |
| SG-7S-20FT | 1.66" | \$46.60 |
| SG-9S-20FT | 1.87" | \$56.99 |
| SG-8S-20FT | 2.13" | \$54.63 |
| SG-10S-20FT | 2.38" | \$85.86 |
| SG-11S-20FT | 2.88" | \$162.97 |

Hose Armor Steel Protective Coil



Rust resistant steel coil for use where hose lines are subjected to excessive abrasion, kinking, or accidental damage. Hose Armor Steel Protective Coil is sold in 20-foot lengths only.

| HA-13S-20FT .57" \$150.6 HA-2S-20FT .63" \$113.0 HA-3S-20FT .75" \$115.7 HA-4S-20FT .88" \$153.6 HA-5S-20FT 1.03" \$67.8 HA-14S-20FT 1.13" \$213.6 HA-6S-20FT 1.22" \$195.7 | Coil I.D. | oil I.D. Price |
|---|--------------|----------------|
| HA-2S-20FT .63" \$113.0 HA-3S-20FT .75" \$115.7 HA-4S-20FT .88" \$153.0 HA-5S-20FT 1.03" \$67.8 HA-14S-20FT 1.13" \$213.0 HA-6S-20FT 1.22" \$195.7 | -20FT .50" | \$39.98 |
| HA-3S-20FT .75" \$115.7 HA-4S-20FT .88" \$153.6 HA-5S-20FT 1.03" \$67.8 HA-14S-20FT 1.13" \$213.6 HA-6S-20FT 1.22" \$195.7 | S-20FT .57" | \$150.63 |
| HA-4S-20FT.88"\$153.6HA-5S-20FT1.03"\$67.8HA-14S-20FT1.13"\$213.6HA-6S-20FT1.22"\$195.7 | -20FT .63" | 53" \$113.02 |
| HA-5S-20FT1.03"\$67.8HA-14S-20FT1.13"\$213.6HA-6S-20FT1.22"\$195.7 | -20FT .75" | /5" \$115.74 |
| HA-14S-20FT 1.13" \$213.6 HA-6S-20FT 1.22" \$195.7 | -20FT .88" | \$153.61 |
| HA-6S-20FT 1.22" \$195.7 | -20FT 1.03" | .03" \$67.88 |
| • | S-20FT 1.13" | .13" \$213.61 |
| | -20FT 1.22" | .22" \$195.74 |
| TIA-73-20F1 1.47 393.2 | -20FT 1.47" | .47" \$93.20 |
| HA-9S-20FT 1.69" \$392.3 | -20FT 1.69" | .69" \$392.34 |
| HA-8S-20FT 1.91" \$342.5 | -20FT 1.91" | .91" \$342.55 |
| HA-15S-20FT 2.00" \$234.7 | S-20FT 2.00" | .00" \$234.78 |
| HA-10S-20FT 2.13" \$568.5 | S-20FT 2.13" | .13" \$568.51 |
| HA-11S-20FT 2.56" \$726.3 | S-20FT 2.56" | .56" \$726.38 |

Hose-Bend Restrictors



Reduces bending stress near the hose fitting, preventing damage and extending the life of the hose. No adhesive or clamp needed. Designed to work with a variety of hydraulic and pressure-washer hoses.

| ltem # | I.D. | Length | Price |
|--------|-------|--------|--------|
| HB20 | .616" | 5.25" | \$3.24 |
| HB40 | .668" | 5.75" | \$3.42 |
| HB60 | .750" | 6.50" | \$3.50 |
| HB80 | .815" | 7.00" | \$3.66 |
| HB100 | .871" | 7.75" | \$4.61 |



Hose Protection

Hose Strap Steel with protective rubber



Provides support for long hose lengths, or to insure proper hose routing where abrasion, moving parts or heat may exist.

| ltem # | Clamp I.D. | Price |
|----------|------------|--------|
| COV-0509 | 0.25" | \$1.95 |
| COV-0709 | 0.37" | \$1.95 |
| COV-0809 | 0.44" | \$1.95 |
| COV-0913 | 0.50" | \$2.02 |
| COV-1013 | 0.56" | \$2.02 |
| COV-1113 | 0.63" | \$2.02 |
| COV-1213 | 0.68" | \$2.02 |
| COV-1313 | 0.75" | \$2.02 |
| COV-1413 | 0.81" | \$2.02 |
| COV-1513 | 0.87" | \$2.13 |
| COV-1613 | 0.94" | \$2.13 |
| COV-1713 | 1.00" | \$2.13 |
| COV-1817 | 1.12" | \$2.18 |
| COV-1917 | 1.19" | \$2.18 |
| COV-2017 | 1.18" | \$2.25 |
| COV-2117 | 1.25" | \$2.25 |
| COV-2317 | 1.37" | \$2.44 |
| COV-2517 | 1.50" | \$2.47 |
| COV-2617 | 1.56" | \$2.49 |
| COV-2917 | 1.75" | \$2.56 |
| COV-3117 | 1.81" | \$2.59 |
| COV-3217 | 1.93" | \$2.67 |
| COV-3317 | 2.06" | \$2.82 |
| COV-3417 | 2.15" | \$2.85 |
| COV-3617 | 2.25" | \$2.94 |
| COV-4517 | 2.75" | \$3.14 |
| COV-4717 | 2.88" | \$3.84 |
| COV-5717 | 3.56" | \$4.45 |
| | | |

Fire Jacket Protective Wrap



Silicone rubber coating over fiberglass (no asbestos) protects hose and tubing from high temperatures or molten splash.

- Iron oxide red color
- Temperature range: -65° to 500° F
- 3" wide

| Item # | Length | Price |
|--------|---------|----------|
| 4055-3 | 50 feet | \$463.58 |

Fire Tape



Used to seal the ends of fire jacket sleeve and wrap to prevent fraying.

- Iron oxide red color
- Temperature range: -45° to 380° F
- 1" wide

| ltem # | Length | Price |
|--------|----------|---------|
| FTH100 | 12 yards | \$49.00 |

Fire Jacket Protective Sleeve



Silicone rubber coating over fiberglass (no asbestos) protects hose and tubing from high temperatures or molten splash.

- Iron oxide red color
- Temperature range: -65° to 500° F

Each sleeve is 50' in length

| ltem # | Sleeve I.D. | Price |
|---------|-------------|----------|
| 0610-04 | 0.25" | \$176.87 |
| 1010-06 | 0.38" | \$184.41 |
| 1310-08 | 0.50" | \$220.12 |
| 1610-10 | 0.63" | \$248.35 |
| 1910-12 | 0.75" | \$280.34 |
| 2210-14 | 0.88" | \$331.13 |
| 2510-16 | 1.00" | \$378.15 |
| 3210-20 | 1.25" | \$428.40 |
| 3810-24 | 1.50" | \$478.07 |
| 4510-28 | 1.75" | \$577.41 |
| 5110-32 | 2.00" | \$651.91 |

Reelcraft® Hose Reels





Spring Retractable Fuel Delivery Reels

Reelcraft's spring retractable fuel delivery reels, equipped with Viton® seals, incorporate metal forms to insure the greatest possible strength and are ideal for mobile and permanentmount applications. These rugged, corrosion-resistant reels are available with or without fuel grade UL330 and ULC approved hose.

F7925-OLP



| Reel with Hose and Bumper | Price | Pressure (psi) | Hose I.D. | Hose O.D. | (M) NPTF Outlet | (F) NPTF Inlet | Hose Length | Without Hose and Bumper | Price | Pressure (psi) |
|------------------------------|-----------|-------------------|-----------|-----------|--------------------|-------------------|----------------|----------------------------|----------|-------------------|
| F7925-OLP | \$495.60 | 50 | 3/4" | 1.188" | 3/4" | 3/4" | 25 feet | F7900-OLP | \$372.75 | 500 |
| F83050-OLP | \$846.30 | 50 | 3/4" | 1.188" | 3/4" | 3/4" | 50 feet | F83000-OLP | \$565.95 | 500 |
| FD83075-OLP | \$1067.85 | 50 | 3/4" | 1.188" | 3/4" | 3/4" | 75 feet | FD83000-OLP | \$637.35 | 500 |



Medium Duty Spring Retractable Reels

Reelcraft's Series RT is an economical choice for a medium duty, lighter weight, spring-driven hose reel for applications that are less demanding, yet require a product that can withstand industrial and commercial use. The industrial-grade drive spring is protected from the environment in a polypropylene spool for longer service life. Guide arm adjusts to seven positions.



RT605-OLP

| Reel with Hose and Bumper | Price | Pressure (psi) | Hose I.D. | Hose O.D. | (M) NPTF Outlet | (F) NPTF Inlet | Hose Length | Without Hose and Bumper | Price | Pressure (psi) |
|------------------------------|----------|-------------------|-----------|-----------|--------------------|-------------------|----------------|----------------------------|----------|-------------------|
| RT450-OLP | \$194.25 | 300 | 1/4" | 0.475" | 1/4" | 1/4" | 50 feet | RT405-OLP | \$148.05 | 300 |
| RT650-OLP | \$235.20 | 300 | 3/8" | 0.600" | 3/8" | 3/8" | 50 feet | RT605-OLP | \$175.35 | 300 |
| RT850-OLP | \$317.10 | 300 | 1/2" | 0.750" | 1/2" | 1/2" | 50 feet | RT805-OLP | \$256.20 | 300 |



Pressure Wash Reels

Compact design and quality steel construction are incorporated into Reelcraft's newest line of pressure wash reels. The Series H18006 and PW80000 reels are able to carry 100 to 300 feet of tangle-free hose come complete with Super Swivel® for maximum product delivery.



| Reel Only (Hose and Bumper not included) | Price | Hose I.D. | Hose Capacity | Pressure (psi) | (F) NPTF Reel Inlet | Length | Width | Height |
|---|----------|-----------|------------------|-------------------|------------------------|--------|-------|--------|
| H18006M | \$212.10 | 3/8" | 100 feet | 3,000 | 1/2" | 18¼" | 20" | 19" |
| CA38106M | \$286.65 | 3/8" | 140 feet | 3,000 | 1/2" | 19" | 17¾" | 20¼" |
| CA38112M | \$286.65 | 3/8" | 300 feet | 3,000 | 1/2" | 25" | 17¾" | 201⁄4" |
| PW7600-OHP | \$407.40 | 3/8" | 50 feet | 4,500 | 1/2" | 19" | 7" | 20¼" |
| PW81000-OHP | \$613.20 | 3/8" | 100 feet | 4,500 | 1/2" | 24" | 10½" | 201⁄2" |



Hose Cutting and Cleaning Tools

HS150/HS300/HS500 Hose Cutting Saws

Professional cutting tools with scalloped blade for all hose cutting applications. Hose retaining system is included with HS300 and HS500 Series.



| Item | Blade | Motor / Power | Max. Hose Capacity | Price |
|---------|---------------|--------------------------|------------------------|-----------|
| HS150 | 10" Scalloped | 1 HP / 115V, 3450 RPM | 1¼" 4-wire, 1½" 1-wire | \$1154.48 |
| HS300 | 12" Scalloped | 3 HP / 220V Three Phase | 1¼" 6-wire, 2" 2-wire | \$1990.80 |
| HS300-1 | 12" Scalloped | 3 HP / 220V Single Phase | 1¼" 6-wire, 2" 2-wire | \$2158.80 |
| HS500 | 12" Scalloped | 5 HP / 220V Three Phase | All hoses up to 2" | \$2572.50 |
| HS500-1 | 12" Scalloped | 5 HP / 220V Single Phase | All hoses up to 2" | \$2740.50 |



Optional 103073 Hose Channel System is available in 5-foot sections with built-in tape measure and adjustable leg. Sold separately for the HS300 and HS500 series only.

Replacement Blades and Accessories

| Item # and Description | Price | | | |
|-------------------------------|----------|--|--|--|
| 102210 10" Scalloped Blade | \$314.06 | | | |
| 104033 12" Scalloped Blade* | \$379.68 | | | |
| 103172 Mister Kit* | \$468.30 | | | |
| 103073 Channel Section* | \$110.88 | | | |
| * HS300 and HS500 Series only | | | | |



Optional 103172 Mister Kit sprays a fine mist of air tool oil, cooling and lubricating the blade as it cuts. Sold separately for the HS300 and HS500 Series only.



JetCleaner JCL-2030 Hose/Tube Cleaning Kit

The JetCleaner pneumatic hose cleaning gun uses compressed air to shoot oversized foam projectiles. As the projectile is propelled forward, it pushes out deposits, leaving the tube, pipe or hose thoroughly cleaned.

- Cleans straight, curved and coiled hoses, with or without fittings
- · Simple to operate, minimal training required
- Push button trigger reduces fatigue
- Quick disconnect fittings for no-tools connection
- Power requirements: 90–120 psi compressed air

| ltem # | Description | Hose | Price |
|--------|-----------------|------|----------|
| JR-09 | 100 Projectiles | 1/4" | \$43.84 |
| JR-14 | 100 Projectiles | 3/8" | \$50.93 |
| JR-18 | 100 Projectiles | 1/2" | \$59.59 |
| JR-22 | 100 Projectiles | 5/8" | \$77.18 |
| JR-26 | 50 Projectiles | 3/4" | \$43.84 |
| JR-33 | 50 Projectiles | 1" | \$66.68 |
| JR-40 | 50 Projectiles | 1¼" | \$108.68 |



 JCL-2030 JetCleaner Kit
 \$1761.90

 Includes gun, carrying case and nine nozzles
 (1/4", 3/8", 1/2", 5/8", 3/4" 1", 1¼", 1½", and 2").

 Projectiles sold separately.
 Projectiles sold separately.

14" Cut-Off Saw

2 HP single-phase electric motor (3,500 max. RPM) cuts two-, four- and six-wire hydraulic hose up to 4" I.D.. Also cuts metal or masonry.

14" abrasive cutting wheel (sold separately) leaves a straight, smooth edge for easy assembly.

Built-in work vise holds hose securely for cutting.

| Item # and Description | Price |
|--------------------------|----------|
| CS14 Cut-Off Saw | \$147.00 |
| CS14-5B Pack of 5 blades | \$39.90 |

Hydraulic Hose Crimpers

D-Series Hydraulic Hose Crimpers accommodate a wide range of hose and fitting types.

Unlike some crimpers that only work with one brand of hose and fittings, our D-Series Hydraulic Hose Crimpers can crimp hose and fittings from virtually any manufacturer.

These fully adjustable crimpers can be set to the precise crimp diameter needed without the use of shims or spacer rings.



D100H Hand-Operated Crimper includes 2-stage manual pump and steel carrying case

Heavy-duty cylinder (D100 Series) delivers up to 35 tons of crimping force

Removable pusher and spring-loaded die sets for easy loading, even with bent tube and special fittings



Lightweight portable models are ideal for emergency repairs in the field

Direct-reading metric micrometer allows for precise adjustment of crimp diameters

Open design provides excellent operator visibility

D100S Standalone Crimper works with any 10,000 psi hydraulic pump (not included)

D100P Air-Powered Crimper includes pneumatic pump and steel carrying case



Two-piece die sets allow quick, easy die changes. With an effective crimp range of two to four millimeters, each adjustable die set crimps a variety of hoses and fittings.

crimp specifications on pages 70–73.

Steel carrying case (D100H and D100P only) has a storage compartment in the operator's manual.



| A | |
|-------------|--|
| ALL B | |
| | |
| | |
| and and and | |

Dies are sold separately, so you can buy as many or as few as you need. Recommended die selection is shown with

lid for dies, tools and



Adjustable Effective Price **Crimp Range** 22-26 mm \$303.34 25-29 mm \$303.34 28-32 mm \$303.34 31-35 mm \$303.34 35-39 mm \$303.34 39-43 mm \$303.34 43-45 mm \$303.34 47-51 mm \$303.34 51-55 mm \$303.34 55-57 mm \$530.46 58-60 mm \$530.46 60-62mm \$530.46 72-74 mm \$530.46 74-76 mm \$530.46

(1) For use with D165 only. (2) DA double-angle dies require additional double-angle tooling (sold separately).



Hydraulic Hose Crimpers

| D-Series Crimper Specifications Dies sold separately. Please see crimp specifications on pages 70–73 for die selection. | | | | | |
|---|------------------------|------------------------|-------------|---------------|-------------------|
| | D1005 | D100H | D100P | D165 | D205 |
| Max. Cylinder Force | 35 ton | 35 ton | 35 ton | 60 ton | 80 ton |
| Included Pump | None | 2-stage manual | Pneumatic | 1 HP Electric | 2 HP Electric |
| Power Requirements | 10,000 psi | n/a | 80 psi air | 110V-15A | 220V Single Phase |
| Dies (sold separately) | D100 Series | D100 Series | D100 Series | D100 Series | D200 Series |
| Max. 2-wire hose I.D. | 1" (1¼"*) | 1" (1¼"*) | 1" (1¼"*) | 11⁄4" | 1½" (2"*) |
| Max. 4-wire hose I.D. | ³ ⁄4" (1"*) | ³ ⁄4" (1"*) | 3⁄4" (1"*) | 11⁄4" | 1½" (2"*) |
| Max. 6-wire hose I.D. | n/a | n/a | n/a | 1" | 2" with DA dies* |
| Crimper Weight | 45 pounds | 75 pounds | 85 pounds | 140 pounds | 400 pounds |
| Crimper Depth | 14" | 16" | 16" | 22" | 29" |
| Crimper Width | 11" | 16" | 16" | 12.5" | 37.5" |
| Crimper Height | 23.5" | 17" | 17" | 22.5" | 32" |
| Catalog Price | \$1212.75 | \$1863.75 | \$2163.00 | \$2913.75 | \$4677.75 |

* Requires DA double-angle dies and additional double-angle tooling (sold separately).



D165 Compact Hose Crimper

includes 1 HP 110V-15A electric pump

- Crimps 2-wire and 4-wire hose up to 11/4" I.D.
- Foot pedal keeps both hands free to handle hose.
- Adjustable retraction stop limits ram retractions for quick repetitive crimps.
- Adjustable coupling stop for accurate, repetitive positioning of the assembly inside the dies.



D205 Large Hose Crimper includes 2 HP 220V electric pump

- Crimps 2-wire, 4-wire and 6-wire hose up to 2" I.D.
- Work light included
- Foot pedal keeps both hands free to handle hose.
- Adjustable retraction stop limits ram retractions for quick repetitive crimps.
- Adjustable coupling stop for accurate, repetitive positioning of the assembly inside the dies.

Hose Crimpers and Swaging Tools



DST1 Hand Swaging Tool

This hand-operated hose machine produces smooth, uniform coupling surfaces, without raised edge or ridges common in other coupling methods. The DST1 Hand Swaging Tool is designed to mount directly to your workbench or table.

Dies and pushers sold separately. Pusher and die selection chart is shown on page 31.

DST1 Hand Swaging Tool \$424.20 Use only with thermoplastic hose and fittings.



| DST1 Swaging T | ool Dies | Male Pushers |
|--------------------------|--------------------|---------------|
| 4540-302 | \$115.38 | 4599-MP001 |
| 4540-303 | \$115.38 | 4599-MP002 |
| 4540-304 | \$115.38 | 4599-MP003 |
| 4540-305 | \$115.38 | 4599-MP004 |
| 4540-306 | \$115.38 | 4599-MP005 |
| 4540-308 | \$115.38 | 4599-MP006 |
| 4540-312 | \$115.38 | 4599-MP007 |
| 4540-316 | \$115.38 | 4599-MP008 |
| | | 4599-MP009 |
| Female Pushers | | 4599-MP010 |
| 4599-FP002 | \$54.17 | 4599-MP011 |
| 4599-FP002 4599-FP004 | \$54.17 | 4599-MP012 |
| 4599-FP004 4599-FP005 | \$54.17 | 4599-MP013 |
| 4599-FP005 4599-FP006 | \$54.17 | 4599-MP023 |
| 4599-FP008 | | 4599-MP037 |
| 4599-FP008 4599-FP009 | \$54.17 | 4599-MP045 |
| 4599-FP009 4599-FP010 | \$54.17 \$54.17 | 4599-MP046 |
| 4599-FP010 4599-FP011 | \$54.17 | |
| 4599-FP011 4599-FP012 | \$54.17 | Bent Tube Pus |
| 4599-FP012 4599-FP013 | • • • | 4599-TP204 |
| 4599-FP013 4599-FP014 | \$54.17 | |
| | \$54.17 | 4599-TP205 |
| 4599-FP015 | \$54.17 | 4599-TP206 |
| 4599-FP016 | \$54.17 | 4599-TP208 |
| 4599-FP018 | \$59.22 | 4599-TP308 |

| 4599-MP001 | \$43.16 |
|------------|---------|
| 4599-MP002 | \$43.16 |
| 4599-MP003 | \$43.16 |
| 4599-MP004 | \$43.16 |
| 4599-MP005 | \$43.16 |
| 4599-MP006 | \$43.16 |
| 4599-MP007 | \$43.16 |
| 4599-MP008 | \$43.16 |
| 4599-MP009 | \$43.16 |
| 4599-MP010 | \$43.16 |
| 4599-MP011 | \$43.16 |
| 4599-MP012 | \$49.06 |
| 4599-MP013 | \$57.84 |
| 4599-MP023 | \$43.16 |
| 4599-MP037 | \$91.14 |
| 4599-MP045 | \$91.14 |
| 4599-MP046 | \$91.14 |
| | |

ent Tube Pushers

| \$54.17 | 4599-TP204 | \$141.96 |
|---------|------------|----------|
| \$54.17 | 4599-TP205 | \$141.96 |
| \$54.17 | 4599-TP206 | \$141.96 |
| \$54.17 | 4599-TP208 | \$141.96 |
| \$59.22 | 4599-TP308 | \$187.43 |
| | | |



Hose Crimpers and Swaging Tools

Ferrule Vises

Our ferrule vise crimping tools are ideal for light duty repetitive hose crimping. With a wide variety of available dies (sold separately) in either ribbed or straight configuration, these crimpers will consistently produce good looking accurate crimps time after time. Positive over-center action assures a consistent and repeatable crimp diameter with no need for adjustment.

The rugged cast iron frame and base is designed to provide years of dependable service and both the 670T and the 660T models have mounting holes which permit them to be securely mounted to a workbench.

| 660T | Manually-Operated Ferrule Vise | \$799.58 |
|------|--|-----------|
| 670T | Air-Operated Ferrule Vise | \$2199.75 |
| | Requires 80 psi compressed air (not included). | |
| Dies | All Sizes (see pages 44–45) | \$138.60 |



660T Manually-Operated Ferrule Vise

Brass Ferrule Crimper

The 855 Brass Ferrule Crimper provides "big tool" crimping advantages at a fraction of the cost. Rugged, portable and easy to use. Available in two models, each with five dies. Additional dies are available to increase the range of your crimper. *Use with brass ferrules only.*

- 855 Brass Ferrule Crimper (.49" to .71") \$168.00 Includes 856-1, 856-2, 856-3, 856-4 and 856-5 dies
- **855A** Brass Ferrule Crimper (.45" to .67") \$168.00 Includes 856-1, 856-2, 856-3, 856-4 and 856-7 dies

| Hose O.D. | Die # | Price | Hose O.D. | Die # | Price |
|--------------|--------|---------|--------------|-------|---------|
| .38" to .41" | 856-10 | \$26.20 | .64" to .67" | 856-1 | \$26.20 |
| .45" to .47" | 856-7 | \$26.20 | .69" to .71" | 856-5 | \$26.20 |
| .49" to .52" | 856-4 | \$26.20 | .76" to .78" | 856-8 | \$26.20 |
| .54" to .56" | 856-3 | \$26.20 | .82" to .84" | 856-9 | \$26.20 |
| .59" to .62" | 856-2 | \$26.20 | | | |

Large Brass Ferrule Crimper

The 860 Large Brass Ferrule Crimper brings the same economical utility of the 855 and 855A to larger hoses (with outside diameters from 11/16" to 1½"). Dies sold separately. *Use with brass or aluminum ferrules only.*

| 860 | Large Brass Ferrule Crimper | \$199.50 |
|-----|-----------------------------|----------|
| | Dies are not included. | |

| Hose O.D. | Die # | Price | Hose O.D. | Die # | Price |
|-----------|--------|---------|-----------|--------|---------|
| 11/16" | 861-22 | \$31.45 | 1" | 861-32 | \$31.45 |
| 23/32" | 861-23 | \$31.45 | 1-1/32" | 861-33 | \$31.45 |
| 3/4" | 861-24 | \$31.45 | 1-1/16" | 861-34 | \$31.45 |
| 25/32" | 861-25 | \$31.45 | 1-1/8" | 861-36 | \$31.45 |
| 13/16" | 861-26 | \$31.45 | 1-3/16" | 861-38 | \$31.45 |
| 27/32" | 861-27 | \$31.45 | 1-1/4" | 861-40 | \$31.45 |
| 7/8" | 861-28 | \$31.45 | 1-5/16" | 861-42 | \$31.45 |
| 29/32" | 861-29 | \$31.45 | 1-3/8" | 861-44 | \$31.45 |
| 15/16" | 861-30 | \$31.45 | 1-7/16" | 861-46 | \$31.45 |
| 32/32" | 861-31 | \$31.45 | 1-1/2" | 861-48 | \$31.45 |



CAUTION: the hose assembly tools on this page are not intended for use with high pressure hose assemblies. Please see our hydraulic hose crimpers beginning on page 60.



| Hose Fitting | | | Crimp Diameter +/005" (0.13 mm) | Recommended Die Select the die for your crim | | | Micrometer Setting |
|-----------------------------------|----------|-----------|------------------------------------|--|-----------|--------------|-----------------------|
| SAE 100R1AT H | ydraulic | Hose (R1) | | D100 | D165 | D205 | |
| | 1/4" | R1-04 | 0.575" (14.60 mm) | D100-12MM | D100-12MM | D200-12MM | 2.60 |
| | 3/8" | R1-06 | 0.725" (18.41 mm) | D100-16MM | D100-16MM | D200-16MM | 2.41 |
| Braided Hose | 1/2" | R1-08 | 0.845" (21.46 mm) | D100-19MM | D100-19MM | D200-19MM | 2.46 |
| Fittings | 5/8" | R1-10 | 0.995" (25.27 mm) | D100-22MM | D100-22MM | D200-22MM | 3.27 |
| crimp to knurl | 3/4" | R1-12 | 1.100" (27.90 mm) | D100-25MM | D100-25MM | D200-25MM | 2.90 |
| | 1" | R1-16 | 1.430" (36.30 mm) | D100-35MM | D100-35MM | D200-35MM | 1.30 |
| | 1-1/4" | R1-20 | 1.830" (46.50 mm) | N/A | D100-43MM | D200-43MM | 3.50 |
| | 1/4" | R1-04 | 0.655" (16.65 mm) | D100-16MM | D100-16MM | D200-16MM | 0.65 |
| W Series | 3/8" | R1-06 | 0.790" (20.05 mm) | D100-19MM | D100-19MM | D200-19MM | 1.05 |
| Bite-To-The Wire | 1/2" | R1-08 | 0.920" (23.36 mm) | D100-22MM | D100-22MM | D200-22MM | 1.36 |
| Hose Fittings crimp full shell | 3/4" | R1-12 | 1.215" (30.86 mm) | D100-28MM | D100-28MM | D200-28MM | 2.86 |
| chimp full shell | 1" | R1-16 | 1.625" (41.30 mm) | D100-39MM | D100-39MM | D200-39MM | 2.30 |
| | 1-1/4" | R1-20 | 1.965" (49.91 mm) | N/A | D100-47MM | D200-47MM | 2.91 |
| SAE 100R2AT H | ydraulic | Hose (R2) |) | D100 | D165 | D205 | |
| | 1/4" | R2-04 | 0.645" (16.38 mm) | D100-16MM | D100-16MM | D200-16MM | 0.38 |
| | 3/8" | R2-06 | 0.800" (20.32 mm) | D100-19MM | D100-19MM | D200-19MM | 1.32 |
| Braided Hose | 1/2" | R2-08 | 0.910" (23.10 mm) | D100-22MM | D100-22MM | D200-22MM | 1.10 |
| Fittings | 5/8" | R2-10 | 1.030" (26.16 mm) | D100-25MM | D100-25MM | D200-25MM | 1.16 |
| crimp to knurl | 3/4" | R2-12 | 1.190" (30.25 mm) | D100-28MM | D100-28MM | D200-28MM | 2.25 |
| | 1" | R2-16 | 1.507" (38.27 mm) | D100-35MM | D100-35MM | D200-35MM | 3.27 |
| | 1-1/4" | R2-20 | 1.908" (48.46 mm) | N/A | D100-47MM | D200-47MM | 1.46 |
| | 1/4" | R2-04 | 0.695" (17.65 mm) | D100-16MM | D100-16MM | D200-16MM | 1.65 |
| | 3/8" | R2-06 | 0.845" (21.46 mm) | D100-19MM | D100-19MM | D200-19MM | 2.48 |
| | 1/2" | R2-08 | 0.970" (24.63 mm) | D100-22MM | D100-22MM | D200-22MM | 2.63 |
| W Series | 5/8" | R2-10 | 1.200" (30.48 mm) | D100-28MM | D100-28MM | D200-28MM | 2.48 |
| Bite-To-The Wire Hose Fittings | 3/4" | R2-12 | 1.285" (32.65 mm) | D100-31MM | D100-31MM | D200-31MM | 1.65 |
| crimp full shell | 1" | R2-16 | 1.665" (42.30 mm) | D100-41MM | D100-41MM | D200-41MM | 1.30 |
| | 1-1/4" | R2-20 | 2.060" (52.32 mm) | N/A | D100-51MM | D200-51MM | 1.32 |
| | 1-1/2" | R2-24 | 2.400" (60.95 mm) | N/A | N/A | D200DA-60MM* | 0.95 |
| | 2" | R2-32 | 2.870" (72.90 mm) | N/A | N/A | D200DA-72MM* | 0.90 |

* D200DA Double-Angle Die Sets require double-angle tooling (sold separately).









D200 Double Angle Tooling

See pg. 66 of our hydraulic hose catalog for more information.



| Hose Fitting | Hose I.D. | Product Code | Crimp Diameter +/005" (0.13 mm) | Recommended Die Set Select the die for your crimper below | | | Micrometer Setting |
|---|--------------|-----------------|---|--|-----------|--------------|-----------------------|
| SAE 100R3 Gen | eral Purj | pose/Hydı | raulic Hose (R3) | D100 | D165 | D205 | |
| Braided Hose | 1/4" | R3-04 | 0.615" (15.60 mm) | D100-14MM | D100-14MM | D200-14MM | 1.60 |
| | 3/8" | R3-06 | 0.790" (20.05 mm) | D100-19MM | D100-19MM | D200-19MM | 1.05 |
| Fittings | 1/2" | R3-08 | 0.950" (24.15 mm) | D100-22MM | D100-22MM | D200-22MM | 2.15 |
| crimp to knurl | 3/4" | R3-12 | 1.240" (31.50 mm) | D100-31MM | D100-31MM | D200-31MM | 0.50 |
| | 1" | R3-16 | 1.520" (36.60 mm) | D100-35MM | D100-35MM | D200-35MM | 1.60 |
| SAE 100R4 Suct | ion and | Return Ho | ose (R4) | D100 | D165 | D205 | |
| Braided Hose | 3/4" | R4-12 | 1.233" (31.30 mm) | D100-31MM | D100-31MM | D200-31MM | 0.30 |
| Fittings | 1" | R4-16 | 1.466" (37.25 mm) | D100-35MM | D100-35MM | D200-35MM | 2.25 |
| crimp to knurl | 1-1/4" | R4-20 | 1.780" (45.20 mm) | N/A | D100-43MM | D200-43MM | 2.20 |
| | 3/4" | R4-12 | 1.280" (32.50 mm) | D100-31MM | D100-31MM | D200-31MM | 1.50 |
| Two-Piece | 1" | R4-16 | 1.540" (39.10 mm) | D100-39MM | D100-39MM | D200-39MM | 0.10 |
| Suction Hose Fittings | 1-1/4" | R4-20 | 1.825" (46.35 mm) | N/A | D100-43MM | D200-43MM | 3.35 |
| crimp full shell | 1-1/2" | R4-24 | 2.040" (51.80 mm) | N/A | N/A | D200-51MM | 0.80 |
| | 2" | R4-32 | 2.480" (63.00 mm) | N/A | N/A | D200DA-62MM* | 1.00 |
| W Series | 1-1/2" | R4-24 | 2.360" (59.94 mm) | N/A | N/A | D200DA-58MM* | 1.94 |
| Bite-To-The Wire Hose Fittings crimp full shell | 2" | R4-32 | 2.900" (73.66 mm) | N/A | N/A | D200DA-72MM* | 1.66 |
| SAE 100R5 Gen | eral Purj | pose/Truc | k Hose (R5) | D100 | D165 | D205 | |
| | 3/16" | R5-04 | 0.535" (13.60 mm) | D100-12MM | D100-12MM | D200-12MM | 1.60 |
| | 1/4" | R5-05 | 0.660" (16.75 mm) | D100-16MM | D100-16MM | D200-16MM | 0.75 |
| | 5/16" | R5-06 | 0.725" (18.40 mm) | D100-16MM | D100-16MM | D200-16MM | 2.40 |
| | 13/32" | R5-08 | 0.830" (21.10 mm) | D100-19MM | D100-19MM | D200-19MM | 2.10 |
| R5 Series Truck Hose Fittings | 1/2" | R5-10 | 0.915" (23.30 mm) | D100-22MM | D100-22MM | D200-22MM | 1.30 |
| crimp to knurl | 5/8" | R5-12 | 1.035" (26.30 mm) | D100-25MM | D100-25MM | D200-25MM | 1.30 |
| | 7/8" | R5-16 | 1.240" (31.50 mm) | D100-29MM | D100-29MM | D200-29MM | 2.50 |
| | 1-1/8" | R5-20 | 1.535" (38.95 mm) | D100-35MM | D100-35MM | D200-35MM | 3.95 |
| | 1-3/8" | R5-24 | 1.730" (43.95 mm) | N/A | D100-43MM | D200-43MM | 0.95 |
| | 1-13/16" | R5-32 | 2.225" (56.50 mm) | N/A | N/A | D200DA-55MM* | 1.50 |
| SAE 100R7 Ther | moplast | tic Hose (R | 7BK/R7NC) | D100 | D165 | D205 | |
| | 1/8" | R7-02 | 0.358" (09.10 mm) | D100-08MM | D100-08MM | D200-08MM | 1.10 |
| 3 Series | 3/16" | R7-03 | 0.478" (12.14 mm) | D100-10MM | D100-10MM | D200-10MM | 2.14 |
| Thermoplastic | 1/4" | R7-04 | 0.555" (14.10 mm) | D100-12MM | D100-12MM | D200-12MM | 2.10 |
| Hose Fittings crimp to knurl | 5/16" | R7-05 | 0.630" (16.00 mm) | D100-14MM | D100-14MM | D200-14MM | 2.00 |
| | 3/8" | R7-06 | 0.675" (17.15 mm) | D100-16MM | D100-16MM | D200-16MM | 1.15 |
| | 1/2" | R7-08 | 0.825" (20.96 mm) | D100-19MM | D100-19MM | D200-19MM | 1.96 |
| | 3/16" | R7-03 | 0.495" (12.57 mm) | D100-10MM | D100-10MM | D200-10MM | 2.57 |
| | 1/4" | R7-04 | 0.580" (14.73 mm) | D100-12MM | D100-12MM | D200-12MM | 2.73 |
| Braided Hose | 5/16" | R7-05 | 0.630" (16.00 mm) | D100-14MM | D100-14MM | D200-14MM | 2.00 |
| Fittings | 3/8" | R7-06 | 0.720" (18.28 mm) | D100-16MM | D100-16MM | D200-16MM | 4.28 |
| crimp to knurl | 1/2" | R7-08 | 0.850" (21.59 mm) | D100-19MM | D100-19MM | D200-19MM | 2.59 |
| | 3/4" | R7-12 | 1.120" (28.44 mm) | D100-28MM | D100-28MM | D200-28MM | 0.44 |
| | 1" | R7-16 | 1.400" (35.56 mm) | D100-35MM | D100-35MM | D200-35MM | |

800-535-1302 • SAVE 6% WHEN YOU BUY ONLINE at www.DiscountHydraulicHose.com Page 71



| Hose Fitting | ng Hose Product I.D. Code | | Crimp Diameter +/005" (0.13 mm) | Recommended Die Set Select the die for your crimper below | | | Micrometer Setting |
|--|------------------------------|-----------------|---|---|-----------|-----------|-----------------------|
| SAE 100R8 The | moplas | tic Hose (F | R8BK/R8NC) | D100 | D165 | D205 | |
| | 3/16" | R8-03 | 0.358" (12.14 mm) | D100-10MM | D100-10MM | D200-10MM | 2.14 |
| 3 Series | 1/4" | R8-04 | 0.555" (14.10 mm) | D100-12MM | D100-12MM | D200-12MM | 2.10 |
| Thermoplastic Hose Fittings crimp to knurl | 5/16" | R8-05 | 0.630" (16.00 mm) | D100-14MM | D100-14MM | D200-14MM | 2.00 |
| | 3/8" | R8-06 | 0.675" (17.15 mm) | D100-16MM | D100-16MM | D200-16MM | 1.15 |
| | 1/2" | R8-08 | 0.825" (20.96 mm) | D100-19MM | D100-19MM | D200-19MM | 1.96 |
| | 3/16" | R8-03 | 0.485" (12.32 mm) | D100-12MM | D100-12MM | D200-12MM | 0.32 |
| Braided Hose Fittings | 1/4" | R8-04 | 0.580" (14.73 mm) | D100-12MM | D100-12MM | D200-12MM | 2.73 |
| crimp to knurl | 3/8" | R8-06 | 0.725" (18.41 mm) | D100-16MM | D100-16MM | D200-16MM | 2.41 |
| | 1/2" | R8-08 | 0.830" (21.08 mm) | D100-19MM | D100-19MM | D200-19MM | 2.08 |
| Pressure Washe | r Hose (| PW/PWB) | | D100 | D165 | D205 | |
| Braided Hose Fittings | 1/4" | PW-04 PWB-04 | 0.560" (14.22 mm) | D100-14MM | D100-14MM | D200-14MM | 0.22 |
| crimp to knurl | 3/8" | PW-04 PWB-04 | 0.670" (17.02 mm) | D100-16MM | D100-16MM | D200-16MM | 1.02 |

* D200DA Double-Angle Die Sets require double-angle tooling (sold separately).

Braided Vs. W-Series Fittings

Our braided hose fittings are made to interchange with most Weatherhead "U' series fittings, and attach by crimping to the outer rubber jacket of the hose. Our W-Series bite-to-the wire fittings are designed for superior performace by biting into the steel reinforced wire of the hydraulic hoses.



Finished Braided Crimp



Finished W-Series Crimp

Remember to always measure your crimps!

Item: 93293-3VGA

CEN-TECH



| Hose Fitting | HoseProductCrimp DiameterI.D.Code+/005" (0.13 mm) | | Re Select t | Micrometer Setting | | | |
|---|---|------------|-----------------------|-----------------------|-----------|--------------|------|
| SAE 100R12 Fou | ur-Wire I | Hydraulic | Hose (R12) | D100 | D165 | D205 | |
| | 3/8" | R12-06 | 0.870" (22.10 mm) | D100-22MM | D100-22MM | D200-22MM | 0.10 |
| | 1/2" | R12-08 | 1.010" (25.65 mm) | D100-25MM | D100-25MM | D200-25MM | 0.65 |
| W Series | 3/4" | R12-12 | 1.320" (33.55 mm) | D100-31MM | D100-31MM | D200-31MM | 2.55 |
| Bite-To-The Wire Hose Fittings | 1" | R12-16 | 1.630" (41.40 mm) | D100-39MM | D100-39MM | D200-39MM | 2.40 |
| crimp full shell | 1-1/4" | R12-20 | 2.045" (51.95 mm) | N/A | D100-51MM | D200-51MM | 0.95 |
| | 1-1/2" | R12-24 | 2.375" (60.35 mm) | N/A | N/A | D200DA-60MM* | 0.35 |
| | 2" | R12-32 | 2.885" (73.30 mm) | N/A | N/A | D200DA-72MM* | 1.30 |
| SAE 100R13 Hy | draulic H | lose (R13) | | D100 | D165 | D205 | |
| W Series Bite-To-The Wire | 3/4" | R13-12 | 1.335" (33.90 mm) | D100-31MM | D100-31MM | D200-31MM | 2.90 |
| Hose Fittings crimp full shell | 1" | R13-16 | 1.645" (41.80 mm) | D100-39MM | D100-39MM | D200-39MM | 2.80 |
| JJ Series Skived Hose | 1-1/4" | R13-20 | 2.050" (52.05 mm) | N/A | D100-51MM | D200-51MM | 1.05 |
| Fittings | 1-1/2" | R13-24 | 2.320" (58.95 mm) | N/A | N/A | D200DA-58MM* | 0.95 |
| skive before assembly, crimp full shell | 2" | R13-32 | 2.980" (75.70 mm) | N/A | N/A | D200DA-75MM* | 0.70 |
| SAE 100R14A P | TFE Hos | e (R14) | | D100 | D165 | D205 | |
| | 3/16" | R14-04 | 0.395" (10.05 mm) | D100-10MM | D100-10MM | D200-10MM | 0.05 |
| | 1/4" | R14-05 | 0.430" (10.90 mm) | D100-10MM | D100-10MM | D200-10MM | 0.90 |
| T Series | 5/16" | R14-06 | 0.490" (12.45 mm) | D100-12MM | D100-12MM | D200-12MM | 0.45 |
| PTFE Hose Fittings | 3/8" | R14-07 | 0.565" (14.35 mm) | D100-14MM | D100-14MM | D200-14MM | 0.35 |
| crimp to knurl | 1/2" | R14-10 | 0.695" (17.65 mm) | D100-16MM | D100-16MM | D200-16MM | 1.65 |
| | 3/4" | R14-14 | 0.995" (25.25 mm) | D100-25MM | D100-25MM | D200-25MM | 0.25 |
| | 1" | R14-18 | 1.225" (31.10 mm) | D100-31MM | D100-31MM | D200-31MM | 0.10 |
| SAE 100R16 Hy | draulic H | lose (R16) | | D100 | D165 | D205 | |
| | 1/4" | R16-04 | 0.615" (15.60 mm) | D100-14MM | D100-14MM | D200-14MM | 1.60 |
| | 3/8" | R16-06 | 0.740" (18.79 mm) | D100-16MM | D100-16MM | D200-16MM | 2.79 |
| Braided Hose Fittings | 1/2" | R16-08 | 0.860" (21.84 mm) | D100-19MM | D100-19MM | D200-19MM | 2.84 |
| crimp to knurl | 5/8" | R16-10 | 1.000" (25.40 mm) | D100-25MM | D100-25MM | D200-25MM | 0.40 |
| | 3/4" | R16-12 | 1.130" (28.70 mm) | D100-28MM | D100-28MM | D200-28MM | 0.70 |
| | 1" | R16-16 | 1.425" (36.20 mm) | D100-35MM | D100-35MM | D200-35MM | 1.20 |
| | 1/4" | R16-04 | 0.670" (17.01 mm) | D100-16MM | D100-16MM | D200-16MM | 1.01 |
| W Series | 3/8" | R16-06 | 0.815" (20.70 mm) | D100-19MM | D100-19MM | D200-19MM | 1.70 |
| Bite-To-The Wire | 1/2" | R16-08 | 0.945" (24.00 mm) | D100-22MM | D100-22MM | D200-22MM | 2.00 |
| Hose Fittings crimp full shell | 5/8" | R16-10 | 1.178" (29.92 mm) | D100-28MM | D100-28MM | D200-28MM | 1.92 |
| | 3/4" | R16-12 | 1.230" (31.25 mm) | D100-31MM | D100-31MM | D200-31MM | 0.25 |
| | 1" | R16-16 | 1.555" (39.50 mm) | D100-39MM | D100-39MM | D200-39MM | 0.50 |

* D200DA Double-Angle Die Sets require double-angle tooling (sold separately).



| Hose Fitting | Hose Fitting Hose Product I.D. Code | | Crimp Diameter +/005" (0.13 mm) | | ecommended Di he die for your crin | | Micrometer Setting |
|------------------------------|--|-------------|---|-----------|--|--------------|-----------------------|
| SAE 100R17 Hy | draulic l | Hose (R17) | | D100 | D165 | D205 | |
| | 1/4" | R17-04 | 0.565" (14.35 mm) | D100-14MM | D100-14MM | D200-14MM | 0.35 |
| Braided Hose | 3/8" | R17-06 | 0.705" (17.90 mm) | D100-16MM | D100-16MM | D200-16MM | 1.90 |
| Fittings | 1/2" | R17-08 | 0.840" (21.35 mm) | D100-19MM | D100-19MM | D200-19MM | 2.35 |
| crimp to knurl | 5/8" | R17-10 | 0.995" (25.27 mm) | D100-25MM | D100-25MM | D200-25MM | 0.27 |
| | 3/4" | R17-12 | 1.140" (28.95 mm) | D100-28MM | D100-28MM | D200-28MM | 0.95 |
| | 1/4" | R17-04 | 0.625" (15.90 mm) | D100-14MM | D100-14MM | D200-14MM | 1.90 |
| W Series | 3/8" | R17-06 | 0.779" (19.80 mm) | D100-19MM | D100-19MM | D200-19MM | 0.80 |
| Bite-To-The Wire | 1/2" | R17-08 | 0.950" (24.10 mm) | D100-22MM | D100-22MM | D200-22MM | 2.10 |
| Hose Fittings | 5/8" | R17-10 | 1.170" (29.70 mm) | D100-28MM | D100-28MM | D200-28MM | 1.70 |
| crimp full shell | 3/4" | R17-12 | 1.275" (32.40 mm) | D100-31MM | D100-31MM | D200-31MM | 1.40 |
| | 1" | R17-16 | 1.564" (39.75 mm) | D100-35MM | D100-35MM | D200-35MM | 4.75 |
| Hydraulax [™] TOl | JGH Hyd | lraulic Hos | e (HT) | D100 | D165 | D205 | |
| | 1/4" | HT-04 | 0.600" (15.25 mm) | D100-14MM | D100-14MM | D200-14MM | 1.25 |
| Braided Hose | 3/8" | HT-06 | 0.750" (19.05 mm) | D100-16MM | D100-16MM | D200-16MM | 3.05 |
| Fittings | 1/2" | HT-08 | 0.860" (21.85 mm) | D100-19MM | D100-19MM | D200-19MM | 2.85 |
| crimp to knurl | 5/8" | HT-10 | 0.985" (25.01 mm) | D100-22MM | D100-22MM | D200-22MM | 3.01 |
| | 3/4" | HT-12 | 1.151" (29.25 mm) | D100-28MM | D100-28MM | D200-28MM | 1.25 |
| | 1/4" | HT-04 | 0.660" (16.75 mm) | D100-16MM | D100-16MM | D200-16MM | 0.75 |
| W Series | 3/8" | HT-06 | 0.800" (20.30 mm) | D100-19MM | D100-19MM | D200-19MM | 1.30 |
| Bite-To-The Wire | 1/2" | HT-08 | 0.950" (24.15 mm) | D100-22MM | D100-22MM | D200-22MM | 2.15 |
| Hose Fittings | 5/8" | HT-10 | 1.170" (29.70 mm) | D100-28MM | D100-28MM | D200-28MM | 1.70 |
| crimp full shell | 3/4" | HT-12 | 1.240" (31.50 mm) | D100-31MM | D100-31MM | D200-31MM | 0.50 |
| | 1" | HT-16 | 1.545" (39.25 mm) | D100-35MM | D100-35MM | D200-35MM | 4.25 |
| 10,000 PSI Hydr | aulic Jac | k Hose (H | JK) | D100 | D165 | D205 | |
| Braided Hose Fittings | 1/4" | HJK-04 | 0.634" (16.10 mm) | D100-14MM | D100-14MM | D200-14MM | 2.10 |
| crimp to knurl | 3/8" | HJK-06 | 0.785" (19.95 mm) | D100-19MM | D100-19MM | D200-19MM | 0.95 |
| EN 856 4SH Hy | draulic H | lose (4SH) | | D100 | D165 | D205 | |
| W.C | 3/4" | 4SH-12 | 1.320" (33.55 mm) | D100-31MM | D100-31MM | D200-31MM | 2.55 |
| W Series Bite-To-The Wire | 1" | 4SH-16 | 1.630" (41.40 mm) | D100-39MM | D100-39MM | D200-39MM | 2.40 |
| Hose Fittings | 1-1/4" | 4SH-20 | 1.990" (50.55 mm) | N/A | D100-47MM | D200-47MM | 3.55 |
| crimp full shell | 1-1/2" | 4SH-24 | 2.390" (60.70 mm) | N/A | N/A | D200DA-60MM* | 0.70 |

* D200DA Double-Angle Die Sets require double-angle tooling (sold separately).



Dies can be found on page 66 of our Hydraulic Hose Catalog. Hose Cutting Saws are located on page 65.





NATIONAL PIPE THREADS

There are several variations of pipe threads. Thread forms include the Dryseal American Standard Taper Pipe Thread (NPTF), the National Pipe Straight Threads for Mechanical Joints (NPSM) and the dryseal American Fuel Internal Straight Pipe Thread (NPSF). Each series is normally identified by the abbreviated letter designation.

The NPTF thread is recommended for hydraulic service. This thread series is used on both male and female ends and forms a seal by the interference fit at the root and crest of the mating threads. The NPTF male also has an internal chamfer of 30° which allows it to seal at the seat with female NPSM pipe swivels. The NPSM is a straight pipe thread and sealing is obtained by the mating of the 30° seats of the male and female ends.

FLARED TUBE FITTINGS

SAE 37° Flare (JIC): The seal is obtained by the mating of two beveled metal surfaces. The function of the threads is simply to draw these two surfaces together. This style is used particularly in high pressure systems. As illustrated below, both the bevel on the male and the seat in the female are machined to 37°.

SAE 45° Flare: These flared tube fittings are similar to JIC, however the mating surfaces are machined at 45°. These couplings are usually used for low pressure applications such as refrigerant and fuel lines in conjunction with copper tubing which flares easily to 45°.

O-RING CONNECTIONS

SAE Straight Thread (O-Ring Boss): This fitting is a modification of the male JIC where the beveled 37° nose has been removed and a groove has been machined between the threads and the hex in which an O-ring is seated. The female is a port which has been tapped to the proper straight thread size and chamfered at the port face to provide an O-ring seat. The seal is made when the O-ring is trapped between port chamfer, thread under-cut, and the male fitting.

O-Ring Face Seal (ORFS): Uses an O-ring (SAE J515) in a groove on the male face side. This is mated to flat face with an O-ring on the female swivel side, forming a seal without metal deformation much the same as an SAE four bolt split flange connection without the bolts. The O-ring face seal connection has been tested to SAE J343 tests and procedures and meets or exceeds SAE J1453 specifications. This connector has proven its superiority in leak resistance, ease of installation, high operating pressure, increased torque tolerance and reusability with its ability to be connected and disconnected frequently.

SAE J518 Four-Bolt Flange: Available in two pressure ratings. Code 61 is referred to as the "standard" series and Code 62 is the "6000 psi" series. The design of both series is the same, but the bolt-hole and flange diameters are different. The female port is unthreaded. The male consists of a flanged head, grooved for an O-ring. The seal is made when the O-ring is compressed between the flange head and the surface surrounding the port.

| Nominal Size | Dash Size | National Pipe Thread | SAE 37° Flare (JIC) | SAE 45° Flare | SAE Straight Thread O-Ring Boss (ORB) | g O-Ring Face Seal (ORFS) | Code 61 Flange | Code 62 Flange |
|---|----------------------------|-------------------------|------------------------|----------------------|---|------------------------------|----------------------|-------------------|
| Nominal size usua to inside pipe dia or outside tube d With flanges, non size refers to port diameter. | méter iameter. ninal | | | | | | | |
| 1/8" | -02 | 1⁄8–27 | ⁵ ⁄16–24 | ⁵ ⁄16–24 | ⁵ ⁄16–24 | | | |
| 3/16" | -03 | | ³ ⁄8–24 | ³ ⁄8–24 | 3∕8–24 | | | |
| 1/4" | -04 | 1⁄4–18 | 7⁄16–20 | 7⁄16–20 | 7⁄16–20 | %16–18 | | |
| 5/16" | -05 | | 1⁄2–20 | 1⁄2–20 | 1⁄2–20 | | | |
| 3/8" | -06 | 3∕8−18 | %16–18 | ⁵⁄8–18 | %16–18 | ¹¹ ⁄16–16 | | |
| 7/16" | -07 | | | ¹¹ ⁄16–16 | | | | |
| 1/2" | -08 | 1⁄2–14 | 3⁄4–16 | 3⁄4–16 | 3⁄4–16 | ¹³ ⁄16–16 | 1 ³ ⁄16" | 1 ¼" |
| 5/8" | -10 | | ‰−14 | 7⁄8–14 | ‰−14 | 1–14 | | |
| 3/4" | -12 | ³ ⁄4–14 | 1 1⁄16–12 | 1 1⁄16–14 | 1 1⁄16–12 | 1 ³ ⁄16–12 | 1 1⁄2" | 1 5⁄8" |
| 7/8" | -14 | | 1 ³ ⁄16–12 | 1 ¼–12 | 1 ¾6–12 | | | |
| 1" | -16 | 1–11½ | 1 5⁄16–12 | 1 ¾–12 | 1 5⁄16–12 | 1 7⁄16–12 | 1 3⁄4" | 1 1%" |
| 11⁄4" | -20 | 1 ¼–11½ | 1 5⁄8–12 | | 1 5⁄8–12 | 1 11/16–12 | 2" | 2 1⁄8" |
| 11⁄2" | -24 | 1 ½–11½ | 1 %–12 | | 1 %–12 | 2–12 | 2 3⁄8" | 2 1⁄2" |
| 2" | -32 | 2–11½ | 2 1⁄2–12 | | 2 1⁄2–12 | | 2 ¹³ ⁄16" | 3 1⁄8" |