

GoldSeam[™]

DECK PROTECTION-ROOF SEALING TAPE



Closes the gap in preventing water infiltration

IKO GoldSeam™

ROOF SEALING TAPE



PRODUCT SPECIFICATIONS

Length	66.7' (20.32 m)
Width	4.25" (108 mm)
Package	1 roll per carton

Note: All values shown are approximate

- DECK PROTECTION | ROOF SEALING TAPE
 IKO GoldSeam™
 - 1a (Apply where the fascia and the eaves meet).
 - **1b** (Apply over seams when sealing deck using synthetic underlayment).

DECK PROTECTION | ICE & WATER PROTECTORS

1c IKO StormShield®, ArmourGard™ or GoldShield™

- 2 SYNTHETIC UNDERLAYMENT

 Stormtite® Or RoofGard Cool Grey™
- 3 ROOF STARTERS

 Leading Edge Plus or EdgeSeal®
 (used at eaves and rakes).
- 4 CAPPING SHINGLES

 Hip & Ridge 12™, Hip & Ridge Plus™

 or IKO UltraHP® / IKO UltraHP IR

Note: The information in this document is subject to change without notice. IKO assumes no responsibility for errors that may appear in this document.





Seal the Gap with IKO GoldSeam.

Leading industry experts have identified the gap between the fascia and the roof deck as the most vulnerable area of the roof. It's the primary site of ice damming, moisture and rot issues, water infiltration and a main entry point for insect and rodent infestation.

IKO GoldSeam is an advanced multi-function tape that effectively seals that gap and protects other areas susceptible to such potential problems.

- Premium protection against leaks.
- Extreme flexibility for superior performance.
- Self-sealing around roofing nails for enhanced leak protection.
- Silicone-treated release sheet for quick and easy installation.
- Meets or exceeds most national building code requirements.
- Specially treated film provides slip-resistant surface for safer, surer footing on steep slopes.





IKO GoldSeam is part of the PROFORMAX Integrated Roofing Components System.



Use IKO GoldSeam to seal between the eave and fascia. Installing about 4" of this tape over the gap provides superior eave flashing and protection. Its extreme flexibility ensures that it won't crack or tear and the tape is ultra-tacky to help ensure a tight seal. It creates a highly effective barrier against potentially damaging water infiltration and helps deter insect and rodent access into the attic space.



Use IKO GoldSeam Tape to seal roof deck seams. The joints where plywood or OSB panels butt up against each other on the roof deck must be properly sealed. Once the seams have been taped, you can continue to cover the deck with IKO's synthetic underlayment. Remember to use IKO Ice and Water Protector in areas required by code.

Use IKO GoldSeam Tape to pre- or sub-flash any area where traditional metal flashing will later be installed. This includes around skylights, chimneys, walls, pipes or other likely sites of infiltration.

Find out more about our products now by talking to an IKO sales representative or your professional contractor or contact us directly at: **United States**

1-888-IKO-ROOF (1-888-456-7663), Canada 1-855-IKO-ROOF (1-855-456-7663).

Learn more at: IKO.COM