

# Maßtabelle für Rohrgewinde

Whitworth Rohrgewinde DIN ISO 228 (DIN 259) BSP (British Standard Pipe)

Gewindekennung	Durchmesser Inch	Durchmesser aussen mm	Durchmesser Mutter mm	Durchmesser Kernloch mm	Gänge je Inch	Steigung mm
G 1/8"	1/8	9,73	8,85	8,80	28	0,907
G 1/4"	1/4	13,16	11,89	11,80	19	1,337
G 3/8"	3/8	16,66	15,39	15,25	19	1,337
G 1/2"	1/2	20,95	19,17	19,00	14	1,814
G 5/8"	5/8	22,91	21,13	21,00	14	1,814
G 3/4"	3/4	26,44	24,66	24,50	14	1,814
G 7/8"	7/8	30,20	28,42	28,25	14	1,814
G 1"	1	33,25	30,93	30,75	11	2,309
G 1 1/8"	1 1/8	37,90	35,58	35,30	11	2,309
G 1 1/4"	1 1/4	41,91	39,59	39,25	11	2,309
G 1 3/8"	1 3/8	44,32	42,00	41,70	11	2,309
G 1 1/2"	1 1/2	47,80	45,48	45,25	11	2,309
G 1 3/4"	1 3/4	53,74	51,43	51,10	11	2,309
G 2"	2	59,61	57,29	57,00	11	2,309
G 2 1/4"	2 1/4	65,71	63,39	63,10	11	2,309
G 2 1/2"	2 1/2	75,18	72,86	72,60	11	2,309
G 2 3/4"	2 3/4	81,53	79,21	78,90	11	2,309
G 3"	3	87,88	85,56	85,30	11	2,309
G 3 1/4"	3 1/4	93,98	91,66	91,50	11	2,309
G 3 1/2"	3 1/2	100,33	98,01	97,70	11	2,309
G 3 3/4"	3 3/4	106,68	104,30	104,00	11	2,309
G 4"	4	113,03	110,71	110,40	11	2,309

