

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST
CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE)
CB SCHEME


SYSTEME CEI D'ACCEPTATION MUTUELLE DE
CERTIFICATS D'ESSAIS DES EQUIPEMENTS
ELECTRIQUES (IECEE) METHODE OC

CB TEST CERTIFICATE CERTIFICAT D'ESSAI OC

Product	LED Luminaires LED luminaires for professional use
Name and address of the applicant	Arnold & Richter Cine Technik GmbH & Co Betriebs KG Pulvermühle 83071 Stephanskirchen, GERMANY
Name and address of the manufacturer	Arnold & Richter Cine Technik GmbH & Co Betriebs KG Pulvermühle, 83071 Stephanskirchen, GERMANY
Name and address of the factory	Arnold & Richter Cine Technik GmbH & Co Betriebs KG Pulvermühle, 83071 Stephanskirchen, GERMANY
Ratings and principal characteristics	Rated power: Skypanel S30-X versions: max. 200 W (LED) Skypanel S60-X Versions: max. 400 W (LED) Skypanel S120-X versions: max. 400 W (LED) Skypanel S360-X Versions: max. 1500 W (LED) Protection class: III Degree of protection: IP20 Rated voltage: Skypanel S360-X: 54 V DC (= Input of electronic control gear) all other models: 48 V DC (= Input of electronic control gear) or 23 – 36 V DC (= battery input)
Trade mark (if any)	ARRI
Customer's Testing Facility (CTF) Stage used	CTF Stage 1
Model/type Ref.	Skypanel S30-X; Skypanel S60-X Skypanel S120-X; Skypanel S360-X Further Parameter see attachment.
Additional information (if necessary)	Certificate DE 3 - 2168 issued 2016-09-01 is replaced by this version due to technical changes.
A sample of the product was tested and found to be in conformity with	IEC 60598-2-17:2017 IEC 60598-1:2014 IEC 62471:2006
as shown in the Test Report Ref. No. which forms part of this certificate	028-713088431-100

This CB Test Certificate is issued by the National Certification Body
Ce Certificat d'essai OC est établi par l'Organisme **National de Certification**

Date, 2017-11-08
CB 17 10 13563 136



Christian Seidl



TÜV SÜD Product Service GmbH · Certification Body · Ridlerstrasse 65 · D-80339 München

Product Service

Additional to CB Certificate Ref.No.:

Where X can be any alphanumeric character or a combination of any alphanumeric characters or blank and describes the version of the LED luminaire.

For example:

X = C: (Color) - nominal color temperature: 2800 K – 10000 K + RGBW-light

X = D: (Daylight) - nominal color temperature: 5600 K

X = RP: (Remote Phosphor) - color temperature selection by changeable remote phosphor panels

X = T: (Tungsten) - nominal color temperature: 3200 K

National deviations for DE, AR, CN, NZ, AU, CA, ZA were considered.

Date, 2017-11-08
CB 17 10 13563 136


Christian Seidl



Product Service

TÜV Product Service GmbH • Certification Body • Ridlerstrasse 65 • D-80339 München