

## EARTHMAX SR 49 - Technische Daten



### Description

EARTHMAX SR 49 (L-4) ist ein All-Steel Radialreifen, der speziell für Radlader und Planierer, für Fahrlader (LHD) und flache Dumper entwickelt wurde. EARTHMAX SR 49 bietet hervorragende Leistung im harten Bergbaueinsatz, bei dem ausgezeichnete Traktion und Stabilität gefordert ist. Der Reifen hat ein richtungsgebundenes Muster und ist aus einer speziellen, schnittfesten Gummimischung, die erstklassige Beständigkeit bietet.

### UM

International Standard

### Construction

 RADIAL

### Machinery

OTR: Planierer • Fahrlader LHD • Radlader • flache Dumper

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	35/65 R 33
LI/SS	224 A2

## Dimensions International Standard

Overall Width (mm)	899
Overall Diameter (mm)	2061
Static Loaded Radius (mm)	890
Rolling Circumference (mm)	6125
Rim Rec	28.00/3.5
Rim Alt	--
Star Rating	**
TRA Code	L4

## Load capacity (Kg)

km/h / bar	5.25	5.50	5.75	6.00	6.25	6.50
10	23600	25000	25750	26500	27250	28000

Printed on 02.05.2024 15:15

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..